

PROJECTORS

Dart Maxi

Code  
1E4459EL

| LIGHT COLOUR         | LIGHT DISTRIBUTION | OUTPUT          |
|----------------------|--------------------|-----------------|
| 4000K<br>80          | NSP<br>5°          | 16.6W<br>1412lm |
| POWER SUPPLY CONTROL | COLOUR             |                 |
| 220-240Vac<br>ON-OFF | <div></div>        |                 |



The figures on the drawing are expressed in mm.



Technical Data

Concept

Professional adjustable LED projector.

Source

High efficiency Chip on Board LED Ra80.

|                         |                  |
|-------------------------|------------------|
| Energy efficiency class | E                |
| Nominal power           | 14W              |
| Nominal flux            | 1736lm           |
| Colour rendering index  | 80               |
| Rf                      | 84               |
| Rg                      | 93               |
| CCT nominal             | 4000K            |
| SDCM                    | 3                |
| Lifetime (L80/B10)      | 100000h tq +25°C |
| Lifetime (L90/B10)      | 72000h tq +25°C  |

TARGETTI

CCIAA Firenze  
Share Capital: € 500.000,00  
VAT N. (IT): 01537660480  
R.E.A: FI-275656

Targetti Sankey S.r.l.  
Via Giuseppe Garibaldi, 82  
50041 Calenzano (FI)  
Italy  
  
Tel: +39 055 37911  
targetti.com  
targetti@targetti.com

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.  
Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).  
  
We reserve the right to make technical changes.

## Technical Data

### Illuminotechnical characteristics

Optics with methacrylate precision lenses and diffusion filter.

|                        |                                   |
|------------------------|-----------------------------------|
| Optic                  | NSP                               |
| Beam angles            | NSP                               |
| Optical efficiency     | 81.36%                            |
| Fixture flux           | 1412lm                            |
| Luminous efficacy      | 85lm/W                            |
| Photobiological safety | Compliant with RG1 low risk group |

### Mechanical characteristics

Painted die-cast anodised aluminium body and painted stainless steel mounting bracket.  $\pm 45^\circ$  rotation on the horizontal plane and 0-180° on the vertical plane.

|                       |                     |
|-----------------------|---------------------|
| Colour and finish     | Ferrite             |
| Dimensions            | AxBxH 214x201x147mm |
| Weight                | 6.7Kg               |
| Degree of protection  | IP66                |
| Mechanical Resistance | IK10                |

### Electrical characteristics

Complete with electronic ON-OFF power supply. Pre-cabled with a 1.5m H07RN-F cable.

|                          |                                                                                                      |
|--------------------------|------------------------------------------------------------------------------------------------------|
| Fixture Power            | 16.6W                                                                                                |
| Power supply             | 220-240Vac 50/60Hz                                                                                   |
| Insulation Class         | CLASS 1                                                                                              |
| Type of driver / Control | ON-OFF                                                                                               |
| Driver included          | YES                                                                                                  |
| SAFE FLICKER             | PstLM=<1 and SVM=<0.4 (IEC TR 61547-1 and IEC TR 63158), to ensure a more comfortable and safe light |
| Ambient temperature      | -25°C / +35°C                                                                                        |

### Installation

Mounting bracket with aiming adjustability.

### Notes

Uses the "Waterblock Smart" technical solution that involves resin coating the connection cables, limiting the risk of humidity reaching the driver or the fixture. It is possible to subject the product to Cataphoresis treatment on request. 110-277Vac version available on request.

### Warranty

5 years.

### Warning

Luminaire designed for disposal/recycling at end-of-life. Replaceable (LED only) light source by a professional. Replaceable control gear by a professional.

# TARGETTI

CCIAA Firenze  
Share Capital: € 500.000,00  
VAT N. (IT): 01537660480  
R.E.A: FI-275656

Targetti Sankey S.r.l.  
Via Giuseppe Garibaldi, 82  
50041 Calenzano (FI)  
Italy

Tel: +39 055 37911  
targetti.com  
targetti@targetti.com

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.  
Luminous flux and power supply have +/-10% tolerances with respect to the indicated value.  $t_q +25^\circ\text{C}$  (CIE 121).

We reserve the right to make technical changes.

## Accessories

## Filter



## CODE

1E3094

Blade of light filter.  
PMMA holographic filter for a blade of light effect.  
To be completed with a dedicated holder ring.  
Diameter 168mm.

## Grid



## CODE

1E3096

## COLOUR



Anti-glare louver.  
The central elements may be removed to obtain two different levels of glare control.  
Powder coated stainless steel.

## Screen



## CODE

1E3095

## COLOUR



Asymmetric screen.  
Powder coated stainless steel.

## Mounting System



## CODE

1E3026

## COLOUR



Plate for fixture rotation.  
Powder coated stainless steel.



## CODE

1E3188

## COLOUR



## ØXH

150x352mm

Earthspike.  
Powder coated stainless steel.



## CODE

1E2825

## COLOUR



Pole bracket.  
Anodised and powder coated aluminium.  
Pole Ø 60mm (+/-2mm).

# TARGETTI

CCIAA Firenze  
Share Capital: € 500.000,00  
VAT N. (IT): 01537660480  
R.E.A: FI-275656

Targetti Sankey S.r.l.  
Via Giuseppe Garibaldi, 82  
50041 Calenzano (FI)  
Italy

Tel: +39 055 37911  
targetti.com  
targetti@targetti.com

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.  
Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.

## Accessories

## Mounting System



CODE

COLOUR

1E3097



Pole multiple mounting system.  
Powder coated stainless steel.  
To be completed with 1E2825.  
Max 4 projectors.



CODE

COLOUR

1E3187



Pole with base.  
Powder coated stainless steel.

## Holder Ring



CODE

COLOUR

1E3093



Holder ring.  
Powder coated stainless steel.  
Ax B 195x195mm.

## Tool



CODE

COLOUR

1E3098



Laser pointing system.  
Installed by friction on the projector's body.  
Powder coated stainless steel.  
Laser included.

## Connector



CODE

1E2769

Linear connection box IP66/IP68.  
5 poles max. wire section 1.5mm<sup>2</sup>.  
Cable diameter range from 7 to 12mm.



CODE

1E2494

Multiple connection box IP68.  
1 IN - 3 OUT 4 poles max. wire section 2.5mm<sup>2</sup>.  
Cable diameter range from 6 to 12mm.

# TARGETTI

CCIAA Firenze  
Share Capital: € 500.000,00  
VAT N. (IT): 01537660480  
R.E.A: FI-275656

Targetti Sankey S.r.l.  
Via Giuseppe Garibaldi, 82  
50041 Calenzano (FI)  
Italy

Tel: +39 055 37911  
targetti.com  
targetti@targetti.com

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.  
Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.

## Accessories

## Surge protector



## CODE

A013A

Surge protector compatible with CLASS I lighting fixtures.

Operating voltage 230-277Vac.

SPD type 2+3.

Max surge protection 10kV.

CLASS I

IP67

**TARGETTI**

CCIAA Firenze  
Share Capital: € 500.000,00  
VAT N. (IT): 01537660480  
R.E.A: FI-275656

Targetti Sankey S.r.l.  
Via Giuseppe Garibaldi, 82  
50041 Calenzano (FI)  
Italy

Tel: +39 055 37911  
targetti.com  
targetti@targetti.com

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.  
Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.