
TRACK PROJECTORS


Zeno 130



Code
T039FLL740DPW

LIGHT COLOUR	LIGHT DISTRIBUTION	OUTPUT
4000K 97	FL 36°	29.1W 2252lm

POWER SUPPLY CONTROL	COLOUR
220-240Vac DIMM ON BOARD	



The figures on the drawing are expressed in mm.





4000K		H(m)	D(m)	Emax(lx)
Ra97			36°	
Fixture Power	29W	1	0.64	6374
Source Flux	2791lm	2	1.28	1593
Fixture Flux	2252lm	3	1.92	708
Efficacy	77lm/W	4	2.57	398
Imax	6374cd	5	3.21	255

Technical Data

Concept

Professional adjustable LED projector.

Source

High efficiency Chip on Board LED Ra97.	
Energy efficiency class	E
Nominal power	26W
Nominal flux	2791lm
Colour rendering index	97
Rf	92
Rg	102
CCT nominal	4000K
Lifetime (L80/B10)	72000h tq +25°C
Lifetime (L90/B10)	72000h tq +25°C

TARGETTI

CCIAA Firenze
Share Capital: € 500.000,00
VAT N. (IT): 01537660480
R.E.A: FI-275656

Targetti Sankey S.r.l.
Via Giuseppe Garibaldi, 82
50041 Calenzano (FI)
Italy

Tel: +39 055 37911
targetti.com
targetti@targetti.com

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.
Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.

Technical Data

Illuminotechnical characteristics

Flood version with an optical grade PMMA TIR lens.

Optic	FL
Beam angles	FL
Optical efficiency	80.67%
Fixture flux	2252lm
Luminous efficacy	77lm/W
Photobiological safety	Compliant with RG1 low risk group

Mechanical characteristics

Die-cast painted aluminium optical unit. The optical unit can be adjusted from 0 to -90° on the vertical plane; and 355° on the horizontal plane with aiming blocking system.

Colour and finish	Plaster white
Dimensions	ØxH 134x85mm
Weight	0.95Kg
Degree of protection	IP20

Electrical characteristics

Electronic 1—10V driver with on-board dimmer integrated into the track adapter.

Fixture Power	29.1W
Power supply	220-240Vac 50/60Hz
Insulation Class	CLASS 2
Type of driver / Control	DIMM ON BOARD
Driver included	YES
Ambient temperature	0°C / +25°C

Installation

Electrified track mounting. Mechanical and optic accessories available, to be installed with holder ring (necessary).

Notes

110-277Vac version available on request.

Regulations and Certifications

CE

Warranty

5 years.

Warning


Luminaire designed for disposal/recycling at end-of-life. Replaceable (LED only) light source by a professional. Replaceable control gear by a professional.

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.
Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.

Accessories

Filter



CODE
1T6060

Blade of light filter.
Methacrylate holographic filter.
This makes the beam take on an oval shape and when combined with spotlights, the light blade appears more prominent.
To be completed with a dedicated holder ring.

It cannot be used with NSP and Wall Washer optics.

Grid



CODE	COLOUR
1T6061	●

Anti-glare louver.
Black lacquered aluminium honeycomb structure.
To be completed with a dedicated holder ring.

It cannot be used with NSP and Wall Washer optics.

Cut-off



CODE	COLOUR
1T6062	●

Black painted steel cut-off.
To be completed with a dedicated holder ring.

It cannot be used with NSP and Wall Washer optics.



CODE	COLOUR
1T6063	●

Black painted steel asymmetric cut-off.
To be completed with a dedicated holder ring.

It cannot be used with NSP and Wall Washer optics.

Ray Shade



CODE	COLOUR
1T6064	●

Adjustable barn doors flaps made of black painted steel.
To be completed with a dedicated holder ring.

They cannot be used with NSP and Wall Washer optics.

Holder Ring



CODE	COLOUR
1T6059	◯

Black painted aluminium accessory holder ring.

TARGETTI

CCIAA Firenze
Share Capital: € 500.000,00
VAT N. (IT): 01537660480
R.E.A: FI-275656

Targetti Sankey S.r.l.
Via Giuseppe Garibaldi, 82
50041 Calenzano (FI)
Italy

Tel: +39 055 37911
targetti.com
targetti@targetti.com

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.
Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.