
RECESSED LUMINAIRES | CEILING LUMINAIRES | PENDANT LUMINAIRES | WALL MOUNTED LUMINAIRES


Threesixty Ø 870mm

Code
1T6232DA90




LIGHT COLOUR	LIGHT DISTRIBUTION	OUTPUT
3000K 90	Opal+Halo	198W 12335lm

POWER SUPPLY CONTROL	COLOUR
220-240Vac DALI	



The figures on the drawing are expressed in mm.





3000K		H(m)	D(m)	Emax(lx)
Ra90			114°	
Fixture Power	198W	1	3.09	3912
Source Flux	19698lm	2	6.17	978
Fixture Flux	12335lm	3	9.26	435
Efficacy	62lm/W	4	12.35	244
Imax	3912cd	5	15.44	156

TS1524 Imax=199cd/klm

Technical Data

Concept

Circular LED fixture for ceiling, recessed, semi-recessed and wall mounted installations.

Source

The LED Engine is made up of self-cooling circular boards. Tunable White version available on request.

Energy efficiency class	E
Nominal power	176W
Nominal flux	19698lm
Colour rendering index	90
Rf	91.4
Rg	100.8
CCT nominal	3000K
Lifetime (L80/B10)	100000h tq +25°C
Lifetime (L90/B10)	59000h tq +25°C

TARGETTI

CCIAA Firenze
Share Capital: € 500.000,00
VAT N. (IT): 01537660480
R.E.A: FI-275656

Targetti Sankey S.r.l.
Via Giuseppe Garibaldi, 82
50041 Calenzano (FI)
Italy

Tel: +39 055 37911
targetti.com
targetti@targetti.com

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.
Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.

Technical Data

Illuminotechnical characteristics

OPAL Direct + HALO effect Version: High luminance transmission and light diffusion opaline polycarbonate lower diffusive screen. Small indirect light component for a backlit effect.

Emission	Direct/Indirect
Optic	Opal+Halo
Optical efficiency	62.62%
Fixture flux	12335lm
Luminous efficacy	62lm/W
Photobiological safety	Compliant with RG1 low risk group

Mechanical characteristics

Calendered extruded aluminium body.

Colour and finish	Deep black
Dimensions	ØxH 870x120mm
Weight	14Kg
Degree of protection	IP20 for recessed part
Degree of protection	IP40 for exposed part

Electrical characteristics

Integrated DALI power supply. Emergency Pack available on request. Equipped with a rapid connector for mains connection.

Fixture Power	198W
Power supply	220-240Vac 50/60Hz
Insulation Class	CLASS 1
Type of driver / Control	DALI
Driver included	YES
Ambient temperature	0°C / +25°C

Installation

Polycarbonate fixing system is pre-set for ceiling or wall mounted installations. Recessed installation is possible using a special accessory to be ordered separately.

Notes

Casambi control system available using a dedicated accessory. Check mounting instructions to verify the quantity of DALI drivers installed. 110-277Vac version available on request. Commissioning of the control system via free APP; the intervention of a specialist technician can be quoted on request.

Regulations and Certifications

CE

Warranty

5 years.

Warning

Luminaire designed for disposal/recycling at end-of-life. Replaceable (LED only) light source by a professional. Replaceable control gear by a professional.

TARGETTI

CCIAA Firenze
Share Capital: € 500.000,00
VAT N. (IT): 01537660480
R.E.A: FI-275656

Targetti Sankey S.r.l.
Via Giuseppe Garibaldi, 82
50041 Calenzano (FI)
Italy

Tel: +39 055 37911
targetti.com
targetti@targetti.com

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.
Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.

Accessories

Control systems



CODE

2T0131

IP20 Extender for wireless control of LED driver with dimming DALI (or 1-10V) interface based on Casambi technology.
It has a DALI2 output with the capacity to control up to 40 lighting fixtures.
With the addition of a further external BUS DALI power supply it is possible to control up to 64 fixtures.
IP20 Extender is preset to the DALI broadcast profile, meaning all the luminaires connected to it are dimmable at the same level.
In addition to the DALI broadcast other operating modes are available, such as:

- EXTENDER DALI 8CH
- EXTENDER DALI Tunable White
- EXTENDER 0/1-10V
- EXTENDER DALI 4CH
- EXTENDER DALI DT8 Tunable White

If different from the preset mode, the desired operating profile must be set directly by the user before coupling the extender to the Casambi network.
LxHxP=130x22x30mm.

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.
Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.