


## LIGHTING SYSTEMS

# Ivy Stem mounted projector

Code  
**1E4287CA**

| LIGHT COLOUR         | LIGHT DISTRIBUTION                                                                | OUTPUT        |
|----------------------|-----------------------------------------------------------------------------------|---------------|
| 3500K<br>90          | NSP<br>8°                                                                         | 4.2W<br>235lm |
| POWER SUPPLY CONTROL | COLOUR                                                                            |               |
| 48Vdc                |  |               |



The figures on the drawing are expressed in mm.



|  | 3500K                         | H(m)             | D(m)   | E <sub>max</sub> (lx) |      |     |
|--------------------------------------------------------------------------------------|-------------------------------|------------------|--------|-----------------------|------|-----|
|                                                                                      | Ra90                          |                  | 8°     |                       |      |     |
|                                                                                      | Fixture Power                 | 4W               | 1      | 0.13                  | 5789 |     |
|                                                                                      | Source Flux                   | 362lm            | 2      | 0.26                  | 1447 |     |
|                                                                                      | Fixture Flux                  | 235lm            | 3      | 0.39                  | 643  |     |
|                                                                                      | Efficacy                      | 56lm/W           | 4      | 0.53                  | 362  |     |
| TS1719                                                                               | I <sub>max</sub> =16015cd/klm | I <sub>max</sub> | 5789cd | 5                     | 0.66 | 232 |

## Technical Data

## Concept

Adjustable LED 1x light module with rigid suspension, powered at low voltage, to be installed into the installation profile.

## Source

Emitter Ra90.

|                         |                  |
|-------------------------|------------------|
| Energy efficiency class | F                |
| Nominal power           | 3.8W             |
| Nominal flux            | 362lm            |
| Colour rendering index  | 90               |
| Rf                      | 94               |
| Rg                      | 99               |
| CCT nominal             | 3500K            |
| Lifetime (L80/B10)      | 100000h tq +25°C |
| Lifetime (L90/B10)      | 100000h tq +25°C |

# TARGETTI

CCIAA Firenze  
Share Capital: € 500.000,00  
VAT N. (IT): 01537660480  
R.E.A: FI-275656

Targetti Sankey S.r.l.  
Via Giuseppe Garibaldi, 82  
50041 Calenzano (FI)  
Italy

Tel: +39 055 37911  
targetti.com  
targetti@targetti.com

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.  
Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.

## Technical Data

### Illuminotechnical characteristics

NSP beam. Optics made of a lens in optical grade PMMA and a holographic diffusion filter.

|                        |                                   |
|------------------------|-----------------------------------|
| Optic                  | NSP                               |
| Beam angles            | NSP                               |
| Optical efficiency     | 65.1%                             |
| Fixture flux           | 235lm                             |
| Luminous efficacy      | 56lm/W                            |
| Photobiological safety | Compliant with RG1 low risk group |

### Mechanical characteristics

Cylindrical aluminium body obtained through CNC machining process and protected with a layer of black anodization with a minimum thickness of 15μ. Powder painted Ferrite grey. Tempered extra clear front glass. Aluminium joint with locking system and rigid suspension in black anodized aluminium. Adjustability of the optical unit of 90° on the vertical plane (friction locking system) and 355° on the horizontal plane with the possibility of mechanical aiming locking through no tools system. Electronic components hosted inside a polymeric plastic box sealed by a silicone rubber gasket.

|                      |                    |
|----------------------|--------------------|
| Colour and finish    | Ferrite            |
| Dimensions           | AxBxH 148x60x652mm |
| Weight               | 0.52Kg             |
| Version              | CASAMBI            |
| Degree of protection | IP65               |

### Electrical characteristics

|                     |               |
|---------------------|---------------|
| Fixture Power       | 4.2W          |
| Power supply        | 48Vdc         |
| Insulation Class    | CLASS 3       |
| Ambient temperature | -25°C / +35°C |

### Installation

Fast connection system of the modules through anodized aluminium clips. Free positioning all over the installation profile according to installation needs with mechanical lock through Hex Key. Designed for connection in series through H05RN-F (0.15m + 0.15m) cable completed with male/female miniaturised IP65 connectors.

### Notes

Version with built-in Casambi control system (Casambi Ready). DALI control system available using a special accessory. Commissioning of the control system via free APP; the intervention of a specialist technician can be quoted on request.

### Warranty

5 years.

### Warning

Luminaire designed for disposal/recycling at end-of-life. Replaceable (LED only) light source by a professional. Replaceable control gear by a professional.

# TARGETTI

CCIAA Firenze  
Share Capital: € 500.000,00  
VAT N. (IT): 01537660480  
R.E.A: FI-275656

Targetti Sankey S.r.l.  
Via Giuseppe Garibaldi, 82  
50041 Calenzano (FI)  
Italy

Tel: +39 055 37911  
targetti.com  
targetti@targetti.com

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.  
Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.

## Related codes

## Power Supply



| CODE   | COLOUR | DRIVER |
|--------|--------|--------|
| 1E4169 | ●      | ON-OFF |

48Vdc driver box (IP65).

L=450mm 90W.

Equipped with connection cable H05RN-F (0.15m + 0.15m) complete with male/female IP65 connectors for 220V and miniaturized female IP65 connector for 48V.



| CODE   | COLOUR | DRIVER |
|--------|--------|--------|
| 1E4175 | ●      | ON-OFF |

48Vdc driver box (IP65).

L=450mm 150W.

Equipped with connection cable H05RN-F (0.15m + 0.15m) complete with male/female IP65 connectors for 220V and miniaturized female IP65 connector for 48V.



| CODE   | IP   | OUTPUT VOLTAGE | POWER SUPPLY | POWER | LXHXP       |
|--------|------|----------------|--------------|-------|-------------|
| 1E2320 | IP67 | 48Vdc          | 220-240Vac   | 70W   | 225x51x65mm |
| 1E2321 | IP67 | 48Vdc          | 220-240Vac   | 150W  | 225x51x65mm |

Electronic ON-OFF power supply.

Cable length 0.5m (IN and OUT).

To be completed with Connection kit 1E4184.



| CODE     | IP   | OUTPUT VOLTAGE | POWER SUPPLY | POWER | LXHXP       |
|----------|------|----------------|--------------|-------|-------------|
| 1T6917EL | IP20 | 48Vdc          | 220-240Vac   | 60W   | 225x36x60mm |
| 1T6916EL | IP20 | 48Vdc          | 220-240Vac   | 130W  | 240x49x60mm |

Electronic ON-OFF power supply.

To be completed with Connection kit 1E4184.

## Accessories

## Cable



| CODE   | L      |
|--------|--------|
| 1E4270 | 500mm  |
| 1E4181 | 1000mm |
| 1E4182 | 2000mm |
| 1E4183 | 3000mm |

Connection cable complete with male/female connectors.

# TARGETTI

CCIAA Firenze  
Share Capital: € 500.000,00  
VAT N. (IT): 01537660480  
R.E.A: FI-275656

Targetti Sankey S.r.l.  
Via Giuseppe Garibaldi, 82  
50041 Calenzano (FI)  
Italy

Tel: +39 055 37911  
targetti.com  
targetti@targetti.com

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.  
Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.

## Accessories

## Tool



## CODE

1E4171

Microscrewdriver with hexagonal head (diameter 0.9mm) for wiring 1E4184 connection kit.

## Connector



## CODE

1E4184

Connection kit 24/48V.

Wire not included.  
Maximum cable diameter 7.5mm.  
To be used for lengths >3m.



## CODE

1E2769

Linear connection box IP66/IP68.  
5 poles max. wire section 1.5mm<sup>2</sup>.  
Cable diameter range from 7 to 12mm.



## CODE

1E3184

IP68 4-way cable connector (5 pole).

## Control systems



## CODE

1T8173CA

Bridge DALI/Casambi: a fixture that allows fixtures equipped with mesh Bluetooth Casambi to interface with a traditional DALI system and to be adjusted by a DALI control unit. Inside the usual DALI circuit it is possible to have a maximum of 64 cabled DALI and Casambi wireless devices.

It only works with Casambi Evolution networks.

The DALI Bridge is transparent in the DALI system, and therefore does not require an address.

There is no need for a power supply given that it is supplied directly by the DALI bus.

To provide IP68 rating to the fixture complete with code 1E3184.

LxHxP=40.4x14x36.3mm.