PROJECTORS


# Jedi Nova 55 Projector Side Box 600

**Code**
**E0542GSL840ELBA**




| LIGHT COLOUR | LIGHT DISTRIBUTION | OUTPUT |
|---|---|---|
| 4000K<br>80 | Grazing SP<br>12° / 12° | 35W<br>3725lm |

| POWER SUPPLY CONTROL | COLOUR |
|---|---|
| 220-240Vac<br>ON-OFF | |




The figures on the drawing are expressed in mm.

3.2 IP66 IP67 IP68 IK07 CE




| 4000K | | H(m) | D(m) | Emax(lx) |
|---|---|---|---|---|
| Ra80 | | | 12° | |
| Fixture Power | 35W | 1 | 0.20 | 57247 |
| Source Flux | 4798lm | 2 | 0.41 | 14312 |
| Fixture Flux | 3725lm | 3 | 0.61 | 6361 |
| Efficacy | 106lm/W | 4 | 0.82 | 3578 |
| TS2098 Imax=11931cd/klm | Imax | 57247cd | 5 | 1.02 | 2290 |

## Technical Data

### Concept

Adjustable linear LED projector.

### Source

| | |
|---|---|
| High Power High Efficiency Ra80 linear LED board. | |
| Energy efficiency class | |
| Nominal power | 31.5 |
| Nominal flux | 4798lm |
| Colour rendering index | 80 |
| CCT nominal | 4000K |
| Lifetime (L80/B10) | 100000h tq +25°C |
| Lifetime (L90/B10) | 96000h tq +25°C |

TARGETTI

CCIAA Firenze
Share Capital: € 500.000,00
VAT N. (IT): 01537660480
R.E.A: FI-275656

Targetti Sankey S.r.l.
Via Giuseppe Garibaldi, 82
50041 Calenzano (FI)
Italy

Tel: +39 055 37911
targetti.com
targetti@targetti.com

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.
Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.

## Technical Data

### Illuminotechnical characteristics

Optic made of optical grade PMMA TIR lenses and a holographic filter.

| | |
|---|---|
| Optic | Grazing SP |
| Beam angles | GRZ 10°x10° |
| Optical efficiency | 77.63% |
| Fixture flux | 3725lm |
| Luminous efficacy | 106lm/W |
| Photobiological safety | Compliant with RG1 low risk group |

### Mechanical characteristics

Extruded anodised aluminium 15µ body. Extra clear 5mm thick glass flat screen. The body of the fixture is adjustable and can be installed away from the mounting surface using accessory snap brackets.

| | |
|---|---|
| Colour and finish | Black anodized |
| Dimensions | AxBxH 588x110x45mm |
| Weight | 3.2Kg |
| Version | Standard |
| Degree of protection | IP66,IP67,IP68 |
| Mechanical Resistance | IK07 |

### Electrical characteristics

Integrated driver available in the ON-OFF version (positioned laterally to the optical body). Supplied with through-wiring withlongitudinal sealing IN/OUT panel connectors (the sealing limits the risk of humidity raising towards the driver/optical body). Luminaire compliant with EN 60598-2-22 for power supply from a centralised emergency system CPSS (Central Power Supply System), not incorporated in the luminaire - high risk areas excluded. The default power and flux are 100% in AC and 100% in DC.

| | |
|---|---|
| Fixture Power | 35W |
| Power supply | 220-240Vac 50/60Hz |
| Insulation Class | CLASS 1 |
| Type of driver / Control | ON-OFF - PUSH |
| Driver included | YES |
| SAFE FLICKER | PstLM=<1 and SVM=<0.4 (IEC TR 61547-1 and IEC TR 63158), to ensure a more comfortable and safe light |
| Ambient temperature | -25°C / +35°C |

### Installation

To be completed with powder coated stainless steel fixed or adjustable brackets (available in different lengths).

### Notes

110-277Vac version available on request.

### Regulations and Certifications

CE

### Warranty

5 years.

## Technical Data

## Warning

Luminaire designed for disposal/recycling at end-of-life. Replaceable (LED only) light source by a professional. Replaceable control gear by a professional.

TARGETTI

CCIAA Firenze
Share Capital: € 500.000,00
VAT N. (IT): 01537660480
R.E.A: FI-275656

Targetti Sankey S.r.l.
Via Giuseppe Garibaldi, 82
50041 Calenzano (FI)
Italy

Tel: +39 055 37911
targetti.com
targetti@targetti.com

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.
Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.

## Related codes

### Bracket



| CODE | COLOUR |
|---|---|
| A108BT | ● |

Fixed bracket kit in powder-coatedstainless steel for surface installation (2 pieces).



| CODE | COLOUR | VERSION | L |
|---|---|---|---|
| A109BT | ● | Short | 57mm |

Adjustable bracket kit in powder-coated stainless steel for surface installation (2 pieces).
Rotation +/-90°.



| CODE | COLOUR | VERSION | L |
|---|---|---|---|
| A110BT | ● | Medium | 157mm |

Adjustable bracket kit in powder-coated stainless steel for surface installation (2 pieces).
Rotation +/-90°.



| CODE | COLOUR | VERSION | L |
|---|---|---|---|
| A111ZBT | ● | Long | 303mm |
| A111YBT | ● | Long | 453mm |
| A111XBT | ● | Long | 603mm |

Adjustable bracket kit in powder-coated stainless steel for surface installation (2 pieces).
Rotation +/-90°.

### Mounting System



| CODE | COLOUR | H |
|---|---|---|
| A112 | ● | 181mm |

Earthspike.
Powder coated stainless steel.
To be used with A108, A109, A110.

## Accessories

### Connector



| CODE |
|---|
| A117 |

IP66/IP68 female connector.
5 pôles (STANDARD 3G2,5mm² MAX, DALI 5G1,5mm² MAX).
Cable diameter range from 7 to 12mm.

TARGETTI

CCIAA Firenze
Share Capital: € 500.000,00
VAT N. (IT): 01537660480
R.E.A: FI-275656

Targetti Sankey S.r.l.
Via Giuseppe Garibaldi, 82
50041 Calenzano (FI)
Italy

Tel: +39 055 37911
targetti.com
targetti@targetti.com

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.
Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).


We reserve the right to make technical changes.



| CODE |
| --- |
| A118 |

Male/female IP66/IP68 connector kit.
5 pôles (STANDARD 3G2,5mm² MAX, DALI 5G1,5mm² MAX).
Cable diameter range from 7 to 12mm.

## Cable



| CODE | L |
| --- | --- |
| A120Z | 1000mm |
| A120Y | 2000mm |
| A120X | 3000mm |

Connection cable.
Complete with 5 pole connectors.
For the ON-OFF and DALI version.

## Grid



| CODE | COLOUR | L |
| --- | --- | --- |
| A146X | ● | 585mm |

Symmetric anti-glare grid in black painted aluminium.
Externally mounted.



| CODE | COLOUR | L |
| --- | --- | --- |
| A147X | ● | 585mm |

Asymmetric anti-glare grid in black painted aluminium.
Externally mounted.

## Ray Shade



| CODE | COLOUR | L |
| --- | --- | --- |
| A148XBA | ● | 588mm |

Decorative and anti-glare shield in painted aluminium.
Version for Standard and Side Box projectors.



Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.
Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.