

PROYECTORES

Jedi Nova 55
Proyector 900

Código
E0523GWL827ELFW

TEMPERATURA DE COLOR	DISTRIBUCIÓN LUMINOSA	OUTPUT
2700K 80	Grazing 11° / 59°	52.4W 5019lm
ALIMENTACIÓN CONTROL	COLOR	
220-240Vac ON-OFF		



Los datos mostrados en el dibujo están expresados en mm.



The diagram shows a light beam with a beam spread of 120°. The beam diameter at 1m is 0.19m, and at 2m it is 0.37m. The beam diameter at 3m is 0.56m, and at 4m it is 0.74m. The beam diameter at 5m is 0.93m. The beam diameter at 6m is 1.14m, and at 7m it is 1.41m. The beam diameter at 8m is 1.68m, and at 9m it is 1.95m. The beam diameter at 10m is 2.22m, and at 11m it is 2.49m. The beam diameter at 12m is 2.76m, and at 13m it is 3.03m. The beam diameter at 14m is 3.30m, and at 15m it is 3.57m. The beam diameter at 16m is 3.84m, and at 17m it is 4.11m. The beam diameter at 18m is 4.38m, and at 19m it is 4.65m. The beam diameter at 20m is 4.92m, and at 21m it is 5.19m. The beam diameter at 22m is 5.43m, and at 23m it is 5.67m. The beam diameter at 24m is 5.94m, and at 25m it is 6.15m. The beam diameter at 26m is 6.46m, and at 27m it is 6.63m. The beam diameter at 28m is 6.98m, and at 29m it is 7.11m. The beam diameter at 30m is 7.40m, and at 31m it is 7.59m. The beam diameter at 32m is 7.92m, and at 33m it is 8.07m. The beam diameter at 34m is 8.24m, and at 35m it is 8.55m. The beam diameter at 36m is 8.76m, and at 37m it is 9.03m. The beam diameter at 38m is 9.08m, and at 39m it is 9.51m. The beam diameter at 40m is 9.40m, and at 41m it is 9.99m. The beam diameter at 42m is 9.72m, and at 43m it is 10.47m. The beam diameter at 44m is 10.04m, and at 45m it is 10.95m. The beam diameter at 46m is 10.36m, and at 47m it is 11.43m. The beam diameter at 48m is 10.68m, and at 49m it is 11.91m. The beam diameter at 50m is 11.00m, and at 51m it is 12.39m. The beam diameter at 52m is 11.32m, and at 53m it is 12.87m. The beam diameter at 54m is 11.64m, and at 55m it is 13.35m. The beam diameter at 56m is 11.96m, and at 57m it is 13.83m. The beam diameter at 58m is 12.28m, and at 59m it is 14.31m. The beam diameter at 60m is 12.60m, and at 61m it is 14.79m. The beam diameter at 62m is 12.92m, and at 63m it is 15.27m. The beam diameter at 64m is 13.24m, and at 65m it is 15.75m. The beam diameter at 66m is 13.56m, and at 67m it is 16.23m. The beam diameter at 68m is 13.88m, and at 69m it is 16.71m. The beam diameter at 70m is 14.20m, and at 71m it is 17.19m. The beam diameter at 72m is 14.52m, and at 73m it is 17.67m. The beam diameter at 74m is 14.84m, and at 75m it is 18.15m. The beam diameter at 76m is 15.16m, and at 77m it is 18.63m. The beam diameter at 78m is 15.48m, and at 79m it is 19.11m. The beam diameter at 80m is 15.80m, and at 81m it is 19.59m. The beam diameter at 82m is 16.12m, and at 83m it is 20.07m. The beam diameter at 84m is 16.44m, and at 85m it is 20.55m. The beam diameter at 86m is 16.76m, and at 87m it is 21.03m. The beam diameter at 88m is 17.08m, and at 89m it is 21.51m. The beam diameter at 90m is 17.40m, and at 91m it is 21.99m. The beam diameter at 92m is 17.72m, and at 93m it is 22.47m. The beam diameter at 94m is 18.04m, and at 95m it is 22.95m. The beam diameter at 96m is 18.36m, and at 97m it is 23.43m. The beam diameter at 98m is 18.68m, and at 99m it is 23.91m. The beam diameter at 100m is 19.00m, and at 101m it is 24.39m. The beam diameter at 102m is 19.32m, and at 103m it is 24.87m. The beam diameter at 104m is 19.64m, and at 105m it is 25.35m. The beam diameter at 106m is 19.96m, and at 107m it is 25.83m. The beam diameter at 108m is 20.28m, and at 109m it is 26.31m. The beam diameter at 110m is 20.60m, and at 111m it is 26.79m. The beam diameter at 112m is 20.92m, and at 113m it is 27.27m. The beam diameter at 114m is 21.24m, and at 115m it is 27.75m. The beam diameter at 116m is 21.56m, and at 117m it is 28.23m. The beam diameter at 118m is 21.88m, and at 119m it is 28.71m. The beam diameter at 120m is 22.20m, and at 121m it is 29.19m. The beam diameter at 122m is 22.52m, and at 123m it is 29.67m. The beam diameter at 124m is 22.84m, and at 125m it is 30.15m. The beam diameter at 126m is 23.16m, and at 127m it is 30.63m. The beam diameter at 128m is 23.48m, and at 129m it is 31.11m. The beam diameter at 130m is 23.80m, and at 131m it is 31.59m. The beam diameter at 132m is 24.12m, and at 133m it is 32.07m. The beam diameter at 134m is 24.44m, and at 135m it is 32.55m. The beam diameter at 136m is 24.76m, and at 137m it is 33.03m. The beam diameter at 138m is 25.08m, and at 139m it is 33.51m. The beam diameter at 140m is 25.40m, and at 141m it is 33.99m. The beam diameter at 142m is 25.72m, and at 143m it is 34.47m. The beam diameter at 144m is 26.04m, and at 145m it is 34.95m. The beam diameter at 146m is 26.36m, and at 147m it is 35.43m. The beam diameter at 148m is 26.68m, and at 149m it is 35.91m. The beam diameter at 150m is 27.00m, and at 151m it is 36.39m. The beam diameter at 152m is 27.32m, and at 153m it is 36.87m. The beam diameter at 154m is 27.64m, and at 155m it is 37.35m. The beam diameter at 156m is 27.96m, and at 157m it is 37.83m. The beam diameter at 158m is 28.28m, and at 159m it is 38.31m. The beam diameter at 160m is 28.60m, and at 161m it is 38.79m. The beam diameter at 162m is 28.92m, and at 163m it is 39.27m. The beam diameter at 164m is 29.24m, and at 165m it is 39.75m. The beam diameter at 166m is 29.56m, and at 167m it is 40.23m. The beam diameter at 168m is 29.88m, and at 169m it is 40.71m. The beam diameter at 170m is 30.20m, and at 171m it is 41.19m. The beam diameter at 172m is 30.52m, and at 173m it is 41.67m. The beam diameter at 174m is 30.84m, and at 175m it is 42.15m. The beam diameter at 176m is 31.16m, and at 177m it is 42.63m. The beam diameter at 178m is 31.48m, and at 179m it is 43.11m. The beam diameter at 180m is 31.80m, and at 181m it is 43.59m. The beam diameter at 182m is 32.12m, and at 183m it is 44.07m. The beam diameter at 184m is 32.44m, and at 185m it is 44.55m. The beam diameter at 186m is 32.76m, and at 187m it is 45.03m. The beam diameter at 188m is 33.08m, and at 189m it is 45.51m. The beam diameter at 190m is 33.40m, and at 191m it is 45.99m. The beam diameter at 192m is 33.72m, and at 193m it is 46.47m. The beam diameter at 194m is 34.04m, and at 195m it is 46.95m. The beam diameter at 196m is 34.36m, and at 197m it is 47.43m. The beam diameter at 198m is 34.68m, and at 199m it is 47.91m. The beam diameter at 200m is 35.00m, and at 201m it is 48.39m. The beam diameter at 202m is 35.32m, and at 203m it is 48.87m. The beam diameter at 204m is 35.64m, and at 205m it is 49.35m. The beam diameter at 206m is 35.96m, and at 207m it is 49.83m. The beam diameter at 208m is 36.28m, and at 209m it is 50.31m. The beam diameter at 210m is 36.60m, and at 211m it is 50.79m. The beam diameter at 212m is 36.92m, and at 213m it is 51.27m. The beam diameter at 214m is 37.24m, and at 215m it is 51.75m. The beam diameter at 216m is 37.56m, and at 217m it is 52.23m. The beam diameter at 218m is 37.88m, and at 219m it is 52.71m. The beam diameter at 220m is 38.20m, and at 221m it is 53.19m. The beam diameter at 222m is 38.52m, and at 223m it is 53.67m. The beam diameter at 224m is 38.84m, and at 225m it is 54.15m. The beam diameter at 226m is 39.16m, and at 227m it is 54.63m. The beam diameter at 228m is 39.48m, and at 229m it is 55.11m. The beam diameter at 230m is 39.80m, and at 231m it is 55.59m. The beam diameter at 232m is 40.12m, and at 233m it is 56.07m. The beam diameter at 234m is 40.44m, and at 235m it is 56.55m. The beam diameter at 236m is 40.76m, and at 237m it is 57.03m. The beam diameter at 238m is 41.08m, and at 239m it is 57.51m. The beam diameter at 240m is 41.40m, and at 241m it is 57.99m. The beam diameter at 242m is 41.72m, and at 243m it is 58.47m. The beam diameter at 244m is 42.04m, and at 245m it is 58.95m. The beam diameter at 246m is 42.36m, and at 247m it is 59.43m. The beam diameter at 248m is 42.68m, and at 249m it is 59.91m. The beam diameter at 250m is 43.00m, and at 251m it is 60.39m. The beam diameter at 252m is 43.32m, and at 253m it is 60.87m. The beam diameter at 254m is 43.64m, and at 255m it is 61.35m. The beam diameter at 256m is 43.96m, and at 257m it is 61.83m. The beam diameter at 258m is 44.28m, and at 259m it is 62.31m. The beam diameter at 260m is 44.60m, and at 261m it is 62.79m. The beam diameter at 262m is 44.92m, and at 263m it is 63.27m. The beam diameter at 264m is 45.24m, and at 265m it is 63.75m. The beam diameter at 266m is 45.56m, and at 267m it is 64.23m. The beam diameter at 268m is 45.88m, and at 269m it is 64.71m. The beam diameter at 270m is 46.20m, and at 271m it is 65.19m. The beam diameter at 272m is 46.52m, and at 273m it is 65.67m. The beam diameter at 274m is 46.84m, and at 275m it is 66.15m. The beam diameter at 276m is 47.16m, and at 277m it is 66.63m. The beam diameter at 278m is 47.48m, and at 279m it is 67.11m. The beam diameter at 280m is 47.80m, and at 281m it is 67.59m. The beam diameter at 282m is 48.12m, and at 283m it is 68.07m. The beam diameter at 284m is 48.44m, and at 285m it is 68.55m. The beam diameter at 286m is 48.76m, and at 287m it is 69.03m. The beam diameter at 288m is 49.08m, and at 289m it is 69.51m. The beam diameter at 290m is 49.40m, and at 291m it is 69.99m. The beam diameter at 292m is 49.72m, and at 293m it is 70.47m. The beam diameter at 294m is 50.04m, and at 295m it is 70.95m. The beam diameter at 296m is 50.36m, and at 297m it is 71.43m. The beam diameter at 298m is 50.68m, and at 299m it is 71.91m. The beam diameter at 300m is 51.00m, and at 301m it is 72.39m. The beam diameter at 302m is 51.32m, and at 303m it is 72.87m. The beam diameter at 304m is 51.64m, and at 305m it is 73.35m. The beam diameter at 306m is 51.96m, and at 307m it is 73.83m. The beam diameter at 308m is 52.28m, and at 309m it is 74.31m. The beam diameter at 310m is 52.60m, and at 311m it is 74.79m. The beam diameter at 312m is 52.92m, and at 313m it is 75.27m. The beam diameter at 314m is 53.24m, and at 315m it is 75.75m. The beam diameter at 316m is 53.56m, and at 317m it is 76.23m. The beam diameter at 318m is 53.88m, and at 319m it is 76.71m. The beam diameter at 320m is 54.20m, and at 321m it is 77.19m. The beam diameter at 322m is 54.52m, and at 323m it is 77.67m. The beam diameter at 324m is 54.84m, and at 325m it is 78.15m. The beam diameter at 326m is 55.16m, and at 327m it is 78.63m. The beam diameter at 328m is 55.48m, and at 329m it is 79.11m. The beam diameter at 330m is 55.80m, and at 331m it is 79.59m. The beam diameter at 332m is 56.12m, and at 333m it is 80.07m. The beam diameter at 334m is 56.44m, and at 335m it is 80.55m. The beam diameter at 336m is 56.76m, and at 337m it is 81.03m. The beam diameter at 338m is 57.08m, and at 339m it is 81.51m. The beam diameter at 340m is 57.40m, and at 341m it is 81.99m. The beam diameter at 342m is 57.72m, and at 343m it is 82.47m. The beam diameter at 344m is 58.04m, and at 345m it is 82.95m. The beam diameter at 346m is 58.36m, and at 347m it is 83.43m. The beam diameter at 348m is 58.68m, and at 349m it is 83.91m. The beam diameter at 350m is 59.00m, and at 351m it is 84.39m. The beam diameter at 352m is 59.32m, and at 353m it is 84.87m. The beam diameter at 354m is 59.64m, and at 355m it is 85.35m. The beam diameter at 356m is 59.96m, and at 357m it is 85.83m. The beam diameter at 358m is 60.28m, and at 359m it is 86.31m. The beam diameter at 360m is 60.60m, and at 361m it is 86.79m. The beam diameter at 362m is 60.92m, and at 363m it is 87.27m. The beam diameter at 364m is 61.24m, and at 365m it is 87.75m. The beam diameter at 366m is 61.56m, and at 367m it is 88.23m. The beam diameter at 368m is 61.88m, and at 369m it is 88.71m. The beam diameter at 370m is 62.20m, and at 371m it is 89.19m. The beam diameter at 372m is 62.52m, and at 373m it is 89.67m. The beam diameter at 374m is 62.84m, and at 375m it is 90.15m. The beam diameter at 376m is 63.16m, and at 377m it is 90.63m. The beam diameter at 378m is 63.48m, and at 379m it is 91.11m. The beam diameter at 380m is 63.80m, and at 381m it is 91.59m. The beam diameter at 382m is 64.12m, and at 383m it is 92.07m. The beam diameter at 384m is 64.44m, and at 385m it is 92.55m. The beam diameter at 386m is 64.76m, and at 387m it is 93.03m. The beam diameter at 388m is 65.08m, and at 389m it is 93.51m. The beam diameter at 390m is 65.40m, and at 391m it is 93.99m. The beam diameter at 392m is 65.72m, and at 393m it is 94.47m. The beam diameter at 394m is 66.04m, and at 395m it is 94.95m. The beam diameter at 396m is 66.36m, and at 397m it is 95.43m. The beam diameter at 398m is 66.68m, and at 399m it is 95.91m. The beam diameter at 400m is 67.00m, and at 401m it is 96.39m. The beam diameter at 402m is 67.32m, and at 403m it is 96.87m. The beam diameter at 404m is 67.64m, and at 405m it is 97.35m. The beam diameter at 406m is 67.96m, and at 407m it is 97.83m. The beam diameter at 408m is 68.28m, and at 409m it is 98.31m. The beam diameter at 410m is 68.60m, and at 411m it is 98.79m. The beam diameter at 412m is 68.92m, and at 413m it is 99.27m. The beam diameter at 414m is 69.24m, and at 415m it is 99.75m. The beam diameter at 416m is 69.56m, and at 417m it is 100.23m. The beam diameter at 418m is 69.88m, and at 419m it is 100.71m. The beam diameter at 420m is 70.20m, and at 421m it is 101.19m. The beam diameter at 422m is 70.52m, and at 423m it is 101.67m. The beam diameter at 424m is 70.84m, and at 425m it is 102.15m. The beam diameter at 426m is 71.16m, and at 427m it is 102.63m. The beam diameter at 428m is 71.48m, and at 429m it is 103.11m. The beam diameter at 430m is 71.80m, and at 431m it is 103.59m. The beam diameter at 432m is 72.12m, and at 433m it is 104.07m. The beam diameter at 434m is 72.44m, and at 435m it is 104.55m. The beam diameter at 436m is 72.76m, and at 437m it is 105.03m. The beam diameter at 438m is 73.08m, and at 439m it is 105.51m. The beam diameter at 440m is 73.40m, and at 441m it is 105.99m. The beam diameter at 442m is 73.72m, and at 443m it is 106.47m. The beam diameter at 444m is 74.04m, and at 445m it is 106.95m. The beam diameter at 446m is 74.36m, and at 447m it is 107.43m. The beam diameter at 448m is 74.68m, and at 449m it is 107.91m. The beam diameter at 450m is 75.00m, and at 451m it is 108.39m. The beam diameter at 452m is 75.32m, and at 453m it is 108.87m. The beam diameter at 454m is 75.64m, and at 455m it is 109.35m. The beam diameter at 456m is 75.96m, and at 457m it is 109.83m. The beam diameter at 458m is 76.28m, and at 459m it is 110.31m. The beam diameter at 460m is 76.60m, and at 461m it is 110.79m. The beam diameter at 462m is 76.92m, and at 463m it is 111.27m. The beam diameter at 464m is 77.24m, and at 465m it is 111.75m. The beam diameter at 466m is 77.56m, and at 467m it is 112.23m. The beam diameter at 468m is 77.88m, and at 469m it is 112.71m. The beam diameter at 470m is 78.20m, and at 471m it is 113.19m. The beam diameter at 472m is 78.52m, and at 473m it is 113.67m. The beam diameter at 474m is 78.84m, and at 475m it is 114.15m. The beam diameter at 476m is 79.16m, and at 477m it is 114.63m. The beam diameter at 478m is 79.48m, and at 479m it is 115.11m. The beam diameter at 480m is 79.80m, and at 481m it is 115.59m. The beam diameter at 482m is 80.12m, and at 483m it is 116.07m. The beam diameter at 484m is 80.44m, and at 485m it is 116.55m. The beam diameter at 486m is 80.76m, and at 487m it is 117.03m. The beam diameter at 488m is 81.08m, and at 489m it is 117.51m. The beam diameter at 490m is 81.40m, and at 491m it is 117.99m. The beam diameter at 492m is 81.72m, and at 493m it is 118.47m. The beam diameter at 494m is 82.04m, and at 495m it is 118.95m. The beam diameter at 496m is 82.36m, and at 497m it is 119.43m. The beam diameter at 498m is 82.68m, and at 499m it is 119.91m. The beam diameter at 500m is 83.00m, and at 501m it is 120.39m. The beam diameter at 502m is 83.32m, and at 503m it is 120.87m. The beam diameter at 504m is 83.64m, and at 505m it is 121.35m. The beam diameter at 506m is 83.96m, and at 507m it is 121.83m. The beam diameter at 508m is 84.28m, and at 509m it is 122.31m. The beam diameter at 510m is 84.60m, and at 511m it is 122.79m. The beam diameter at 512m is 84.92m, and at 513m it is 123.27m. The beam diameter at 514m is 85.24m, and at 515m it is 123.75m. The beam diameter at 516m is 85.56m, and at 517m it is 124.23m. The beam diameter at 518m is 85.88m, and at 519m it is 124.71m. The beam diameter at 520m is 86.20m, and at 521m it is 125.19m. The beam diameter at 522m is 86.52m, and at 523m it is 125.67m. The beam diameter at 524m is 86.84m, and at 525m it is 126.15m. The beam diameter at 526m is 87.16m, and at 527m it is 126.63m. The beam diameter at 528m is 87.48m, and at 529m it is 127.11m. The beam diameter at 530m is 87.80m, and at 531m it is 127.59m. The beam diameter at 532m is 88.12m, and at 533m it is 128.07m. The beam diameter at 534m is 88.44m, and at 535m it is 128.55m. The beam diameter at 536m is 88.76m, and at 537m it is 129.03m. The beam diameter at 538m is 89.08m, and at 539m it is 129.51m. The beam diameter at 540m is 89.40m, and at 541m it is 130.00m. The beam diameter at 542m is 89.72m, and at 543m it is 130.48m. The beam diameter at 544m is 90.04m, and at 545m it is 130.96m. The beam diameter at 546m is 90.36m, and at 547m it is 131.44m. The beam diameter at 548m is 90.68m, and at 549m it is 131.92m. The beam diameter at 550m is 91.00m, and at 551m it is 132.40m. The beam diameter at 552m is 91.32m, and at 553m it is 132.88m. The beam diameter at 554m is 91.64m, and at 555m it is 133.36m. The beam diameter at 556m is 91.96m, and at 557m it is 133.84m. The beam diameter at 558m is 92.28m, and at 559m it is 134.32m. The beam diameter at 560m is 92.60m, and at 561m it is 134.80m. The beam diameter at 562m is 92.92m, and at 563m it is 135.28m. The beam diameter at 564m is 93.24m, and at 565m it is 135.76m. The beam diameter at 566m is 93.56m, and at 567m it is 136.24m. The beam diameter at 568m is 93.88m, and at 569m it is 136.72m. The beam diameter at 570m is 94.20m, and at 571m it is 137.20m. The beam diameter at 572m is 94.52m, and at 573m it is 137.68m. The beam diameter at 574m is 94.84m, and at 575m it is 138.16m. The beam diameter at 576m is 95.16m, and at 577m it is 138.64m. The beam diameter at 578m is 95.48m, and at 579m it is 139.12m. The beam diameter at 580m is 95.80m, and at 581m it is 139.60m. The beam diameter at 582m is 96.12m, and at 583m it is 140.08m. The beam diameter at 584m is 96.44m, and at 585m it is 140.56m. The beam diameter at 586m is 96.76m, and at 587m it is 141.04m. The beam diameter at 588m is 97.08m, and at 589m it is 141.52m. The beam diameter at 590m is 97.40m, and at 591m it is 142.00m. The beam diameter at 592m is 97.72m, and at 593m it is 142.48m. The beam diameter at 594m is 98.04m, and at 595m it is 142.96m. The beam diameter at 596m is 98.36m, and at 597m it is 143.44m. The beam diameter at 598m is 98.68m, and at 599m it is 143.92m. The beam diameter at 600m is 99.00m, and at 601m it is 144.40m. The beam diameter at 602m is 99.32m, and at 603m it is 144.88m. The beam diameter at 604m is 99.64m, and at 605m it is 145.36m. The beam diameter at 606m is 99.96m, and at 607m it is 145.84m. The beam diameter at 608m is 100.28m, and at 609m it is 146.32m. The beam diameter at 610m is 100.60m, and at 611m it is 146.80m. The beam diameter at 612m is 100.92m, and at 613m it is 147.28m. The beam diameter at 614m is 101.24m, and at 615m it is 147.76m. The beam diameter at 616m is 101.56m, and at 617m it is 148.24m. The beam diameter at 618m is 101.88m, and at 619m it is 148.72m. The beam diameter at 620m is 102.20m, and at 621m it is 149.20m. The beam diameter at 622m is 102.52m, and at 623m it is 149.68m. The beam diameter at 624m is 102.84m, and at 625m it is 150.16m. The beam diameter at 626m is 103.16m, and at 627m it is 150.64m. The beam diameter at 628m is 103.48m, and at 629m it is 151.12m. The beam diameter at 630m is 103.80m, and at 631m it is 151.60m. The beam diameter at 632m is 104.12m, and at 633m it is 152.08m. The beam diameter at 634m is 104.44m, and at 635m it is 152.56m. The beam diameter at 636m is 104.76m, and at 637m it is 153.04m. The beam diameter at 638m is 105.08m, and at 639m it is 153.52m. The beam diameter at 640m is 105.40m, and at 641m it is 154.00m. The beam diameter at 642m is 105.72m, and at 643m it is 154.48m. The beam diameter at 644m is 106.04m, and at 645m it is 154.96m. The beam diameter at 646m is 106.36m, and at 647m it is 155.44m. The beam diameter at 648m is 106.68m, and at 649m it is 155.92m. The beam diameter at 650m is 107.00m, and at 651m it is 156.40m. The beam diameter at 652m is 107.32m, and at 653m it is 156.88m. The beam diameter at 654m is 107.64m, and at 655m it is 157.36m. The beam diameter at 656m is 107.96m, and at 657m it is 157.84m. The beam diameter at 658m is 108.28m, and at 659m it is 158.32m. The beam diameter at 660m is 108.60m, and at 661m it is 158.80m. The beam diameter at 662m is 108.92m, and at 663m it is 159.28m. The beam diameter at 664m is 109.24m, and at 665m it is 159.76m. The beam diameter at 666m is 109.56m, and at 667m it is 160.24m. The beam diameter at 668m is 109.88m, and at 669m it is 160.72m. The beam diameter at 670m is 110.20m, and at 671m it is 161.20m. The beam diameter at 672m is 110.52m, and at 673m it is 161.68m. The beam diameter at 674m is 110.84m, and at 675m it is 162.16m. The beam diameter at 676m is 111.16m, and at 677m it is 162.64m. The beam diameter at 678m is 111.48m, and at 679m it is 163.12m. The beam diameter at 680m is 111.80m, and at 681m it is 163.60m. The beam diameter at 682m is 112.12m, and at 683m it is 164.08m. The beam diameter at 684m is 112.44m, and at 685m it is 164.56m. The beam diameter at 686m is 112.76m, and at 687m it is 165.04m. The beam diameter at 688m is 113.08m, and at 689m it is 165.52m. The beam diameter at 690m is 113.40m, and at 691m it is 166.00m. The beam diameter at 692m is 113.72m, and at 693m it is 166.48m. The beam diameter at 694m is 114.04m, and at 695m it is 166.96m. The beam diameter at 696m is 114.36m, and at 697m it is 167.44m. The beam diameter at 698m is 114.68m, and at 699m it is 167.92m. The beam diameter at 700m is 115.00m, and at 701m it is 168.40m. The beam diameter at 702m is 115.32m, and at 703m it is 168.88m. The beam

Datos técnicos

Concept

Proyector lineal orientable de LED.

Lámpara

Tarjetas lineales LED High Power High Efficiency Ra80.

Clase de eficiencia energética

Potencia nominal	47.2
Flujo nominal	6669lm
Índice de reproducción cromática	80
CCT nominal	2700K
Duración útil (L80/B10)	100000h tq +25°C
Duración útil (L90/B10)	96000h tq +25°C

TARGETTI

CCIAA Firenze
Capital Social: € 500.000,00
NIF (IT): 01537660480
R.E.A: FI-275656

Targetti Sankey S.r.l.
Via Giuseppe Garibaldi, 82
50041 Calenzano (FI)
Italy

Tel: +39 055 37911
targetti.com
targetti@targetti.com

En función de la continua evolución tecnológica de los componentes electrónicos, los datos indicados están sujetos a actualización por lo que es necesario solicitar confirmación al hacer el pedido.
El flujo luminoso y la potencia eléctrica presentan tolerancias +/-10% respecto al valor indicado. tq +25°C (CIE 121).

Nos reservamos el derecho de realizar cambios técnicos.

Datos técnicos

Características luminotécnicas

óptica compuesta por lentes TIR de PMMA de grado óptico y filtro holográfico.	
Óptica	Grazing
Apertura del haz de luz	GRZ 10°x60°
Eficiencia óptica	75,26%
Flujo luminaria	5019lm
Rendimiento luminoso	96lm/W
Seguridad fotobiológica	Conforme al grupo de riesgo RG1 (Riesgo Bajo)

Características mecánicas

Cuerpo de aluminio extruido anodizado 15μ. Pantalla plana de cristal extra claro de 5mm de espesor. Cuerpo de la luminaria orientable respecto a la superficie de instalación mediante estribos accesorios.	
Color y acabado	Blanco florentino
Dimensiones	AxBxH 868x55x90mm
Peso	4,4Kg
Versión	Standard
Grado de protección	IP66,IP67,IP68
Resistencia mecánica	IK07

Características eléctricas

Driver integrado, en la versión ON-OFF (posicionado debajo del cuerpo óptico). Equipado con cableado pasante con conectores IN/OUT para instalación de panel con sellado longitudinal (el sellado limita el riesgo de ascenso de la humedad hacia el driver / cuerpo óptico). Luminaria compatible con EN 60598-2-22 para suministro de energía desde un sistema de emergencia centralizado CPSS (Central Power Supply System), no incorporado en la luminaria - áreas de alto riesgo excluidas. La potencia y el flujo predeterminados son 100% en CA y 100% en CC.	
Potencia luminaria	52,4W
Alimentación	220-240Vac 50/60Hz
Clase de aislamiento	CLASE 1
Tipo driver / Control	ON-OFF - PUSH
Driver incluido	SÍ
SAFE FLICKER	PstLM=<1 e SVM=<0,4 (IEC TR 61547-1 e IEC TR 63158), garantizando una luz más cómoda y segura
Temperatura ambiente	-25°C / +35°C

Instalación

A completar con estribos de fijación fijos u orientables de acero inoxidable pintado con pintura en polvo (disponible en diferentes longitudes).

Notas

Disponible bajo petición la versión 110-277Vac.

Garantía

5 años.

Datos técnicos

Advertencias

Luminaria diseñada para su eliminación/reciclaje al final de su vida útil. Fuente luminosa reemplazable (solo LED) por un profesional. Equipo de control reemplazable por un profesional.

TARGETTI

CCIAA Florencia
Capital Social: € 500.000,00
NIF (IT): 01537660480
R.E.A: FI-275656

Targetti Sankey S.r.l.
Via Giuseppe Garibaldi, 82
50041 Calenzano (FI)
Italy

Tel: +39 055 37911
targetti.com
targetti@targetti.com

En función de la continua evolución tecnológica de los componentes electrónicos, los datos indicados están sujetos a actualización por lo que es necesario solicitar confirmación al hacer el pedido.
El flujo luminoso y la potencia eléctrica presentan tolerancias +/-10% respecto al valor indicado, tq +25°C (CIE 121).

Nos reservamos el derecho de realizar cambios técnicos.

Códigos para completar

Estribo



CÓDIGO	COLOR
A108BT	

Kit estribos fijo en acero inoxidable, pintado en polvo para instalación en superficie (2 unidades).



CÓDIGO	COLOR	VERSIÓN	L
A109FW		Corta	57mm

Kit estribos orientable en acero inoxidable, pintado en polvo para instalación en superficie (2 unidades).
Rotación +/-90°.



CÓDIGO	COLOR	VERSIÓN	L
A110FW		Mediana	157mm

Kit estribos orientable en acero inoxidable, pintado en polvo para instalación en superficie (2 unidades).
Rotación +/-90°.



CÓDIGO	COLOR	VERSIÓN	L
A111ZFW		Larga	303mm
A111YFW		Larga	453mm
A111XFW		Larga	603mm

Kit estribos orientable en acero inoxidable, pintado en polvo para instalación en superficie (2 unidades).
Rotación +/-90°.

Sistema de fijación



CÓDIGO	COLOR	H
A112		181mm

Piqueta para terreno.
Acero inoxidable pintado con pintura en polvo.
Para uso con A108, A109, A110.

Accesorios

Conector



CÓDIGO
A117

Conector hembra IP66/IP68.
5 polos (STANDARD 3G2,5mm² MAX, DALI 5G1,5mm² MAX).
Diámetro del cable de 7 a 12mm.

Accesorios

Conector



CÓDIGO

A118

kit de conectores IP66/IP68 macho/hembra.
5 polos (STANDARD 3G2,5mm² MAX, DALI 5G1,5mm² MAX).
Diámetro del cable de 7 a 12mm.



CÓDIGO

A119

Caja de conexión múltiple IP68.
1 IN - 2 OUT 5 polos (STANDARD 3G2,5mm² MAX, DALI 5G1,5mm² MAX).
Diámetro del cable de 7 a 12mm.

Cable



CÓDIGO

L

A120Z 1000mm

A120Y 2000mm

A120X 3000mm

Cable de conexión.
Equipado con conectores 5 polos.
Para versión ON-OFF y DALI.

Rejilla



CÓDIGO

COLOR

L

A146Y ● 865mm

Griglia antiabbagliamento simmetrica in alluminio verniciato nero.
Installazione esterna al prodotto.



CÓDIGO

COLOR

L

A147Y ● 865mm

Griglia antiabbagliamento asimmetrica in alluminio verniciato nero.
Installazione esterna al prodotto.

Parasol



CÓDIGO

COLOR


L

A148YFW ● 868mm

Paraluce estetico e antiabbagliamento in alluminio verniciato.
Versione per proiettore standard e side box.

Accesorios

Parasol



CÓDIGO	COLOR	L
A156YFW		868mm

Paraluce estetico e antiabbagliamento in alluminio verniciato.
Versione per proiettore standard.