
WALL MOUNTED LUMINAIRES


Hall



Code
1T4499CA90


LIGHT COLOUR	LIGHT DISTRIBUTION	OUTPUT
3000K 90	Asymmetrical	40W 3722lm

POWER SUPPLY CONTROL	COLOUR
220-240Vac CASAMBI	



The figures on the drawing are expressed in mm.





3000K		H(m)	D1(m)	D2(m)	Emax(lx)
Ra90			121°	89°	
Fixture Power	40W	1	3.52	4.23	1396
Source Flux	4314lm	2	7.04	8.47	349
Fixture Flux	3722lm	3	10.56	12.70	155
Efficacy	93lm/W	4	14.08	16.93	87
Imax	2099cd	5	17.60	21.17	56

Technical Data

Concept

Wall mounted fixture with indirect light emission for LED sources.

Source

Linear Low Power High Efficiency LED board Ra90.	
Energy efficiency class	E
Nominal power	36W
Nominal flux	4314lm
Colour rendering index	90
Rf	91.4
Rg	100.8
CCT nominal	3000K
Lifetime (L80/B10)	100000h tq +25°C
Lifetime (L90/B10)	59000h tq +25°C

TARGETTI

CCIAA Firenze
Share Capital: € 500.000,00
VAT N. (IT): 01537660480
R.E.A: FI-275656

Targetti Sankey S.r.l.
Via Giuseppe Garibaldi, 82
50041 Calenzano (FI)
Italy

Tel: +39 055 37911
targetti.com
targetti@targetti.com

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.
Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.

Technical Data

Illuminotechnical characteristics

A high reflectance anodised aluminium reflector.

Emission	Indirect
Optic	Asymmetrical
Optical efficiency	86.28%
Fixture flux	3722lm
Luminous efficacy	93lm/W
Photobiological safety	Compliant with RG1 low risk group

Mechanical characteristics

Painted metal body. Diffusive protective screen.

Colour and finish	Florentine white
Dimensions	AxBxH 297x330x110mm
Weight	3.6Kg
Degree of protection	IP20

Electrical characteristics

Casambi control system included in the LOF version. Luminaire compliant with EN 60598-2-22 for power supply from a centralised emergency system CPSS (Central Power Supply System), not incorporated in the luminaire - high risk areas excluded. The default power and flux are 100% in AC and 100% in DC.

Fixture Power	40W
Power supply	220-240Vac 50/60Hz
Insulation Class	CLASS 1
Type of driver / Control	CASAMBI
Driver included	YES
SAFE FLICKER	PstLM=<1 and SVM=<0.4 (IEC TR 61547-1 and IEC TR 63158), to ensure a more comfortable and safe light
Ambient temperature	0°C / +25°C

Notes

Design Daniel Bernard. Commissioning of the control system via free APP; the intervention of a specialist technician can be quoted on request.

Regulations and Certifications

CE

Warranty

5 years.

Warning

Luminaire designed for disposal/recycling at end-of-life. Replaceable (LED only) light source by a professional. Replaceable control gear by a professional.