


## IN-GROUND LUMINAIRES

## Keplero 280 Zoom

Code

E013ZMH827ELCSS

| LIGHT COLOUR         | LIGHT DISTRIBUTION                                                                | OUTPUT               |
|----------------------|-----------------------------------------------------------------------------------|----------------------|
| 2700K<br>80          | Multioptic Zoom<br>19°, 26°, 43°, 64°                                             | 35.3W<br>1707-2960lm |
| POWER SUPPLY CONTROL | COLOUR                                                                            |                      |
| 220-240Vac<br>ON-OFF |  |                      |



The figures on the drawing are expressed in mm.

The fixture's photometric values  
can be found on the following pages

## Technical Data

## Concept

Adjustable recessed professional projector equipped with LED sources and variable beam openings.

## Source

High efficiency Chip on Board LED Ra80. 3500K colour temperature available on request.

|                         |                 |
|-------------------------|-----------------|
| Energy efficiency class | E               |
| Nominal power           | 30W             |
| Nominal flux            | 4662lm          |
| Colour rendering index  | 80              |
| Rf                      | 82              |
| Rg                      | 96              |
| CCT nominal             | 2700K           |
| Lifetime (L80/B10)      | 72000h tq +25°C |
| Lifetime (L90/B10)      | 72000h tq +25°C |

**TARGETTI**

CCIAA Firenze  
Share Capital: € 500.000,00  
VAT N. (IT): 01537660480  
R.E.A: FI-275656

Targetti Sankey S.r.l.  
Via Giuseppe Garibaldi, 82  
50041 Calenzano (FI)  
Italy

Tel: +39 055 37911  
targetti.com  
targetti@targetti.com

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.  
Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.

## Technical Data

### Illuminotechnical characteristics

A patented hybrid lens/reflector Zoom optical system with the possibility of sliding and locking on the vertical axis in four positions for as many beam openings. Beam adjustability up to 20° on the vertical plane and 360° on the horizontal plane obtained by rototranslation of the optical group, with double aim locking system. Optic group pre-set for the installation of one or more dedicated optical accessories to be ordered separately.

|                        |                                   |
|------------------------|-----------------------------------|
| Optic                  | Multioptic Zoom                   |
| Beam angles            | SP, FL, MWFL, WFL                 |
| Optical efficiency     | See photometries                  |
| Fixture flux           | See photometries                  |
| Luminous efficacy      | See photometries                  |
| Photobiological safety | Compliant with RG1 low risk group |

### Mechanical characteristics

Die-cast aluminium body with 3 layers of protection: anodised, cataphoresis and black paint. Brushed stainless steel (AISI 316) ultra flat decorative ring with bevelled edge (natural finish). Version with extra-clear protective glass. Anti theft stainless steel A4 Torx screws.

|                       |                         |
|-----------------------|-------------------------|
| Colour and finish     | Brushed stainless steel |
| Dimensions            | ØxH 280x202mm           |
| Weight                | 5.25Kg                  |
| Version               | Extra-clear glass       |
| Degree of protection  | IP66,IP67,IP68          |
| Mechanical Resistance | IK10                    |

### Electrical characteristics

Integrated IP68 ON-OFF electronic power supply equipped with IP68 waterproof connectors set for connection to the mains with a H07RN8-F (max2x2.5mm<sup>2</sup>) cable. Fixture with a pass-through line.

|                          |                                                                                                      |
|--------------------------|------------------------------------------------------------------------------------------------------|
| Fixture Power            | 35.3W                                                                                                |
| Power supply             | 220-240Vac 50/60Hz                                                                                   |
| Insulation Class         | CLASS 2                                                                                              |
| Type of driver / Control | ON-OFF                                                                                               |
| Driver included          | YES                                                                                                  |
| SAFE FLICKER             | PstLM=<1 and SVM=<0.4 (IEC TR 61547-1 and IEC TR 63158), to ensure a more comfortable and safe light |
| Ambient temperature      | -25°C / +35°C                                                                                        |

### Installation

Nylon installation sleeve to be ordered separately as an accessory. The sleeve is pre-set for both flush or straight edge installation. 20kN resistance to static load.

### Notes

All light fixtures must be completed with an installation sleeve. IP68: the projector is not suitable for permanent underwater installation but can withstand temporary accidental immersion to a depth of 2 metres (max.24h). All versions of the KEPLERO family meet all the requirements of EN 60598-2-13 standard regarding drive-over and walk-over performances. Low temperatures on the glass make them suitable even for installation in "special areas", such as spaces for children. Uses the "Waterblock Plus" technical solution that involves resin coating the connection cables and completely resin coating the integrated driver limiting the risk of humidity reaching the fixture. 110-277Vac version available on request.

# TARGETTI

CCIAA Firenze  
Share Capital: € 500.000,00  
VAT N. (IT): 01537660480  
R.E.A: FI-275656

Targetti Sankey S.r.l.  
Via Giuseppe Garibaldi, 82  
50041 Calenzano (FI)  
Italy

Tel: +39 055 37911  
targetti.com  
targetti@targetti.com

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.  
Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.

## Technical Data

## Warning

Luminaire designed for disposal/recycling at end-of-life. Replaceable (LED only) light source by a professional.  
Replaceable control gear by a professional.

# TARGETTI

CCIAA Firenze  
Share Capital: € 500.000,00  
VAT N. (IT): 01537660480  
R.E.A: FI-275656

Targetti Sankey S.r.l.  
Via Giuseppe Garibaldi, 82  
50041 Calenzano (FI)  
Italy

Tel: +39 055 37911  
targetti.com  
targetti@targetti.com

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.  
Luminous flux and power supply have +/-10% tolerances with respect to the indicated value.  $t_q +25^{\circ}\text{C}$  (CIE 121).

We reserve the right to make technical changes.

Photometries

SP

Fixture flux


1707lm

Luminous efficacy

48lm/W

Optical efficiency

36.62%



|               |                              |                  |                    |
|---------------|------------------------------|------------------|--------------------|
| 2700K         | H(m)                         | D(m)             | Emax(lx)           |
| Ra80          |                              | 19°              |                    |
| Fixture Power | 35W                          | 1                | 0.34 11742         |
| Source Flux   | 4662lm                       | 2                | 0.67 2935          |
| Fixture Flux  | 1707lm                       | 3                | 1.01 1305          |
| Efficacy      | 48lm/W                       | 4                | 1.34 734           |
| TS782         | I <sub>max</sub> =2519cd/klm | I <sub>max</sub> | 11742cd 5 1.68 470 |

FL

Fixture flux


2259lm

Luminous efficacy

64lm/W

Optical efficiency

48.46%



|               |                              |                  |                   |
|---------------|------------------------------|------------------|-------------------|
| 2700K         | H(m)                         | D(m)             | Emax(lx)          |
| Ra80          |                              | 26°              |                   |
| Fixture Power | 35W                          | 1                | 0.46 8134         |
| Source Flux   | 4662lm                       | 2                | 0.93 2034         |
| Fixture Flux  | 2259lm                       | 3                | 1.39 904          |
| Efficacy      | 64lm/W                       | 4                | 1.86 508          |
| TS781         | I <sub>max</sub> =1745cd/klm | I <sub>max</sub> | 8134cd 5 2.32 325 |

MWFL

Fixture flux


2823lm

Luminous efficacy

80lm/W

Optical efficiency

60.55%



|               |                              |                  |                   |
|---------------|------------------------------|------------------|-------------------|
| 2700K         | H(m)                         | D(m)             | Emax(lx)          |
| Ra80          |                              | 43°              |                   |
| Fixture Power | 35W                          | 1                | 0.78 4692         |
| Source Flux   | 4662lm                       | 2                | 1.56 1173         |
| Fixture Flux  | 2823lm                       | 3                | 2.34 521          |
| Efficacy      | 80lm/W                       | 4                | 3.12 293          |
| TS780         | I <sub>max</sub> =1006cd/klm | I <sub>max</sub> | 4692cd 5 3.90 188 |

WFL

Fixture flux


2960lm

Luminous efficacy

84lm/W

Optical efficiency

63.5%



|               |                             |                  |                   |
|---------------|-----------------------------|------------------|-------------------|
| 2700K         | H(m)                        | D(m)             | Emax(lx)          |
| Ra80          |                             | 64°              |                   |
| Fixture Power | 35W                         | 1                | 1.25 2792         |
| Source Flux   | 4662lm                      | 2                | 2.50 698          |
| Fixture Flux  | 2960lm                      | 3                | 3.75 310          |
| Efficacy      | 84lm/W                      | 4                | 5.00 174          |
| TS779         | I <sub>max</sub> =599cd/klm | I <sub>max</sub> | 2792cd 5 6.25 112 |

## Related codes

## Sleeve



## CODE

1E2394

Grey nylon installation sleeve.  
The sleeve is pre-set for both flush or straight edge installation.  
Complete with dedicated cover cap for installations in concrete.  
Flush ring Ø 286 H.225.  
Straight edge ring Ø 271 H. 223.

## Accessories

## Filter



## CODE

1T1696

## Ø

101mm

Flat striped glass blade light refractive filter.  
This makes the beam take on an oval shape and when combined with spotlights, the light blade appears more prominent.

## Grid



## CODE


1T1699

## Ø

101mm

Anti-glare louver.  
Black painted metal honeycomb structure.

## Shutter



## CODE

1E2402

## COLOUR



Half-moon shutter.

## Tool



## CODE

1E2496

Metal handle for fixture removal



## CODE

1E2495

Features TORX HEAD, TX 30.

## Accessories

## Tool



## CODE

1E0388

Sucker tool to raise the glass.

## Connector



## CODE

1E2769

Linear connection box IP66/IP68.  
5 poles max. wire section 1.5mm<sup>2</sup>.  
Cable diameter range from 7 to 12mm.



## CODE

1E2494

Multiple connection box IP68.  
1 IN - 3 OUT 4 poles max. wire section 2.5mm<sup>2</sup>.  
Cable diameter range from 6 to 12mm.

## Surge protector



## CODE

A013B

Surge protector compatible with CLASS II lighting fixtures and electronic drivers.  
Operating voltage 220-240Vac.  
SPD type 2+3.  
Max surge protection 10kV.  
CLASS II  
IP67

# TARGETTI

CCIAA Firenze  
Share Capital: € 500.000,00  
VAT N. (IT): 01537660480  
R.E.A: FI-275656

Targetti Sankey S.r.l.  
Via Giuseppe Garibaldi, 82  
50041 Calenzano (FI)  
Italy

Tel: +39 055 37911  
targetti.com  
targetti@targetti.com

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.  
Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.