CEILING LUMINAIRES | PENDANT LUMINAIRES


# Logico Easy Stand Alone 57 - Opal HO - Emergency

**Code**
**T020BY840ELPW**




| LIGHT COLOUR | LIGHT DISTRIBUTION | OUTPUT |
|---|---|---|
| 4000K<br>80 | Opal | 63W<br>6298lm |

| POWER SUPPLY CONTROL | COLOUR |
|---|---|
| 220-240Vac<br>ON-OFF<br>(EMERGENCY VERSION) | ◯ |




**The figures on the drawing are expressed in mm.**




G0300A Imax=190cd/klm

| 4000K | | H(m) | D(m) | Emax(lx) |
|---|---|---|---|---|
| Ra80 | | | 111° | |
| Fixture Power | 63W | 1 | 2.90 | 1041 |
| Source Flux | 6298lm | 2 | 5.80 | 260 |
| Fixture Flux | 6298lm | 3 | 8.70 | 116 |
| Efficacy | 100lm/W | 4 | 11.60 | 65 |
| Imax | 1200cd | 5 | 14.49 | 42 |

## Technical Data

### Concept

Linear stand alone LED fixture for ceiling mounted or suspension installation. Emergency version.

### Source

| | |
|---|---|
| LED Engine made of linear LED boards Ra80. | |
| Energy efficiency class | D |
| Nominal power | 55W |
| Nominal flux | 6298lm |
| Colour rendering index | 80 |
| Rf | 84 |
| Rg | 95 |
| CCT nominal | 4000K |
| Lifetime (L80/B10) | 100000h tq +25°C |
| Lifetime (L90/B10) | 50000h tq +25°C |

TARGETTI

CCIAA Firenze
Share Capital: € 500.000,00
VAT N. (IT): 01537660480
R.E.A: FI-275656

Targetti Sankey S.r.l.
Via Giuseppe Garibaldi, 82
50041 Calenzano (FI)
Italy

Tel: +39 055 37911
targetti.com
targetti@targetti.com

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.
Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.

## Technical Data

### Illuminotechnical characteristics

Direct/indirect emission. Diffused light - OPAL High Output optic: optical system made of a steel reflector with white polymer coating and a closing diffuser screen in opal anti-glare polycarbonate.

| | |
|---|---|
| Emission | Direct/Indirect |
| Optic | Opal |
| Optical efficiency | 100% |
| Fixture flux | 6298lm |
| Emergency fixture flux BLF | 13% |
| Luminous efficacy | 100lm/W |
| Photobiological safety | Compliant with RG0 exempt risk group |

### Mechanical characteristics

Painted extruded aluminium body with 57mm section and polycarbonate end caps. Upper closing screen in translucent polycarbonate.

| | |
|---|---|
| Colour and finish | White |
| Dimensions | AxBxH 1462x57x80mm |
| Weight | 4.15Kg |
| Version | Linear |
| Degree of protection | IP40 |
| Mechanical Resistance | IK02 |

### Electrical characteristics

Integrated electronic ON-OFF driver. Equipped with emergency pack - permanent emergency (1h autonomy and 24h recharge).

| | |
|---|---|
| Fixture Power | 63W |
| Power supply | 220-240Vac 50/60Hz |
| Insulation Class | CLASS 1 |
| Type of driver / Control | ON-OFF (EMERGENCY VERSION) |
| Driver included | YES |
| SAFE FLICKER | PstLM=<1 and SVM=<0.4 (IEC TR 61547-1 and IEC TR 63158), to ensure a more comfortable and safe light |
| Ambient temperature | 0°C / +25°C |
| Relative humidity UR | <85% |

### Installation

To be completed with mounting systems for surface or suspended application.

### Notes

Commissioning of the control system via free APP; the intervention of a specialist technician can be quoted on request.

### Regulations and Certifications

CE

## Technical Data

### Warranty

5 years.

### Warning

Luminaire designed for disposal/recycling at end-of-life. Replaceable (LED only) light source by a professional. Replaceable control gear by a professional.

TARGETTI

CCIAA Firenze
Share Capital: € 500.000,00
VAT N. (IT): 01537660480
R.E.A: FI-275656

Targetti Sankey S.r.l.
Via Giuseppe Garibaldi, 82
50041 Calenzano (FI)
Italy

Tel: +39 055 37911
targetti.com
targetti@targetti.com

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.
Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.

## Accessories

### Canopy



| CODE | COLOUR |
|---|---|
| A004W | ◯ |

Canopy with 5 poles terminal block.
Feeding cable not included.

### Bracket



| CODE |
|---|
| A007M |

Bracket with adjustment system for suspended installation (2 pieces).
Two brackets needed for each lighting module.

For LOGICO EASY 57.

### Suspension



| CODE | VERSION |
|---|---|
| A008T | L=6m |
| A008U | L=5m |
| A008V | L=4m |
| A008W | L=3m |
| A008X | L=2m |
| A008Y | L=1m |
| A008Z | L=0,5m |

Suspension cable (2 pieces).

TARGETTI

CCIAA Firenze
Share Capital: € 500.000,00
VAT N. (IT): 01537660480
R.E.A: FI-275656

Targetti Sankey S.r.l.
Via Giuseppe Garibaldi, 82
50041 Calenzano (FI)
Italy

Tel: +39 055 37911
targetti.com
targetti@targetti.com

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.
Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.