

Ceiling and Wall

HOCKEY



TARGETTI

HOCKEY

GENERAL INFO

Applique, ceiling mounted
Ø179mm

LED

LED board.
From 1533lm to 1632lm
3000K – 4000K
Ra80

PRODUCT EFFICACY

Unitil 109lm/W

OPTICS

VWFL

POWER SUPPLY

Electronic

MATERIAL

Die-cast ferrite colour
anodised aluminium
body. LED plate with
micro-prismatic diffuser in
transparent PMMA.

ON DEMAND



Easy Custom Colour



Cataphoresis
treatment

A compact fixture with a simple design with two different installation types- ceiling and wall mounted for direct light- that makes this a flexible tool in the hands of lighting designers.

In the wall mounted version the cast aluminium bracket echoes the fixture's rounded shape becoming part of its design.

On request it is possible to subject the product to “Cataphoresis” treatment making it suitable to be installed near the sea (up to 5 metres) or in saline environment or in the presence of corrosive agents.

The entire range uses the “Waterblock Smart” technical solution that involves resin coating the connection cables limiting the risk of humidity reaching the driver or the fixture.




Outdoor

HOCKEY




Wall



LED / 13W / VWFL								
	3000K	H(m)	D(m)	E _{max} (lx)	Driver	Colour	3000K	4000K
	Ra80		84°		EL.		1E2909	1E2910
	Fixture Power	15W	1	1.80	839			
	Source Flux	1533lm	2	3.60	210			
	Fixture Flux	1534lm	3	5.40	93			
	Efficacy	102lm/W	4	7.20	52			
EV328	I _{max} =548cd/klm	I _{max}	840cd	5	9.00	34		



Ceiling



LED / 13W / VWFL								
	3000K	H(m)	D(m)	E _{max} (lx)	Driver	Colour	3000K	4000K
	Ra80		84°		EL.		1E2911	1E2912
	Fixture Power	15W	1	1.80	839			
	Source Flux	1533lm	2	3.60	210			
	Fixture Flux	1534lm	3	5.40	93			
	Efficacy	102lm/W	4	7.20	52			
EV328	I _{max} =548cd/klm	I _{max}	840cd	5	9.00	34		

Requisites and information

All fixtures of the Targetti collection have been designed and produced to comply with European Standard EN60598-1 relative to the safety requisite of light fixtures.



All fixtures comply with the following directives:

- EMC Directive 2014/30/EU
- LV Directive 2014/35/EU
- RoHS Directive 2011/65/EU

Unless specified otherwise

- all fixtures are supplied without lamps;
- all fixtures are sold separately;
- all measurements are expressed in millimeters;
- all fixtures at low voltage are supplied without transformer;
- For products in Class III performance is only guaranteed using the electronic power supplies and drivers indicated in the catalogue.

Consorzio ecolight

Targetti Sankey Spa is a member of the Ecolight consortium that was set up in 2004 (D.Lgs. 49/2014) to comply with the provisions of the European Directive that was adopted in Italy as the European Directive 2012/19/EU for WEEE on managing, recovering and treating waste electrical and electronic equipment, used batteries and accumulators in compliance with all applicable legislation.

The colors of the products illustrated are reproduced as faithfully as possible compatibly with the technical limitations of the printed medium. The company reserves the right to make changes to the production without notice. Reproduction of this catalogue or any part of it is prohibited. The products illustrated in this catalogue are covered by one or more Italian or international patents. The company will take legal action against any imitators.



TARGETTI SANKEY SpA

Certificated ISO 9001 n° 9130. TAR1
Certificated ISO 14001 n° IT319206

The Enec mark, ISO9001 and ISO14001 certifications and the CE marking all guarantee that the activities carried out internally in the company are governed and controlled by procedures which assure constant level of quality.

Accredited laboratory in accordance with ISO 17025.

Light beam apertures

from	to	beam	
5°	10°	Narrow Spot	NSP
11°	25°	Spot	SP
26°	40°	Flood	FL
41°	50°	Medium Wide Flood	MWFL
51°	70°	Wide Flood	WFL
71°	120°	Very Wide Flood	VWFL
		Wall Washer	WW
		Narrow Asymmetric	N. ASYM
		Asymmetric	ASYM

Icons legend

	Class I luminaire in which the protection against electrical shock is guaranteed by the connections of the conductive elements accessible to a protective conductor (earth connection).
	Luminaire in which the connection to a protective conductor (earth connection) guarantees the immunity to radio noises.
	Class II luminaire (double insulation), protected against the accidental contact with parts under tension from the user.
	Class III luminaire, suitable for connection to very low voltage circuits.
	Solid particle and liquid ingress protection degree.
	Protection degree - Recessed part . Protection degree - Exposed part.
	Impact protection degree.
	ENEC European Norms Electrical Certification.

Particular symbols

	Weight of the single fixture.
	Cable length.
	Walk-over.
	Driver-over safe.
	Fixtures that have parameters below the minimum visibility threshold $PstLM \leq 1$ and $SVM \leq 0.4$ (IEC TR 61547-1 and IEC TR 63158).
DBS	Dynamic Beam Shaper optical technology with remote management of the beam opening.
	LED with $Ra_{__}$ where not present in the catalogue, available on request.
	Different colour temperatures available on request.
	Custom finish of your choice from the Targetti Colours range and RAL indicated in the colour chart can be downloaded on line from the download section.
	Treatment carried out on request.
	Supplied on request with an integrated or remote 110-277Vac power supply as indicated for the standard model.
	LED version with a different "Tunable White" tone available on request.

Note

- ➔ Please contact us for on demand treatments and versions.
- ➔ The performances reported on the products refer to the use of the recommended drivers.
- ➔ The drivers selected by Targetti make the fixtures "Safe Flicker".

