LIGHTING SYSTEMS


# Oz Lighting module - Single fixed - 25x25mm

**Code**
**1T7516**




| LIGHT COLOUR | LIGHT DISTRIBUTION | OUTPUT |
|---|---|---|
| 3500K<br>90 | MWFL<br>41° | 2.8W<br>147lm |

| POWER SUPPLY CONTROL | COLOUR |
|---|---|
| 48Vdc | |




The figures on the drawing are expressed in mm.

0.04 IP20 CE




| 3500K | | H(m) | D(m) | Emax(lx) |
|---|---|---|---|---|
| Ra90 | | | 41° | |
| Fixture Power | 3W | 1 | 0.75 | 264 |
| Source Flux | 203lm | 2 | 1.50 | 66 |
| Fixture Flux | 147lm | 3 | 2.26 | 29 |
| Efficacy | 52lm/W | 4 | 3.01 | 16 |
| Imax | 264cd | 5 | 3.76 | 11 |

## Technical Data

### Concept

Fixed magnetic LED light module, powered at low voltage.

### Source

| | |
|---|---|
| Hugh efficiency Ra90 LED Emitter. | |
| Energy efficiency class | F |
| Nominal power | 2,1W |
| Nominal flux | 203lm |
| Colour rendering index | 90 |
| Rf | 91.4 |
| Rg | 103.9 |
| CCT nominal | 3500K |
| SDCM | 2 |
| Lifetime (L80/B10) | 100000h tq +25°C |
| Lifetime (L90/B10) | 72000h tq +25°C |

TARGETTI

CCIAA Firenze
Share Capital: € 500.000,00
VAT N. (IT): 01537660480
R.E.A: FI-275656

Targetti Sankey S.r.l.
Via Giuseppe Garibaldi, 82
50041 Calenzano (FI)
Italy

Tel: +39 055 37911
targetti.com
targetti@targetti.com

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.
Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.

## Technical Data

### Illuminotechnical characteristics

The medium wide flood optical system has acrylic lenses and a black polycarbonate frame. The light is suitable for installation in work environments UGR<19 (EN12464-1).

| | |
|---|---|
| Optic | MWFL |
| Beam angles | MWFL |
| Optical efficiency | 72.2% |
| Fixture flux | 147lm |
| Luminous efficacy | 52lm/W |
| Photobiological safety | Compliant with RG1 low risk group |

### Mechanical characteristics

White painted die-cast aluminium body. Fixed light, 25x25mm.

| | |
|---|---|
| Colour and finish | Plaster white |
| Dimensions | AxBxH 25x25x50mm |
| Weight | 0.042Kg |
| Version | Fixed - ON-OFF |
| Degree of protection | IP20 |

### Electrical characteristics

| | |
|---|---|
| Fixture Power | 2.8W |
| Power supply | 48Vdc |
| Insulation Class | CLASS 3 |
| Ambient temperature | 0°C / +25°C |

### Installation

Extremely rapid, versatile and simple mechanical and electrical coupling system using magnets which support the fixture on the Power Track and feed power inside the fixture on all versions.

### Notes

110-277Vac version available on request.

### Regulations and Certifications

CE

### Warranty

5 years.

### Warning

Luminaire designed for disposal/recycling at end-of-life. Replaceable (LED only) light source by a professional. Replaceable control gear by a professional.