


TRACK PROJECTORS

Ray 75 Reflector

Code

T035FLR940ELPW

| LIGHT COLOUR         | LIGHT DISTRIBUTION                                                                | OUTPUT          |
|----------------------|-----------------------------------------------------------------------------------|-----------------|
| 4000K<br>90          | FL<br>31°                                                                         | 24.7W<br>2190lm |
| POWER SUPPLY CONTROL | COLOUR                                                                            |                 |
| 220-240Vac<br>ON-OFF |  |                 |



The figures on the drawing are expressed in mm.



Technical Data

Concept

Professional adjustable LED projector.

Source

High efficiency Chip on Board LED Ra90. Ra97 on request.

|                         |                 |
|-------------------------|-----------------|
| Energy efficiency class | E               |
| Nominal power           | 21W             |
| Nominal flux            | 2833lm          |
| Colour rendering index  | 90              |
| R <sub>f</sub>          | 90              |
| R <sub>g</sub>          | 98              |
| CCT nominal             | 4000K           |
| Lifetime (L80/B10)      | 72000h tq +25°C |
| Lifetime (L90/B10)      | 72000h tq +25°C |

TARGETTI

CCIAA Firenze  
Share Capital: € 500.000,00  
VAT N. (IT): 01537660480  
R.E.A: FI-275656

Targetti Sankey S.r.l.  
Via Giuseppe Garibaldi, 82  
50041 Calenzano (FI)  
Italy  
  
Tel: +39 055 37911  
targetti.com  
targetti@targetti.com

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.  
Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).  
  
We reserve the right to make technical changes.

## Technical Data

### Illuminotechnical characteristics

Reflector with ellipsoidal facets in reflective anodised aluminium. Interchangeable reflectors available as accessories.

|                        |                                   |
|------------------------|-----------------------------------|
| Optic                  | FL                                |
| Beam angles            | FL                                |
| Optical efficiency     | 77.3%                             |
| Fixture flux           | 2190lm                            |
| Luminous efficacy      | 89lm/W                            |
| Photobiological safety | Compliant with RG1 low risk group |

### Mechanical characteristics

Painted die-cast aluminium body. Black painted polycarbonate front ring. Adjustable from 0° to -90° on the vertical plane and 359° on the horizontal plane. Mechanical beam locking system on the vertical plane and friction beam locking system on the horizontal plane. The centre of gravity always remains in axis with the track regardless of the aiming.

|                      |               |
|----------------------|---------------|
| Colour and finish    | Plaster white |
| Dimensions           | ØxH 76x110mm  |
| Weight               | 0.53Kg        |
| Degree of protection | IP20          |

### Electrical characteristics

ON-OFF electronic driver integrated into the track adapter.

|                          |                    |
|--------------------------|--------------------|
| Fixture Power            | 24.7W              |
| Power supply             | 220-240Vac 50/60Hz |
| Insulation Class         | CLASS 2            |
| Type of driver / Control | ON-OFF             |
| Driver included          | YES                |
| Ambient temperature      | 0°C / +25°C        |

### Installation

Electrified track mounting. Optical accessories that can be installed with a support ring are available.

### Notes

110-277Vac version available on request.

### Warranty

5 years.

### Warning

Luminaire designed for disposal/recycling at end-of-life. Replaceable (LED only) light source by a professional. Replaceable control gear by a professional.

# TARGETTI

CCIAA Firenze  
Share Capital: € 500.000,00  
VAT N. (IT): 01537660480  
R.E.A: FI-275656

Targetti Sankey S.r.l.  
Via Giuseppe Garibaldi, 82  
50041 Calenzano (FI)  
Italy


Tel: +39 055 37911  
targetti.com  
targetti@targetti.com

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.  
Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.

## Accessories


## Optic



| CODE    | OPTIC    | Ø    |
|---------|----------|------|
| A056SPR | SP 17°   | 52mm |
| A056FLR | FL 31°   | 52mm |
| A056MWR | MWFL 48° | 52mm |

Interchangeable anodised reflective aluminium reflectors.  
Available in Spot, Flood and Medium Wide Flood beams.

## Bracket



| CODE   | COLOUR |
|--------|--------|
| A058PW | ○      |
| A058DB | ●      |

Rigid support bracket for projectors with Eurostandard Plus track attachment.  
For compatibility and use please refer to the assembly instructions for the projectors.

For installation of Ray 75 projectors on wall vertical tracks.