

LIGHTING SYSTEMS

Oz Lighting module - Wall Washer - Large - 50x150mm

Code
2T0125CA

LIGHT COLOUR	LIGHT DISTRIBUTION	OUTPUT
3500K 90	Wall Washer	17.8W 1778lm
POWER SUPPLY CONTROL	COLOUR	
48Vdc		



The figures on the drawing are expressed in mm.



	3500K	H(m)	D1(m)	D2(m)	Emax(lx)
	Ra90	36°	76°		
Fixture Power	18W	1	0.69	1.61	1593
Source Flux	2484lm	2	1.39	3.22	398
Fixture Flux	1778lm	3	2.08	4.84	177
Efficacy	100lm/W	4	2.77	6.45	100
TS1841	Imax=683cd/klm	Imax	1696cd	5	3.47
				8.06	64

Technical Data

Concept

Wall Washer magnetic LED light modules, powered at low voltage.

Source

High efficiency Chip on Board LED Ra90.

Energy efficiency class	E
Nominal power	16W
Nominal flux	2484lm
Colour rendering index	90
Rf	91
Rg	100
CCT nominal	3500K
Lifetime (L80/B10)	72000h tq +25°C
Lifetime (L90/B10)	72000h tq +25°C

TARGETTI

CCIAA Firenze
Share Capital: € 500.000,00
VAT N. (IT): 01537660480
R.E.A: FI-275656

Targetti Sankey S.r.l.
Via Giuseppe Garibaldi, 82
50041 Calenzano (FI)
Italy

Tel: +39 055 37911
targetti.com
targetti@targetti.com

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.
Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.

Technical Data

Illuminotechnical characteristics

Wall Washer optical system: a high reflectance anodised aluminium reflector, holographic diffuser filter, frame in black polycarbonate.

Optic	Wall Washer
Optical efficiency	71.59%
Fixture flux	1778lm
Luminous efficacy	100lm/W
Photobiological safety	Compliant with RG1 low risk group

Mechanical characteristics

White painted die-cast aluminium body. Sizes 150x50mm.

Colour and finish	Plaster white
Dimensions	AxBxH 150x50x69mm
Weight	0.24Kg
Version	CASAMBI
Degree of protection	IP20

Electrical characteristics

Fixture Power	17.8W
Power supply	48Vdc
Insulation Class	CLASS 3
Ambient temperature	0°C / +25°C

Installation

Extremely rapid, versatile and simple mechanical and electrical coupling system using magnets which support the fixture on the Power Track and feed power inside the fixture on all versions.

Notes

Version with built-in Casambi control system (Casambi Ready). DALI control system available using a special accessory. 110-277Vac version available on request.

Warranty

5 years.

TARGETTI

CCIAA Firenze
Share Capital: € 500.000,00
VAT N. (IT): 01537660480
R.E.A: FI-275656

Targetti Sankey S.r.l.
Via Giuseppe Garibaldi, 82
50041 Calenzano (FI)
Italy

Tel: +39 055 37911
targetti.com
targetti@targetti.com

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.
Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.