

LIGHTING SYSTEMS

Logico Easy System

57 - UGR16 - Linear

module

Code

T027MX930ELPW

| LIGHT COLOUR         | LIGHT DISTRIBUTION                                                                | OUTPUT        |
|----------------------|-----------------------------------------------------------------------------------|---------------|
| 3000K<br>90          | UGR16                                                                             | 27W<br>2639lm |
| POWER SUPPLY CONTROL | COLOUR                                                                            |               |
| 220-240Vac<br>ON-OFF |  |               |



The figures on the drawing are expressed in mm.



Technical Data

Concept

Linear LED fixture for ceiling mounted or suspension system installation.

Source

LED Engine made of linear LED boards Ra90.

|                         |                  |
|-------------------------|------------------|
| Energy efficiency class | D                |
| Nominal power           | 24W              |
| Nominal flux            | 2639lm           |
| Colour rendering index  | 90               |
| Rf                      | 92               |
| Rg                      | 101              |
| CCT nominal             | 3000K            |
| Lifetime (L80/B10)      | 100000h tq +25°C |
| Lifetime (L90/B10)      | 50000h tq +25°C  |

TARGETTI

CCIAA Firenze  
Share Capital: € 500.000,00  
VAT N. (IT): 01537660480  
R.E.A: FI-275656

Targetti Sankey S.r.l.  
Via Giuseppe Garibaldi, 82  
50041 Calenzano (FI)  
Italy  
  
Tel: +39 055 37911  
targetti.com  
targetti@targetti.com

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.  
Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).  
  
We reserve the right to make technical changes.

## Technical Data

### Illuminotechnical characteristics

Direct emission. Controlled light. UGR16 Optics: optical system made of lenses with differentiated facets for optimizing the direction of the luminous flux and cellular optics in white anti-glare polycarbonate (UGR<16 and L65<1500 cd/m<sup>2</sup> EN-12464-1).

|                        |                                      |
|------------------------|--------------------------------------|
| Emission               | Direct                               |
| Optic                  | UGR16                                |
| Optical efficiency     | 100%                                 |
| Fixture flux           | 2639lm                               |
| Luminous efficacy      | 98lm/W                               |
| Photobiological safety | Compliant with RGO exempt risk group |

### Mechanical characteristics

Painted extruded aluminium body with 57mm section. Upper closing screen in white PVC.

|                       |                    |
|-----------------------|--------------------|
| Colour and finish     | White              |
| Dimensions            | AxBxH 2348x57x80mm |
| Weight                | 6.47Kg             |
| Version               | Linear             |
| Degree of protection  | IP40               |
| Mechanical Resistance | IK02               |

### Electrical characteristics

Integrated electronic ON-OFF driver. "Easy Connection" system for a quick connection between the modules of the system thanks to the pre-assembled plug/socket connection elements. Preset for through wiring allowing to reach a maximum length of 18 meters. Luminaire compliant with EN 60598-2-22 for power supply from a centralised emergency system CPSS (Central Power Supply System), not incorporated in the luminaire - high risk areas excluded. The default power and flux are 100% in AC and 100% in DC.

|                          |                                                                                                      |
|--------------------------|------------------------------------------------------------------------------------------------------|
| Fixture Power            | 27W                                                                                                  |
| Power supply             | 220-240Vac 50/60Hz                                                                                   |
| Insulation Class         | CLASS 1                                                                                              |
| Type of driver / Control | ON-OFF                                                                                               |
| Driver included          | YES                                                                                                  |
| SAFE FLICKER             | PstLM=<1 and SVM=<0.4 (IEC TR 61547-1 and IEC TR 63158), to ensure a more comfortable and safe light |
| Ambient temperature      | 0°C / +25°C                                                                                          |
| Relative humidity UR     | <85%                                                                                                 |

### Installation

To be completed with polycarbonate end caps, mounting systems for surface or suspended application and terminal block for connection to the power line.

### Notes

For angular configurations the L blind joint accessory is available. Commissioning of the control system via free APP; the intervention of a specialist technician can be quoted on request.

### Regulations and Certifications

CE

# TARGETTI

CCIAA Firenze  
Share Capital: € 500.000,00  
VAT N. (IT): 01537660480  
R.E.A: FI-275656

Targetti Sankey S.r.l.  
Via Giuseppe Garibaldi, 82  
50041 Calenzano (FI)  
Italy

Tel: +39 055 37911  
targetti.com  
targetti@targetti.com

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.  
Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.

**Technical Data****Warranty**

---

5 years.

**Warning**

---

Luminaire designed for disposal/recycling at end-of-life. Replaceable (LED only) light source by a professional.  
Replaceable control gear by a professional.

---

**TARGETTI**

CCIAA Firenze  
Share Capital: € 500.000,00  
VAT N. (IT): 01537660480  
R.E.A: FI-275656

Targetti Sankey S.r.l.  
Via Giuseppe Garibaldi, 82  
50041 Calenzano (FI)  
Italy

Tel: +39 055 37911  
targetti.com  
targetti@targetti.com

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.  
Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.

## Accessories

## Electrical Connector



| CODE     | COLOUR | DRIVER |
|----------|--------|--------|
| A014MELW | ○      | ON-OFF |

L-shaped blind joint.

Sizes 818x818x80mm.  
For LOGICO EASY System 57.

## End Caps



| CODE    | COLOUR |
|---------|--------|
| A003M1W | ○      |

End caps (2 pieces).

For LOGICO EASY System 57 - UGR16.

## Canopy



| CODE  | COLOUR |
|-------|--------|
| A004W | ○      |

Canopy with 5 poles terminal block.  
Feeding cable not included.

## Bracket



| CODE  |
|-------|
| A006M |

Bracket for ceiling installation (2 pieces).  
Two brackets needed for each lighting module.

For LOGICO EASY 57.



| CODE  |
|-------|
| A007M |

Bracket with adjustment system for suspended installation (2 pieces).  
Two brackets needed for each lighting module.

For LOGICO EASY 57.

Accessories

Suspension



| CODE  | VERSION  |
|-------|----------|
| A008T | L = 6m   |
| A008U | L = 5m   |
| A008V | L = 4m   |
| A008W | L = 3m   |
| A008X | L = 2m   |
| A008Y | L = 1m   |
| A008Z | L = 0,5m |

Suspension cable (2 pieces).

Terminal Box



| CODE  | VERSION       |
|-------|---------------|
| A009Z | 3 Poli ON-OFF |

Terminal block (plug/socket).  
One for each power supply.

A009Z - For LOGICO EASY 37 | 57 | 100.