
CEILING LUMINAIRES | PENDANT LUMINAIRES


Logico Easy Stand Alone 57 - UGR19



Code
T021MX930ELPW


LIGHT COLOUR	LIGHT DISTRIBUTION	OUTPUT
3000K 90	UGR19	33W 2316lm

POWER SUPPLY CONTROL	COLOUR
220-240Vac ON-OFF	



The figures on the drawing are expressed in mm.





3000K		H(m)	D1(m)	D2(m)	Emax(lx)
Ra90			83°	89°	
Fixture Power	33W	1	1.78	1.97	1280
Source Flux	2316lm	2	3.56	3.94	320
Fixture Flux	2316lm	3	5.33	5.91	142
Efficacy	70lm/W	4	7.11	7.88	80
Imax	1280cd	5	8.89	9.85	51

Technical Data

Concept

Linear stand alone LED fixture for ceiling mounted or suspension installation.

Source

LED Engine made of linear LED boards Ra90.	
Energy efficiency class	E
Nominal power	30W
Nominal flux	2316lm
Colour rendering index	90
Rf	92
Rg	101
CCT nominal	3000K
Lifetime (L80/B10)	100000h tq +25°C
Lifetime (L90/B10)	50000h tq +25°C

TARGETTI

CCIAA Firenze
Share Capital: € 500.000,00
VAT N. (IT): 01537660480
R.E.A: FI-275656

Targetti Sankey S.r.l.
Via Giuseppe Garibaldi, 82
50041 Calenzano (FI)
Italy

Tel: +39 055 37911
targetti.com
targetti@targetti.com

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.
Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.

Technical Data

Illuminotechnical characteristics

Direct emission. Controlled light. UGR19 optics: optical system made of a reflector with white polymer coating and UGR closing diffuser screen (UGR<19 and L65<3000 cd/m² EN-12464-1).

Emission	Direct
Optic	UGR19
Optical efficiency	100%
Fixture flux	2316lm
Luminous efficacy	70lm/W
Photobiological safety	Compliant with RG0 exempt risk group

Mechanical characteristics

Painted extruded aluminium body with 57mm section and polycarbonate end caps. Upper closing screen in white PVC.

Colour and finish	White
Dimensions	AxBxH 2340x57x80mm
Weight	4.995Kg
Version	Linear
Degree of protection	IP40
Mechanical Resistance	IK02

Electrical characteristics

Integrated electronic ON-OFF driver. Luminaire compliant with EN 60598-2-22 for power supply from a centralised emergency system CPSS (Central Power Supply System), not incorporated in the luminaire - high risk areas excluded. The default power and flux are 100% in AC and 100% in DC.

Fixture Power	33W
Power supply	220-240Vac 50/60Hz
Insulation Class	CLASS 1
Type of driver / Control	ON-OFF
Driver included	YES
SAFE FLICKER	PstLM=<1 and SVM=<0.4 (IEC TR 61547-1 and IEC TR 63158), to ensure a more comfortable and safe light
Ambient temperature	0°C / +25°C
Relative humidity UR	<85%

Installation

To be completed with mounting systems for surface or suspended application.

Notes

Commissioning of the control system via free APP; the intervention of a specialist technician can be quoted on request.

Regulations and Certifications

CE

Warranty

5 years.

Technical Data

Warning

Luminaire designed for disposal/recycling at end-of-life. Replaceable (LED only) light source by a professional. Replaceable control gear by a professional.

TARGETTI

CCIAA Firenze
Share Capital: € 500.000,00
VAT N. (IT): 01537660480
R.E.A: FI-275656

Targetti Sankey S.r.l.
Via Giuseppe Garibaldi, 82
50041 Calenzano (FI)
Italy

Tel: +39 055 37911
targetti.com
targetti@targetti.com

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.
Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.

Accessories

Canopy



CODE	COLOUR
A004W	◯

Canopy with 5 poles terminal block.
Feeding cable not included.

Bracket



CODE
A006M

Bracket for ceiling installation (2 pieces).
Two brackets needed for each lighting module.

For LOGICO EASY 57.



CODE
A007M

Bracket with adjustment system for suspended installation (2 pieces).
Two brackets needed for each lighting module.

For LOGICO EASY 57.

Suspension



CODE	VERSION
A008T	L=6m
A008U	L=5m
A008V	L=4m
A008W	L=3m
A008X	L=2m
A008Y	L=1m
A008Z	L=0,5m

Suspension cable (2 pieces).

TARGETTI

CCIAA Firenze
Share Capital: € 500.000,00
VAT N. (IT): 01537660480
R.E.A: FI-275656

Targetti Sankey S.r.l.
Via Giuseppe Garibaldi, 82
50041 Calenzano (FI)
Italy

Tel: +39 055 37911
targetti.com
targetti@targetti.com

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.
Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.