


PROJECTORS

Dart Round Small TW

Code
1E4039

LIGHT COLOUR	LIGHT DISTRIBUTION	OUTPUT
2700-5000K 80	MWFL 45°	4.2W 317-377lm
POWER SUPPLY CONTROL	COLOUR	
700mA		



The figures on the drawing are expressed in mm.



The fixture's photometric values
can be found on the following pages

Technical Data

Concept

Professional adjustable LED projector.

Source

Tunable White board made of high efficiency Ra80 LED Emitters that allow to reach and choose a color temperature between 2700K and 5000K.

Energy efficiency class	F
Nominal power	4,2W
Nominal flux	See photometries
Colour rendering index	80
Rf	83
Rg	97
CCT nominal	See photometries

TARGETTI

CCIAA Firenze
Share Capital: € 500.000,00
VAT N. (IT): 01537660480
R.E.A: FI-275656

Targetti Sankey S.r.l.
Via Giuseppe Garibaldi, 82
50041 Calenzano (FI)
Italy

Tel: +39 055 37911
targetti.com
targetti@targetti.com

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.
Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.

Technical Data

Illuminotechnical characteristics

Equipped with precision methacrylate lens and spreader filter.

Optic	MWFL
Beam angles	MWFL
Optical efficiency	68.87%
Fixture flux	See photometries
Luminous efficacy	See photometries
Photobiological safety	Compliant with RG1 low risk group

Mechanical characteristics

Painted die-cast anodised aluminium body and painted stainless steel mounting bracket. Tempered extra clear front glass.

Colour and finish	Ferrite
Dimensions	ØxH 88x148mm
Weight	1Kg
Degree of protection	IP66
Mechanical Resistance	IK10

Electrical characteristics

Remote electronic driver with DALI DT8 interface. The driver is housed inside an IP68 box and allows to control from 1 to 9 fixtures. All versions are pre-wired with a 1.5m long feeding cable H07RN-F (to be connected to the IP68 driver box).

Fixture Power	4.2W
Power supply	700mA
Insulation Class	CLASS 3
Driver included	NO
Ambient temperature	-25°C / +35°C

Installation

Mounting bracket with aiming adjustability. Adjustable up to $\pm 60^\circ$ on the horizontal pane and $+90^\circ/-45^\circ$ on the vertical plane.

Notes

Casambi control system available using a dedicated accessory (only for DALI version products). Uses the "Waterblock Smart" technical solution that involves resin coating the connection cables, limiting the risk of humidity reaching the driver or the fixture. It is possible to subject the product to Cataphoresis treatment on request. 110-277Vac version available on request. Values related to the power consumption of the fixture do not take into account the consumption of the accessory driver, which depends on the choice of driver. Commissioning of the control system via free APP; the intervention of a specialist technician can be quoted on request.

Warranty

5 years.

Warning

Luminaire designed for disposal/recycling at end-of-life. Replaceable (LED only) light source by a professional.

TARGETTI

CCIAA Firenze
Share Capital: € 500.000,00
VAT N. (IT): 01537660480
R.E.A: FI-275656

Targetti Sankey S.r.l.
Via Giuseppe Garibaldi, 82
50041 Calenzano (FI)
Italy

Tel: +39 055 37911
targetti.com
targetti@targetti.com

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.
Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. $t_q +25^\circ\text{C}$ (CIE 121).

We reserve the right to make technical changes.

Photometries

WW

CCT nominal	2700K
Nominal flux	461lm
Fixture flux	317lm
Luminous efficacy	76lm/W



NW

CCT nominal	3850K
Nominal flux	547lm
Fixture flux	377lm
Luminous efficacy	90lm/W




CW

CCT nominal	5000K
Nominal flux	536lm
Fixture flux	369lm
Luminous efficacy	88lm/W



Related codes

Power Supply



CODE

1E4056

Tunable White DALI driver - 700mA.
50W, LxHxP=220x80x120mm, 110-277Vac.
IP68 gray powder coated aluminum box.

Accessories

Filter



CODE

1E4002

COLOUR



Blade of light filter.
PMMA holographic filter for a blade of light effect.
Completed with powder coated aluminum alloy holder ring.

Grid



CODE

1E4005

COLOUR



Anti-glare louver.
The central elements can be adjusted +/- 60° for a perfect glare control.
Powder coated stainless steel.

Screen



CODE

1E4003

COLOUR



Asymmetric screen.
Powder coated stainless steel.



CODE

1E4004

COLOUR



Cylindrical screen.
Powder coated stainless steel.
Short version.



CODE

1E4057

COLOUR



Cylindrical screen.
Powder coated stainless steel.
Long version.

Mounting System



CODE

1E3015

COLOUR



Plate for fixture rotation.
Powder coated stainless steel.

CCIAA Firenze
Share Capital: € 500.000,00
VAT N. (IT): 01537660480
R.E.A: FI-275656

Italy
Tel: +39 055 37911
targetti.com
targetti@targetti.com

Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. $t_q +25^{\circ}\text{C}$ (CIE 121).

We reserve the right to make technical changes.

Accessories

Mounting System



CODE	COLOUR	ØXH
1E3016		70x182mm

Earthspike.
Powder coated stainless steel.

Control systems



CODE
1E3048

IP67 wireless control unit with DALI interface.
It generates a local DALI2 bus, enabling a direct connection to a DALI interface LED driver. The module can only be used in a closed system and cannot be connected to an existing DALI network.
The module is wireless controlled using a Casambi app for smartphones and tablets using Bluetooth 5.0 technology.
The devices automatically create an adaptive, robust, and reliable wireless mesh network, allowing for the easy and efficient management of a high number of fixtures.
The control unit is preset to the DALI TCH profile, meaning the device can control a single DALI driver with broadcast commands.
In addition to the DALI broadcast, other operating modes are available, such as:

- Button (normally open)
- Control unit 0/1-10V
- Control unit DALI Tunable White DT8
- Presence sensor

If different from the preset mode, the desired operating profile must be set directly by the user before coupling the control unit to the Casambi network.
LxHxP=108x28x65mm.



CODE
1E4369

IP67 Extender for wireless control of LED driver with dimming DALI interface based on Casambi technology.
It has a DALI2 output with the capacity to control up to 40 lighting fixtures.
With the addition of a further external BUS DALI power supply it is possible to control up to 64 fixtures.
IP67 Extender is preset to the DALI broadcast profile, meaning all the luminaires connected to it are dimmable at the same level.
In addition to the DALI broadcast other operating modes are available, such as:

- EXTENDER DALI 8CH
- EXTENDER DALI Tunable White
- EXTENDER DALI 4CH
- EXTENDER DALI DT8 Tunable White

If different from the preset mode, the desired operating profile must be set directly by the user before coupling the extender to the Casambi network.
LxHxP=148x40x150mm.