

## RECESSED LUMINAIRES



# Oz Stand Alone Recessed - Large 5x - 260x60mm

Code

1T8862EL

| LIGHT COLOUR | LIGHT DISTRIBUTION                      | OUTPUT          |
|--------------|-----------------------------------------|-----------------|
| 2700K<br>90  | Elliptical<br>Longitudinal<br>58° / 25° | 20.5W<br>1738lm |

| POWER SUPPLY CONTROL | COLOUR |
|----------------------|--------|
|----------------------|--------|

220-240Vac  
ON-OFF

The figures on the drawing are expressed in mm.

|               | 2700K                        | H(m)             | D1(m)  | D2(m) | E <sub>max</sub> (lx) |
|---------------|------------------------------|------------------|--------|-------|-----------------------|
|               | Ra90                         | 58°              | 25°    |       |                       |
| Fixture Power | 21W                          | 1                | 1.11   | 0.44  | 3400                  |
| Source Flux   | 2415lm                       | 2                | 2.21   | 0.88  | 850                   |
| Fixture Flux  | 1738lm                       | 3                | 3.32   | 1.32  | 378                   |
| Efficacy      | 85lm/W                       | 4                | 4.43   | 1.76  | 212                   |
| TS1255        | I <sub>max</sub> =1408cd/klm | I <sub>max</sub> | 3400cd | 5     | 5.54                  |
|               |                              |                  |        | 2.19  | 136                   |

## Technical Data

## Concept

Recessed LED floodlights.

## Source

High efficiency Chip on Board LED Ra90.

|                         |                 |
|-------------------------|-----------------|
| Energy efficiency class | F               |
| Nominal power           | 18W             |
| Nominal flux            | 2415lm          |
| Colour rendering index  | 90              |
| R <sub>f</sub>          | 92              |
| R <sub>g</sub>          | 99              |
| CCT nominal             | 2700K           |
| SDCM                    | 2               |
| Lifetime (L80/B10)      | 52000h tq +25°C |
| Lifetime (L90/B10)      | 52000h tq +25°C |

# TARGETTI

CCIAA Firenze  
Share Capital: € 500.000,00  
VAT N. (IT): 01537660480  
R.E.A: FI-275656

Targetti Sankey S.r.l.  
Via Giuseppe Garibaldi, 82  
50041 Calenzano (FI)  
Italy

Tel: +39 055 37911  
targetti.com  
targetti@targetti.com

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.  
Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.

## Technical Data

### Illuminotechnical characteristics

ELL optic. Anodised aluminium reflector, a holographic filter and a black polycarbonate frame. The fixture is suitable for installation in workplaces UGR<13/22 (EN12464-1).

|                        |                                   |
|------------------------|-----------------------------------|
| Optic                  | Elliptical Longitudinal           |
| Beam angles            | ELL                               |
| Optical efficiency     | 71.97%                            |
| Fixture flux           | 1738lm                            |
| Luminous efficacy      | 85lm/W                            |
| Photobiological safety | Compliant with RG1 low risk group |

### Mechanical characteristics

Black painted die-cast aluminium body. 5X Large version.

|                      |                   |
|----------------------|-------------------|
| Colour and finish    | Deep black        |
| Dimensions           | AxBxH 260x60x61mm |
| Weight               | 0.7Kg             |
| Version              | 5X                |
| Degree of protection | IP20              |

### Electrical characteristics

Complete with an electronic ON-OFF driver. Luminaire compliant with EN 60598-2-22 for power supply from a centralised emergency system CPSS (Central Power Supply System), not incorporated in the luminaire - high risk areas excluded. The default power and flux are 100% in AC and 100% in DC.

|                          |                                                                                                      |
|--------------------------|------------------------------------------------------------------------------------------------------|
| Fixture Power            | 20.5W                                                                                                |
| Power supply             | 220-240Vac 50/60Hz                                                                                   |
| Insulation Class         | CLASS 2                                                                                              |
| Type of driver / Control | ON-OFF                                                                                               |
| Driver included          | YES                                                                                                  |
| SAFE FLICKER             | PstLM=<1 and SVM=<0.4 (IEC TR 61547-1 and IEC TR 63158), to ensure a more comfortable and safe light |
| Ambient temperature      | 0°C / +25°C                                                                                          |

### Installation

Quick fastening system with springs for installation in false ceilings from 0 to 30mm.

### Notes

110-277Vac version available on request.

### Warranty

5 years.

### Warning

Luminaire designed for disposal/recycling at end-of-life. Replaceable (LED only) light source by a professional. Replaceable control gear by a professional.

# TARGETTI

CCIAA Firenze  
Share Capital: € 500.000,00  
VAT N. (IT): 01537660480  
R.E.A: FI-275656

Targetti Sankey S.r.l.  
Via Giuseppe Garibaldi, 82  
50041 Calenzano (FI)  
Italy

Tel: +39 055 37911  
targetti.com  
targetti@targetti.com

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.  
Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.

## Accessories

### Emergency Kit



#### CODE

**A059**

Emergency kit composed of an inverter a LiFePO4 battery and a LED Green indicator.  
Allows permanent EP emergency use of the fixture it is connected to.  
The 1h or 3h autonomy can be selected by configuring the fixture.  
The batteries take 12h to completely recharge.  
LED Green indicator wired to the inverter through single-core cables L= 800mm.  
Emergency kit for fixtures that comply with EN 60598-2-22 standard, high risk areas excluded.  
Battery size 160x54x30 mm.  
Inverter size 165x40x25 mm.