TRACK PROJECTORS


Zeno 130



Code
T039WWR730DPW


LIGHT COLOUR	LIGHT DISTRIBUTION	OUTPUT
3000K 97	Wall Washer	29.1W 1483lm

POWER SUPPLY CONTROL	COLOUR
220-240Vac DIMM ON BOARD	



The figures on the drawing are expressed in mm.





3000K		H(m)	D1(m)	D2(m)	Emax(lx)
Ra97			34°	54°	
Fixture Power	29W	1	1.06	1.17	1344
Source Flux	2620lm	2	2.11	2.34	336
Fixture Flux	1483lm	3	3.17	3.50	149
Efficacy	51lm/W	4	4.23	4.67	84
Imax	1952cd	5	5.28	5.84	54

Technical Data

Concept

Professional adjustable LED projector.

Source

High efficiency Chip on Board LED Ra97.	
Energy efficiency class	F
Nominal power	26W
Nominal flux	2620lm
Colour rendering index	97
Rf	95
Rg	103
CCT nominal	3000K
Lifetime (L80/B10)	72000h tq +25°C
Lifetime (L90/B10)	72000h tq +25°C

TARGETTI

CCIAA Firenze
Share Capital: € 500.000,00
VAT N. (IT): 01537660480
R.E.A: FI-275656

Targetti Sankey S.r.l.
Via Giuseppe Garibaldi, 82
50041 Calenzano (FI)
Italy

Tel: +39 055 37911
targetti.com
targetti@targetti.com

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.
Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.

Technical Data

Illuminotechnical characteristics

Wall Washer version with a highly reflective pre-anodised specular aluminium optic, a PMMA holographic screen and a black polymer covering element.

Optic	Wall Washer
Beam angles	WW
Optical efficiency	56.59%
Fixture flux	1483lm
Luminous efficacy	51lm/W
Photobiological safety	Compliant with RG1 low risk group

Mechanical characteristics

Die-cast painted aluminium optical unit. The optical unit can be adjusted from 0 to -90° on the vertical plane; and 355° on the horizontal plane with aiming blocking system.

Colour and finish	Plaster white
Dimensions	ØxH 134x85mm
Weight	0.95Kg
Degree of protection	IP20

Electrical characteristics

Electronic 1—10V driver with on-board dimmer integrated into the track adapter.

Fixture Power	29.1W
Power supply	220-240Vac 50/60Hz
Insulation Class	CLASS 2
Type of driver / Control	DIMM ON BOARD
Driver included	YES
Ambient temperature	0°C / +25°C

Installation

Electrified track mounting.

Notes

110-277Vac version available on request.

Regulations and Certifications

CE

Warranty

5 years.

Warning

Luminaire designed for disposal/recycling at end-of-life. Replaceable (LED only) light source by a professional. Replaceable control gear by a professional.

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.
Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.