

## LIGHTING SYSTEMS

# Fortyeight Label 4 - Long arm

Code  
**1T6714EL**

| LIGHT COLOUR         | LIGHT DISTRIBUTION                                                                | OUTPUT        |
|----------------------|-----------------------------------------------------------------------------------|---------------|
| 2700K<br>90          | SP<br>18°                                                                         | 9.5W<br>638lm |
| POWER SUPPLY CONTROL | COLOUR                                                                            |               |
| 48Vdc                |  |               |



The figures on the drawing are expressed in mm.



|  | 2700K         | H(m)                         | D(m)             | E <sub>max</sub> (lx) |      |      |
|--------------------------------------------------------------------------------------|---------------|------------------------------|------------------|-----------------------|------|------|
|                                                                                      | Ra90          |                              | 18°              |                       |      |      |
|                                                                                      | Fixture Power | 9W                           | 1                | 0.31                  | 4325 |      |
|                                                                                      | Source Flux   | 1008lm                       | 2                | 0.62                  | 1081 |      |
|                                                                                      | Fixture Flux  | 638lm                        | 3                | 0.93                  | 481  |      |
|                                                                                      | Efficacy      | 67lm/W                       | 4                | 1.24                  | 270  |      |
|                                                                                      | TS1952        | I <sub>max</sub> =4291cd/klm | I <sub>max</sub> | 4325cd                | 5    | 1.55 |

## Technical Data

## Concept

Low voltage adjustable LED professional projector.

## Source

High efficiency Chip on Board LED Ra90. 3500K on request.

|                         |                 |
|-------------------------|-----------------|
| Energy efficiency class | F               |
| Nominal power           | 8,7W            |
| Nominal flux            | 1008lm          |
| Colour rendering index  | 90              |
| R <sub>f</sub>          | 92              |
| R <sub>g</sub>          | 99              |
| CCT nominal             | 2700K           |
| SDCM                    | 1.5             |
| Lifetime (L80/B10)      | 52000h tq +25°C |
| Lifetime (L90/B10)      | 52000h tq +25°C |

# TARGETTI

CCIAA Firenze  
Share Capital: € 500.000,00  
VAT N. (IT): 01537660480  
R.E.A: FI-275656

Targetti Sankey S.r.l.  
Via Giuseppe Garibaldi, 82  
50041 Calenzano (FI)  
Italy

Tel: +39 055 37911  
targetti.com  
targetti@targetti.com

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.  
Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.

## Technical Data

### Illuminotechnical characteristics

SP - metallised polycarbonate precision optics, a holographic diffusion filter and a black silicone cut off ring.

|                        |                                   |
|------------------------|-----------------------------------|
| Optic                  | SP                                |
| Beam angles            | SP                                |
| Optical efficiency     | 63.31%                            |
| Fixture flux           | 638lm                             |
| Luminous efficacy      | 67lm/W                            |
| Photobiological safety | Compliant with RG1 low risk group |

### Mechanical characteristics

Painted die-cast aluminium body. The optical unit can be adjusted from 0° a 90° on the vertical plane and 360° on the horizontal plane with friction locking system.

|                      |                   |
|----------------------|-------------------|
| Colour and finish    | Deep black        |
| Dimensions           | ØxH 40x70mm       |
| Weight               | 0.16Kg            |
| Version              | Long arm - ON-OFF |
| Degree of protection | IP20              |

### Electrical characteristics

Electronic ON-OFF power supply for track.

|                     |                                                                                                      |
|---------------------|------------------------------------------------------------------------------------------------------|
| Fixture Power       | 9.5W                                                                                                 |
| Power supply        | 48Vdc                                                                                                |
| Insulation Class    | CLASS 3                                                                                              |
| SAFE FLICKER        | PstLM=<1 and SVM=<0.4 (IEC TR 61547-1 and IEC TR 63158), to ensure a more comfortable and safe light |
| Ambient temperature | 0°C / +25°C                                                                                          |

### Installation

Long bracket version for insertion into the trimless deep track version. Quick coupling system for mounting the product on the track.

### Notes

Not polarized fixture. The arm is and the adapter are supplied in the same colour as the body of the projector. 110-277Vac version available on request.

### Warranty

5 years.

### Warning

Luminaire designed for disposal/recycling at end-of-life. Replaceable (LED only) light source by a professional. Replaceable control gear by a professional.

# TARGETTI

CCIAA Firenze  
Share Capital: € 500.000,00  
VAT N. (IT): 01537660480  
R.E.A: FI-275656

Targetti Sankey S.r.l.  
Via Giuseppe Garibaldi, 82  
50041 Calenzano (FI)  
Italy

Tel: +39 055 37911  
targetti.com  
targetti@targetti.com

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.  
Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.

## Accessories

## Filter



| CODE   | Ø    |
|--------|------|
| 1T6931 | 34mm |

PMMA holographic filter with blade effect to ovalize the light beam; more evident when combined with spot and flood optics.

## Grid



| CODE   | Ø    |
|--------|------|
| 1T6930 | 34mm |

Anti-glare louver.  
Black painted metal honeycomb structure.  
Complete with holographic diffusion filter.