PROJECTORS


Jedi Projector RGBW - L. 616mm



Code
1E4249

LIGHT COLOUR	LIGHT DISTRIBUTION	OUTPUT
RGBW	FL 35°	27.5W 1349lm

POWER SUPPLY CONTROL	COLOUR
220-240Vac DMX RDM	



The figures on the drawing are expressed in mm.



The fixture's photometric values can be found on the following pages

Technical Data

Concept

Powerful adjustable linear RGBW LED projector.

Source

LED Multichip RGBW module with white 3000K.	
Energy efficiency class	G
Nominal power	22W
Nominal flux	See photometries
Colour rendering index	
CCT nominal	See photometries
SDCM	2
Lifetime (L80/B10)	100000h tq +25°C
Lifetime (L90/B10)	72000h tq +25°C

TARGETTI

CCIAA Firenze
Share Capital: € 500.000,00
VAT N. (IT): 01537660480
R.E.A: FI-275656

Targetti Sankey S.r.l.
Via Giuseppe Garibaldi, 82
50041 Calenzano (FI)
Italy

Tel: +39 055 37911
targetti.com
targetti@targetti.com

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.
Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.

Technical Data

Illuminotechnical characteristics

Internal optical system composed of a primary cylindrical glass lens, a high reflectance anodised aluminium reflector and an integrated holographic filter.

Optic	FL
Beam angles	FL
Optical efficiency	75.19%
Fixture flux	See photometries
Luminous efficacy	See photometries
Photobiological safety	Compliant with RG1 low risk group

Mechanical characteristics

Extruded anodised aluminium 15µ body. Extra clear 4mm thick glass flat screen. Black polycarbonate driver box. The body of the fixture is adjustable and can be installed away from the mounting surface by sliding the brackets along a special guide.

Colour and finish	Aluminium
Dimensions	AxBxH 616x81x82mm
Weight	3.7Kg
Degree of protection	IP66,IP67
Mechanical Resistance	IK08

Electrical characteristics

Integrated electronic power supply. Controlled using DMX-RDM protocols that allow to programme the fixture remotely (no dip-switch) using the DMX data line. Pass-through power supply with 1 meter cable and 3-pole IP68 connectors. Pass-through DMX line connection with 5-pole IP68 panel connectors. Programming the fixtures is done using the USB-RDM programmer that is available as an accessory.

Fixture Power	See photometries
Power supply	220-240Vac 50/60Hz
Insulation Class	CLASS 1
Type of driver / Control	DMX RDM
Driver included	YES
SAFE FLICKER	PstLM=<1 and SVM=<0.4 (IEC TR 61547-1 and IEC TR 63158), to ensure a more comfortable and safe light
Ambient temperature	-25°C / +35°C

Installation

To be completed with stainless steel fixed or adjustable brackets. The brackets can slide along the body of the fixture to be positioned according to installation needs.

Notes

LMS Casambi wireless control available on request. Photometrics show the maximum emission values of fixtures. Uses the "Waterblock Smart" technical solution that involves resin coating the connection cables, limiting the risk of humidity reaching the driver or the fixture. 110-277Vac version available on request.

Regulations and Certifications

CE

Technical Data

Warranty

5 years.

Warning

Luminaire designed for disposal/recycling at end-of-life. Replaceable (LED only) light source by a professional. Replaceable control gear by a professional.

TARGETTI

CCIAA Firenze
Share Capital: € 500.000,00
VAT N. (IT): 01537660480
R.E.A: FI-275656

Targetti Sankey S.r.l.
Via Giuseppe Garibaldi, 82
50041 Calenzano (FI)
Italy

Tel: +39 055 37911
targetti.com
targetti@targetti.com


Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.
Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.

Photometries

RGBW


Fixture Power	27.5W
Nominal flux	1794lm
Fixture flux	1349lm
Luminous efficacy	49lm/W



-		H(m)	D1(m)	D2(m)	Emax(lx)
-			35°	88°	
Fixture Power	28W	1	0.63	1.94	1168
Source Flux	1794lm	2	1.26	3.88	292
Fixture Flux	1349lm	3	1.90	5.81	130
Efficacy	49lm/W	4	2.53	7.75	73
TS1770 Imax=651cd/klm	Imax	5	3.16	9.69	47

RGB


Fixture Power	19.8W
Nominal flux	1022lm
Fixture flux	768lm
Luminous efficacy	39lm/W



-		H(m)	D1(m)	D2(m)	Emax(lx)
-			35°	88°	
Fixture Power	20W	1	0.63	1.94	665
Source Flux	1022lm	2	1.26	3.88	166
Fixture Flux	768lm	3	1.90	5.81	74
Efficacy	39lm/W	4	2.53	7.75	42
TS1770 Imax=651cd/klm	Imax	5	3.16	9.69	27

WHITE


CCT nominal	3000K
Fixture Power	7.2W
Nominal flux	874lm
Fixture flux	657lm
Luminous efficacy	91lm/W



3000K		H(m)	D1(m)	D2(m)	Emax(lx)
-			35°	88°	
Fixture Power	7W	1	0.63	1.94	569
Source Flux	874lm	2	1.26	3.88	142
Fixture Flux	657lm	3	1.90	5.81	63
Efficacy	91lm/W	4	2.53	7.75	36
TS1770 Imax=651cd/klm	Imax	5	3.16	9.69	23

RED


Fixture Power	5.3W
Nominal flux	314lm
Fixture flux	236lm
Luminous efficacy	45lm/W



-		H(m)	D1(m)	D2(m)	Emax(lx)
-			35°	88°	
Fixture Power	5W	1	0.63	1.94	204
Source Flux	314lm	2	1.26	3.88	51
Fixture Flux	236lm	3	1.90	5.81	23
Efficacy	45lm/W	4	2.53	7.75	13
TS1770 Imax=651cd/klm	Imax	5	3.16	9.69	8

GREEN


Fixture Power	7.4W
Nominal flux	644lm
Fixture flux	484lm
Luminous efficacy	65lm/W



-		H(m)	D1(m)	D2(m)	Emax(lx)
-			35°	88°	
Fixture Power	7W	1	0.63	1.94	419
Source Flux	644lm	2	1.26	3.88	105
Fixture Flux	484lm	3	1.90	5.81	47
Efficacy	65lm/W	4	2.53	7.75	26
TS1770 Imax=651cd/klm	Imax	5	3.16	9.69	17

BLUE

Fixture Power	7.3W
Nominal flux	126lm
Fixture flux	95lm
Luminous efficacy	13lm/W



-		H(m)	D1(m)	D2(m)	Emax(lx)
-			35°	88°	
Fixture Power	7W	1	0.63	1.94	82
Source Flux	126lm	2	1.26	3.88	21
Fixture Flux	95lm	3	1.90	5.81	9
Efficacy	13lm/W	4	2.53	7.75	5
TS1770 Imax=651cd/klm	Imax	5	3.16	9.69	3

TARGETTI

CCIAA Firenze
Share Capital: € 500.000,00
VAT N. (IT): 01537660480
R.E.A: FI-275656

Targetti Sankey S.r.l.
Via Giuseppe Garibaldi, 82
50041 Calenzano (FI)
Italy


Tel: +39 055 37911
targetti.com
targetti@targetti.com

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.
Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.

Related codes


Mounting System



CODE

1E2752


Short bracket for wall installation (2 pieces).



CODE

1E2753

Long bracket for wall installation (2 pieces).




CODE

1E2754

Bracket for ceiling installation (2 pieces).

Accessories

End Caps




CODE

1E2761


End cap with bracket for ceiling installation included.

Cover Panel




CODE	L
1E3045	616mm

Side cover for ceiling installation.



CODE	L
1E2755	616mm

Side cover for wall/cornice installation.



CODE	L
1E2758	616mm

Anti-glare side cover.

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.
Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.

Connector



CODE

1E2769

Linear connection box IP66/IP68.
5 poles max. wire section 1.5mm².
Cable diameter range from 7 to 12mm.



CODE

1E3184

IP68 4-way cable connector (5 pole).

Control systems



CODE

1E2767

USB-RDM Programmer code.
DMX-RDM (Remote Device Management) address planner.
Used with the "RDM Targetti" software that can be downloaded for free from the Targetti website download section.
To be used with all RGBW products.
The USB-RDM programmer manages to direct DMX-RDM fixtures if there are no BUFFER or Splitter DMXs on the section.
Please refer to the instructions for more details.



CODE

A077

my-SCENARIO Show Store.
Programmable DMX interface that integrates the latest innovations in lighting control in architectural and entertainment applications.
It features USB Type-C and Ethernet ports for programming and remote control.
The unit can be fully programmed with ESA Pro 2 software (available for Windows and Mac users) or via mobile applications such as Arcolis (available for iOS or Android devices).
It can be fully customised: pixel mapping, triggering management, patch configuration and much more.
The system offers great possibilities for the control of your lighting installation: multi zone control (allowing the management of up to 5 indipendent zones), extended triggers (time/date, Sunrise/Sunset, input ports, TCP/UDP commands), 16-bit channels management, full recovery after power loss, up to 99 total scenes, and 1024+ DMX channels.
The intuitive backlit keyboard comes with 10 preset buttons for a user friendly experience.



CODE


1T6499

myScenario Wall.
DMX controller with a glass touch sensitive screen for architectural applications.
It can control two different DMX universes (2x 512 channels).
Stand alone function or connected to a computer using a USB port.
Software for creating scenarios (that can be downloaded from the Targetti website) included.
It can manage 10 different lighting zones and 50 scenarios per zone.
The touch keys on the front make it possible to modify and recall programmed scenarios.
USB cable included.
To be used with all RGBW products.

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.
Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.

Surge protector



CODE

A013A

Surge protector compatible with CLASS I lighting fixtures.
Operating voltage 230-277Vac.
SPD type 2+3.
Max surge protection 10kV.
CLASS I
IP67

TARGETTI

CCIAA Firenze
Share Capital: € 500.000,00
VAT N. (IT): 01537660480
R.E.A: FI-275656

Targetti Sankey S.r.l.
Via Giuseppe Garibaldi, 82
50041 Calenzano (FI)
Italy

Tel: +39 055 37911
targetti.com
targetti@targetti.com

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.
Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.