RECESSED LUMINAIRES


# CCTEvo Architectural 160 Trimless



**Code**
## 1T8604ELTR

| LIGHT COLOUR | LIGHT DISTRIBUTION | OUTPUT |
|---|---|---|
| 4000K<br>90 | FL<br>33° | 34.1W<br>3334lm |

| POWER SUPPLY CONTROL | COLOUR |
|---|---|
| 220-240Vac<br>ON-OFF | |




**The figures on the drawing are expressed in mm.**







| 4000K | | H(m) | D(m) | Emax(lx) |
|---|---|---|---|---|
| Ra90 | | | 33° | |
| Fixture Power | 34W | 1 | 0.59 | 9828 |
| Source Flux | 4523lm | 2 | 1.18 | 2457 |
| Fixture Flux | 3334lm | 3 | 1.77 | 1092 |
| Efficacy | 98lm/W | 4 | 2.36 | 614 |
| Imax | 9828cd | 5 | 2.95 | 393 |

## Technical Data

### Concept

Adjustable recessed LED projector in a trimless version.

### Source

| | |
|---|---|
| High efficiency Chip on Board LED Ra90. Ra80 on request. | |
| Energy efficiency class | E |
| Nominal power | 31W |
| Nominal flux | 4523lm |
| Colour rendering index | 90 |
| Rf | 90 |
| Rg | 98 |
| CCT nominal | 4000K |
| Lifetime (L80/B10) | 72000h tq +25°C |
| Lifetime (L90/B10) | 72000h tq +25°C |

TARGETTI

CCIAA Firenze
Share Capital: € 500.000,00
VAT N. (IT): 01537660480
R.E.A: FI-275656

Targetti Sankey S.r.l.
Via Giuseppe Garibaldi, 82
50041 Calenzano (FI)
Italy

Tel: +39 055 37911
targetti.com
targetti@targetti.com

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.
Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.

## Technical Data

### Illuminotechnical characteristics

FL - precision optics with a black silicone cut off ring. Version with a convex faceted highly reflective anodised aluminium reflector and a holographic diffusion filter. UGR<19 (EN 12464-1).

| | |
|---|---|
| Optic | FL |
| Beam angles | FL (33°) |
| Optical efficiency | 73.71% |
| Fixture flux | 3334lm |
| Luminous efficacy | 98lm/W |
| Photobiological safety | Compliant with RG1 low risk group |

### Mechanical characteristics

Die-cast white painted anodised aluminium body and dissipator. White colour cover. The optical unit can be adjusted up to 40° on the vertical plane with a mechanical beam locking system and a graduated scale, and 358° on the horizontal plane. Trimless version with a load-bearing element for installation and finishing in plasterboard.

| | |
|---|---|
| Colour and finish | Plaster white |
| Dimensions | ØxH 156x129mm |
| Weight | 1.15Kg |
| Version | Trimless |
| Degree of protection | IP20 for recessed part |
| Degree of protection | IP40 for exposed part |

### Electrical characteristics

| | |
|---|---|
| Integrated electronic ON-OFF driver. | |
| Fixture Power | 34.1W |
| Power supply | 220-240Vac 50/60Hz |
| Insulation Class | CLASS 2 |
| Type of driver / Control | ON-OFF |
| Driver included | YES |
| SAFE FLICKER | PstLM=<1 and SVM=<0.4 (IEC TR 61547-1 and IEC TR 63158), to ensure a more comfortable and safe light |
| Ambient temperature | 0°C / +25°C |

### Installation

Quick tool-free mounting system for false ceiling installation from 0.5 to 30mm.

### Notes

110-277Vac version available on request.

### Regulations and Certifications

CE

### Warranty

5 years.

## Technical Data

## Warning

Luminaire designed for disposal/recycling at end-of-life. Replaceable (LED only) light source by a professional. Replaceable control gear by a professional.

TARGETTI

CCIAA Firenze
Share Capital: € 500.000,00
VAT N. (IT): 01537660480
R.E.A: FI-275656

Targetti Sankey S.r.l.
Via Giuseppe Garibaldi, 82
50041 Calenzano (FI)
Italy


Tel: +39 055 37911
targetti.com
targetti@targetti.com

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.
Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.

## Accessories

### Filter



| CODE | Ø |
|---|---|
| 1T8094 | 63mm |

Holographic PMMA filter with blade of light effect.
Allows the beam to be made oval; combined with spot and flood optics the effect appears more pronounced.

Cannot be used with HO versions.

### Grid



| CODE | Ø |
|---|---|
| 1T8093 | 63mm |

Anti-glare louver.
Black painted metal honeycomb structure.

Cannot be used with HO versions.

### Mounting System



| CODE | L |
|---|---|
| 1T9606 | 2500mm |

Anti-fall safety cable to secure the body of the appliance to the building structure.

TARGETTI

CCIAA Firenze
Share Capital: € 500.000,00
VAT N. (IT): 01537660480
R.E.A: FI-275656

Targetti Sankey S.r.l.
Via Giuseppe Garibaldi, 82
50041 Calenzano (FI)
Italy

Tel: +39 055 37911
targetti.com
targetti@targetti.com

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.
Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.