
TRACK PROJECTORS


Ray 115 Lens



Code
T032FLL930ELDB


LIGHT COLOUR	LIGHT DISTRIBUTION	OUTPUT
3000K 90	FL 36°	29.5W 2464lm

POWER SUPPLY CONTROL	COLOUR
220-240Vac ON-OFF	



The figures on the drawing are expressed in mm.





3000K		H(m)	D(m)	Emax(lx)
Ra90			36°	
Fixture Power	30W	1	0.64	6974
Source Flux	3054lm	2	1.28	1744
Fixture Flux	2464lm	3	1.92	775
Efficacy	83lm/W	4	2.57	436
Imax	6974cd	5	3.21	279

Technical Data

Concept

Professional adjustable LED projector.

Source

High efficiency Chip on Board LED Ra90. Ra97 on request.	
Energy efficiency class	D
Nominal power	26W
Nominal flux	3054lm
Colour rendering index	90
Rf	92
Rg	101
CCT nominal	3000K
Lifetime (L80/B10)	72000h tq +25°C
Lifetime (L90/B10)	72000h tq +25°C

TARGETTI

CCIAA Firenze
Share Capital: € 500.000,00
VAT N. (IT): 01537660480
R.E.A: FI-275656

Targetti Sankey S.r.l.
Via Giuseppe Garibaldi, 82
50041 Calenzano (FI)
Italy

Tel: +39 055 37911
targetti.com
targetti@targetti.com

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.
Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.

Technical Data

Illuminotechnical characteristics

Optical grade PMMA TIR lens. Interchangeable lenses available as accessories (excluding the Narrow Spot optic).

Optic	FL
Beam angles	FL
Optical efficiency	80.67%
Fixture flux	2464lm
Luminous efficacy	84lm/W
Photobiological safety	Compliant with RG1 low risk group

Mechanical characteristics

Painted die-cast aluminium body. Black painted polycarbonate front ring. Adjustable from 0° to -90° on the vertical plane and 359° on the horizontal plane. Mechanical beam locking system on the vertical plane and friction beam locking system on the horizontal plane. The centre of gravity always remains in axis with the track regardless of the aiming.

Colour and finish	Deep black
Dimensions	ØxH 115x163mm
Weight	1.2Kg
Degree of protection	IP20

Electrical characteristics

ON-OFF electronic driver integrated into the track adapter.

Fixture Power	29.5W
Power supply	220-240Vac 50/60Hz
Insulation Class	CLASS 2
Type of driver / Control	ON-OFF
Driver included	YES
Ambient temperature	0°C / +25°C

Installation

Electrified track mounting. Optical accessories that can be installed with a support ring are available.

Regulations and Certifications

CE

Warranty

5 years.

Warning

Luminaire designed for disposal/recycling at end-of-life. Replaceable (LED only) light source by a professional. Replaceable control gear by a professional.

Accessories

Screen



CODE	COLOUR
A079	●

Black polycarbonate accessory holder ring.



CODE	Ø
1T3143	80mm

Black painted anodized diffusive aluminium asymmetric screen.
Complete with blade light filter.
Ideal for a Wall Washer effect.
To be combined with spot and flood optics.

For RAY 115 versions with lens.

Grid



CODE	Ø
1T1711	70mm

Anti-glare louver.
Black painted metal honeycomb structure.

To be completed with a dedicated holder ring A079.
For RAY 115 versions with lens.

Filter



CODE	Ø
1T1708	70mm

Flat striped glass blade light refractive filter.
This makes the beam take on an oval shape and when combined with spotlights, the light blade appears more prominent.

To be completed with a dedicated holder ring A079.
For RAY 115 versions with lens.

Cut-off



CODE	Ø
1T3142	80mm

Cut-off Tube.
Allows for the beam to be focused while removing the fall-off component.

Ray Shade



CODE	Ø
A025	118mm

Adjustable barn doors flaps made of black painted steel.

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.
Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.

Optic



CODE	OPTIC	Ø
A057SPL	SP 17°	70mm
A057MFL	FL 26°	70mm
A057FLL	FL 36°	70mm

Interchangeable optical grade PMMA lenses.
Available in Spot and Flood beams.

The accessory in not compatible with RAY 115 NSL versions.

TARGETTI

CCIAA Firenze
Share Capital: € 500.000,00
VAT N. (IT): 01537660480
R.E.A: FI-275656

Targetti Sankey S.r.l.
Via Giuseppe Garibaldi, 82
50041 Calenzano (FI)
Italy

Tel: +39 055 37911
targetti.com
targetti@targetti.com

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.
Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.