


PROJECTORS

Dart Small Integrated driver

Code
1E3056EL

LIGHT COLOUR	LIGHT DISTRIBUTION	OUTPUT
3000K 80	NSP 9°	5.2W 147lm
POWER SUPPLY CONTROL	COLOUR	
220-240Vac ON-OFF		



The figures on the drawing are expressed in mm.



Technical Data

Concept

Professional adjustable LED projector.

Source

High efficiency Ra80 LED Emitter.

Energy efficiency class	G
Nominal power	2,7W
Nominal flux	200lm
Colour rendering index	80
R _f	82.9
R _g	98.8
CCT nominal	3000K
SDCM	2
Lifetime (L80/B10)	100000h tq +25°C
Lifetime (L90/B10)	72000h tq +25°C

TARGETTI

CCIAA Firenze
Share Capital: € 500.000,00
VAT N. (IT): 01537660480
R.E.A: FI-275656

Targetti Sankey S.r.l.
Via Giuseppe Garibaldi, 82
50041 Calenzano (FI)
Italy

Tel: +39 055 37911
targetti.com
targetti@targetti.com

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.
Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.

Technical Data

Illuminotechnical characteristics

Equipped with methacrylate lenses.

Optic	NSP
Beam angles	NSP
Optical efficiency	73.57%
Fixture flux	147lm
Luminous efficacy	28lm/W
Photobiological safety	Compliant with RG1 low risk group

Mechanical characteristics

Painted die-cast anodised aluminium body and painted stainless steel mounting bracket. $\pm 20^\circ$ rotation on the horizontal plane and 0-180° on the vertical plane.

Colour and finish	Ferrite
Dimensions	AxBxH 76x69x103mm
Weight	1.04Kg
Degree of protection	IP66
Mechanical Resistance	IK10

Electrical characteristics

Integrated electronic power supply. Pre-cabled with a 1.5m H07RN-F cable.

Fixture Power	5.2W
Power supply	220-240Vac 50/60Hz
Insulation Class	CLASS 2
Type of driver / Control	ON-OFF
Driver included	YES
Ambient temperature	-25°C / +35°C

Installation

Mounting bracket with aiming adjustability.

Notes

Uses the "Waterblock Smart" technical solution that involves resin coating the connection cables, limiting the risk of humidity reaching the driver or the fixture. It is possible to subject the product to Cataphoresis treatment on request. 110-277Vac version available on request.

Warranty

5 years.

Warning

Luminaire designed for disposal/recycling at end-of-life. Replaceable (LED only) light source by a professional. Replaceable control gear by a professional.

TARGETTI

CCIAA Firenze
Share Capital: € 500.000,00
VAT N. (IT): 01537660480
R.E.A: FI-275656

Targetti Sankey S.r.l.
Via Giuseppe Garibaldi, 82
50041 Calenzano (FI)
Italy

Tel: +39 055 37911
targetti.com
targetti@targetti.com

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.
Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. $t_q +25^\circ\text{C}$ (CIE 121).

We reserve the right to make technical changes.

Accessories

Filter



CODE	Ø
1E3012	53mm

Blade of light filter.
PMMA holographic filter for a blade of light effect.
To be completed with a dedicated holder ring.

Grid



CODE	COLOUR
1E3014	

Anti-glare louver.
The central elements may be removed to obtain two different levels of glare control.
Powder coated stainless steel.

Screen



CODE	COLOUR
1E3013	

Asymmetric screen.
Powder coated stainless steel.

Mounting System



CODE	COLOUR
1E3015	

Plate for fixture rotation.
Powder coated stainless steel.



CODE	COLOUR	ØXH
1E3016		70x182mm

Earths spike.
Powder coated stainless steel.

Holder Ring



CODE	COLOUR	L
1E3011		66mm

Holder ring.
Powder coated stainless steel.

Accessories

Connector




CODE

1E2769

Linear connection box IP66/IP68.
5 poles max. wire section 1.5mm².
Cable diameter range from 7 to 12mm.

Surge protector



CODE

A013B

Surge protector compatible with CLASS II lighting fixtures and electronic drivers.
Operating voltage 220-240Vac.
SPD type 2+3.
Max surge protection 10kV.
CLASS II
IP67

TARGETTI

CCIAA Firenze
Share Capital: € 500.000,00
VAT N. (IT): 01537660480
R.E.A: FI-275656

Targetti Sankey S.r.l.
Via Giuseppe Garibaldi, 82
50041 Calenzano (FI)
Italy

Tel: +39 055 37911
targetti.com
targetti@targetti.com

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.
Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.