

LIGHTING SYSTEMS

Logico Easy System

57 - Opal / UGR19 -


Linear module

Emergency

Code

T009MX830ELPW

| LIGHT COLOUR                                | LIGHT DISTRIBUTION                                                                | OUTPUT             |
|---------------------------------------------|-----------------------------------------------------------------------------------|--------------------|
| 3000K<br>80                                 | Opal/UGR19                                                                        | 34W<br>3013-3055lm |
| POWER SUPPLY CONTROL                        | COLOUR                                                                            |                    |
| 220-240Vac<br>ON-OFF<br>(EMERGENCY VERSION) |  |                    |



The figures on the drawing are expressed in mm.



The fixture's photometric values  
can be found on the following pages

Technical Data

Concept

LED luminaire for ceiling or suspended system installation. Emergency linear module.

Source

LED Engine made of linear LED boards Ra80.

|                         |                  |
|-------------------------|------------------|
| Energy efficiency class | D                |
| Nominal power           | 30W              |
| Nominal flux            | See photometries |
| Colour rendering index  | 80               |
| Rf                      | 84               |
| Rg                      | 95               |
| CCT nominal             | 3000K            |
| Lifetime (L80/B10)      | 100000h tq +25°C |
| Lifetime (L90/B10)      | 50000h tq +25°C  |

TARGETTI

CCIAA Firenze  
Share Capital: € 500.000,00  
VAT N. (IT): 01537660480  
R.E.A: FI-275656

Targetti Sankey S.r.l.  
Via Giuseppe Garibaldi, 82  
50041 Calenzano (FI)  
Italy  
  
Tel: +39 055 37911  
targetti.com  
targetti@targetti.com

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.  
Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).  
  
We reserve the right to make technical changes.

## Technical Data

### Illuminotechnical characteristics

Direct emission in two effect variants: diffused light - OPAL optics - and controlled light - UGR19 optics. Diffused light - OPAL optic: optical system made of a steel reflector with white polymer coating and a closing diffuser screen in opal anti-glare polycarbonate supplied in unrollable reels and available as a related code. Controlled light - UGR19 optic: optical system made of a steel reflector with white polymer coating and UGR closing diffuser screen supplied in unrollable reels and available as a related code (UGR<19 and L65<3000 cd/m² EN-12464-1).

|                            |                                      |
|----------------------------|--------------------------------------|
| Emission                   | Direct                               |
| Optic                      | Opal/UGR19                           |
| Optical efficiency         | 100%                                 |
| Fixture flux               | See photometries                     |
| Emergency fixture flux BLF | 13%                                  |
| Luminous efficacy          | See photometries                     |
| Photobiological safety     | Compliant with RGO exempt risk group |

### Mechanical characteristics

Painted extruded aluminium body with 57mm section. Upper closing screen in white PVC.

|                       |                    |
|-----------------------|--------------------|
| Colour and finish     | White              |
| Dimensions            | AxBxH 2336x57x80mm |
| Weight                | 5.955Kg            |
| Version               | Linear             |
| Degree of protection  | IP40               |
| Mechanical Resistance | IK02               |

### Electrical characteristics

Integrated electronic ON-OFF driver. "Easy Connection" system for a quick connection between the modules of the system thanks to the pre-assembled plug/socket connection elements. Preset for through wiring allowing to reach a maximum length of 18 meters. Equipped with emergency pack - permanent emergency (1h autonomy and 24h recharge).

|                          |                                                                                                      |
|--------------------------|------------------------------------------------------------------------------------------------------|
| Fixture Power            | 34W                                                                                                  |
| Power supply             | 220-240Vac 50/60Hz                                                                                   |
| Insulation Class         | CLASS 1                                                                                              |
| Type of driver / Control | ON-OFF (EMERGENCY VERSION)                                                                           |
| Driver included          | YES                                                                                                  |
| SAFE FLICKER             | PstLM=<1 and SVM=<0.4 (IEC TR 61547-1 and IEC TR 63158), to ensure a more comfortable and safe light |
| Ambient temperature      | 0°C / +25°C                                                                                          |
| Relative humidity UR     | <85%                                                                                                 |

### Installation

To be completed with polycarbonate end caps, mounting systems for surface or suspended application and terminal block for connection to the power line.

### Notes

For angular configurations L light modules and the L blind joint accessory are available. Commissioning of the control system via free APP; the intervention of a specialist technician can be quoted on request.

# TARGETTI

CCIAA Firenze  
Share Capital: € 500.000,00  
VAT N. (IT): 01537660480  
R.E.A: FI-275656

Targetti Sankey S.r.l.  
Via Giuseppe Garibaldi, 82  
50041 Calenzano (FI)  
Italy

Tel: +39 055 37911  
targetti.com  
targetti@targetti.com

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.  
Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.

**Technical Data****Regulations and Certifications**

---

CE

**Warranty**

---

5 years.

**Warning**

---

Luminaire designed for disposal/recycling at end-of-life. Replaceable (LED only) light source by a professional.  
Replaceable control gear by a professional.

---

**TARGETTI**

CCIAA Firenze  
Share Capital: € 500.000,00  
VAT N. (IT): 01537660480  
R.E.A: FI-275656

Targetti Sankey S.r.l.  
Via Giuseppe Garibaldi, 82  
50041 Calenzano (FI)  
Italy

Tel: +39 055 37911  
targetti.com  
targetti@targetti.com

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.  
Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.

Photometries

OP

Nominal flux

3055lm

Fixture flux

3055lm

Luminous efficacy

90lm/W

</

## Related codes

## Screen



| CODE | DIMENSIONS |
|------|------------|
|------|------------|

|         |      |
|---------|------|
| A001ML1 | L=6m |
|---------|------|

|         |      |
|---------|------|
| A001ML2 | L=9m |
|---------|------|

|         |       |
|---------|-------|
| A001ML3 | L=15m |
|---------|-------|

UGR19 screen (Direct Emission).

For LOGICO EASY System 57 - UGR19.



| CODE | DIMENSIONS |
|------|------------|
|------|------------|

|         |      |
|---------|------|
| A002ML1 | L=6m |
|---------|------|

|         |      |
|---------|------|
| A002ML2 | L=9m |
|---------|------|

|         |       |
|---------|-------|
| A002ML3 | L=15m |
|---------|-------|

OPAL screen (Direct Emission).

For LOGICO EASY System 57 - OPAL.

## Accessories

## Electrical Connector



| CODE | COLOUR | DRIVER |
|------|--------|--------|
|------|--------|--------|

|          |   |        |
|----------|---|--------|
| A014MELW | ○ | ON-OFF |
|----------|---|--------|

L-shaped blind joint.

Sizes 818x818x80mm.  
For LOGICO EASY System 57.

## End Caps



| CODE | COLOUR |
|------|--------|
|------|--------|

|         |   |
|---------|---|
| A003M2W | ○ |
|---------|---|

End caps (2 pieces).

For LOGICO EASY System 57 - OPAL / UGR19.

## Canopy



| CODE | COLOUR |
|------|--------|
|------|--------|

|       |   |
|-------|---|
| A004W | ○ |
|-------|---|

Canopy with 5 poles terminal block.  
Feeding cable not included.

## Accessories

## Cover Panel



CODE

COLOUR

A005MW



Joint for screens.  
To be used for configurations longer than 15 meters.

For LOGICO EASY System 57.

## Bracket



CODE

A006M

Bracket for ceiling installation (2 pieces).  
Two brackets needed for each lighting module.

For LOGICO EASY 57.



CODE

A007M

Bracket with adjustment system for suspended installation (2 pieces).  
Two brackets needed for each lighting module.

For LOGICO EASY 57.

## Suspension



CODE

VERSION

A008T

L = 6m

A008U

L = 5m

A008V

L = 4m

A008W

L = 3m

A008X

L = 2m

A008Y

L = 1m

A008Z

L = 0,5m

Suspension cable (2 pieces).

## Terminal Box



CODE

VERSION

A009Z

3 Poli ON-OFF

Terminal block (plug/socket).  
One for each power supply.

A009Z - For LOGICO EASY 37 | 57 | 100.

# TARGETTI

CCIAA Firenze  
Share Capital: € 500.000,00  
VAT N. (IT): 01537660480  
R.E.A: FI-275656

Targetti Sankey S.r.l.  
Via Giuseppe Garibaldi, 82  
50041 Calenzano (FI)  
Italy

Tel: +39 055 37911  
targetti.com  
targetti@targetti.com

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.  
Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.