


TRACK PROJECTORS

Label 7

Code
IT8162EL90

LIGHT COLOUR	LIGHT DISTRIBUTION	OUTPUT
3000K 90	FL 26°	29.5W 2489lm
POWER SUPPLY CONTROL	COLOUR	
220-240Vac ON-OFF		



The figures on the drawing are expressed in mm.



Technical Data

Concept

Professional adjustable LED projector.

Source

High efficiency Chip on Board LED Ra90. 2700K-3500K on request.

Energy efficiency class	D
Nominal power	26W
Nominal flux	3054lm
Colour rendering index	90
Rf	92
Rg	101
CCT nominal	3000K
SDCM	1.5
Lifetime (L80/B10)	72000h tq +25°C
Lifetime (L90/B10)	72000h tq +25°C

TARGETTI

CCIAA Firenze
Share Capital: € 500.000,00
VAT N. (IT): 01537660480
R.E.A: FI-275656

Targetti Sankey S.r.l.
Via Giuseppe Garibaldi, 82
50041 Calenzano (FI)
Italy

Tel: +39 055 37911
targetti.com
targetti@targetti.com

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.
Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.

Technical Data

Illuminotechnical characteristics

FL - precision optics with a black silicone cut off ring. Version with a transparent PMMA lens.

Optic	FL
Beam angles	FL
Optical efficiency	81.5%
Fixture flux	2489lm
Luminous efficacy	84lm/W
Photobiological safety	Compliant with RG1 low risk group

Mechanical characteristics

Painted die-cast aluminium body. The optical unit can be adjusted from 0° a 90° on the vertical plane and 355° on the horizontal plane with the possibility to block the beam on the horizontal plane (friction locking system on the vertical plane).

Colour and finish	Deep black
Dimensions	ØxH 74x130mm
Weight	0.69Kg
Degree of protection	IP20

Electrical characteristics

Electronic ON-OFF power supply for track.

Fixture Power	29.5W
Power supply	220-240Vac 50/60Hz
Insulation Class	CLASS 2
Type of driver / Control	ON-OFF
Driver included	YES
Ambient temperature	0°C / +25°C

Notes

The arm is and the adapter are supplied in the same colour as the body of the projector.

Warranty

5 years.

Warning

Luminaire designed for disposal/recycling at end-of-life. Replaceable (LED only) light source by a professional. Replaceable control gear by a professional.

TARGETTI

CCIAA Firenze
Share Capital: € 500.000,00
VAT N. (IT): 01537660480
R.E.A: FI-275656

Targetti Sankey S.r.l.
Via Giuseppe Garibaldi, 82
50041 Calenzano (FI)
Italy

Tel: +39 055 37911
targetti.com
targetti@targetti.com

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.
Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.

Accessories

Filter



CODE	Ø
1T8094	63mm

Holographic PMMA filter with blade of light effect.
Allows the beam to be made oval; combined with spot and flood optics the effect appears more pronounced.

Grid



CODE	Ø
1T8093	63mm

Anti-glare louver.
Black painted metal honeycomb structure.