

LIGHTING SYSTEMS

Logico Easy System 57 - Opal / UGR19 - Linear module Emergency

Code

T009BX830ELPW

LIGHT COLOUR	LIGHT DISTRIBUTION	OUTPUT
3000K 80	Opal/UGR19	79W 8157-8199lm
POWER SUPPLY CONTROL	COLOUR	
220-240Vac ON-OFF (EMERGENCY VERSION)		



The figures on the drawing are expressed in mm.

The fixture's photometric values
can be found on the following pages

Technical Data

Concept

LED luminaire for ceiling or suspended system installation. Emergency linear module.

Source

LED Engine made of linear LED boards Ra80.

Energy efficiency class	D
Nominal power	70W
Nominal flux	See photometries
Colour rendering index	80
Rf	84
Rg	95
CCT nominal	3000K
Lifetime (L80/B10)	100000h tq +25°C
Lifetime (L90/B10)	50000h tq +25°C

TARGETTI

CCIAA Firenze
Share Capital: € 500.000,00
VAT N. (IT): 01537660480
R.E.A: FI-275656

Targetti Sankey S.r.l.
Via Giuseppe Garibaldi, 82
50041 Calenzano (FI)
Italy

Tel: +39 055 37911
targetti.com
targetti@targetti.com

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.
Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.

Technical Data

Illuminotechnical characteristics

Direct/indirect emission in two effect variants: diffused light - OPAL optics - and controlled light - UGR19 optics. Diffused light - OPAL optic: optical system made of a steel reflector with white polymer coating and a closing diffuser screen in opal anti-glare polycarbonate supplied in unrollable reels and available as a related code. Controlled light - UGR19 optic: optical system made of a steel reflector with white polymer coating and UGR closing diffuser screen supplied in unrollable reels and available as a related code (UGR<19 and L65<3000 cd/m² EN-12464-1).

Emission	Direct/Indirect
Optic	Opal/UGR19
Optical efficiency	100%
Fixture flux	See photometries
Emergency fixture flux BLF	13%
Luminous efficacy	See photometries
Photobiological safety	Compliant with RGO exempt risk group

Mechanical characteristics

Painted extruded aluminium body with 57mm section. Upper closing screen in translucent polycarbonate.

Colour and finish	White
Dimensions	AxBxH 2336x57x80mm
Weight	6.405Kg
Version	Linear
Degree of protection	IP40
Mechanical Resistance	IK02

Electrical characteristics

Integrated electronic ON-OFF driver. "Easy Connection" system for a quick connection between the modules of the system thanks to the pre-assembled plug/socket connection elements. Preset for through wiring allowing to reach a maximum length of 18 meters. Equipped with emergency pack - permanent emergency (1h autonomy and 24h recharge).

Fixture Power	79W
Power supply	220-240Vac 50/60Hz
Insulation Class	CLASS 1
Type of driver / Control	ON-OFF (EMERGENCY VERSION)
Driver included	YES
SAFE FLICKER	PstLM=<1 and SVM=<0.4 (IEC TR 61547-1 and IEC TR 63158), to ensure a more comfortable and safe light
Ambient temperature	0°C / +25°C
Relative humidity UR	<85%

Installation

To be completed with polycarbonate end caps, mounting systems for surface or suspended application and terminal block for connection to the power line.

Notes

For angular configurations L light modules and the L blind joint accessory are available. Commissioning of the control system via free APP; the intervention of a specialist technician can be quoted on request.

TARGETTI

CCIAA Firenze
Share Capital: € 500.000,00
VAT N. (IT): 01537660480
R.E.A: FI-275656

Targetti Sankey S.r.l.
Via Giuseppe Garibaldi, 82
50041 Calenzano (FI)
Italy

Tel: +39 055 37911
targetti.com
targetti@targetti.com

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.
Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.

Technical Data**Regulations and Certifications**

CE

Warranty

5 years.

Warning

Luminaire designed for disposal/recycling at end-of-life. Replaceable (LED only) light source by a professional.
Replaceable control gear by a professional.

TARGETTI

CCIAA Firenze
Share Capital: € 500.000,00
VAT N. (IT): 01537660480
R.E.A: FI-275656

Targetti Sankey S.r.l.
Via Giuseppe Garibaldi, 82
50041 Calenzano (FI)
Italy


Tel: +39 055 37911
targetti.com
targetti@targetti.com

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.
Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).


We reserve the right to make technical changes.

Photometries

OP

Fixture flux	8199lm		<table><tr><td>Source Flux</td><td>8199lm</td><td>2</td><td>5.80</td><td>275</td></tr><tr><td>Fixture Flux</td><td>8199lm</td><td>3</td><td>8.70</td><td>122</td></tr><tr><td>Efficacy</td><td>104lm/W</td><td>4</td><td>11.60</td><td>69</td></tr><tr><td>G0300A</td><td>I_{max}=222cd/klm</td><td>I_{max}</td><td>1821cd</td><td>5</td><td>14.49</td><td>44</td></tr></table>				Source Flux	8199lm	2	5.80	275	Fixture Flux	8199lm	3	8.70	122	Efficacy	104lm/W	4	11.60	69	G0300A	I _{max} =222cd/klm	I _{max}	1821cd	5	14.49	44
Source Flux	8199lm		2	5.80	275																							
Fixture Flux	8199lm		3	8.70	122																							
Efficacy	104lm/W		4	11.60	69																							
G0300A	I _{max} =222cd/klm	I _{max}	1821cd	5	14.49	44																						
Luminous efficacy	104lm/W																											

UGR

Nominal flux	8157lm		<table><tr><td>3000K</td><td>H(m)</td><td>D1(m)</td><td>D2(m)</td><td>Emax(lx)</td></tr><tr><td>Ra80</td><td></td><td>83°</td><td>89°</td><td></td></tr><tr><td>Fixture Power</td><td>79W</td><td>1</td><td>1.78</td><td>1.97</td><td>1665</td></tr><tr><td>Source Flux</td><td>8157lm</td><td>2</td><td>3.56</td><td>3.94</td><td>416</td></tr><tr><td>Fixture Flux</td><td>8158lm</td><td>3</td><td>5.33</td><td>5.91</td><td>185</td></tr><tr><td>Efficacy</td><td>103lm/W</td><td>4</td><td>7.11</td><td>7.88</td><td>104</td></tr><tr><td>G0300</td><td>I_{max}=226cd/klm</td><td>I_{max}</td><td>1841cd</td><td>5</td><td>8.89</td><td>9.85</td><td>67</td></tr></table>				3000K	H(m)	D1(m)	D2(m)	Emax(lx)	Ra80		83°	89°		Fixture Power	79W	1	1.78	1.97	1665	Source Flux	8157lm	2	3.56	3.94	416	Fixture Flux	8158lm	3	5.33	5.91	185	Efficacy	103lm/W	4	7.11	7.88	104	G0300	I _{max} =226cd/klm	I _{max}	1841cd	5	8.89	9.85	67
3000K	H(m)		D1(m)	D2(m)	Emax(lx)																																											
Ra80			83°	89°																																												
Fixture Power	79W		1	1.78	1.97	1665																																										
Source Flux	8157lm	2	3.56	3.94	416																																											
Fixture Flux	8158lm	3	5.33	5.91	185																																											
Efficacy	103lm/W	4	7.11	7.88	104																																											
G0300	I _{max} =226cd/klm	I _{max}	1841cd	5	8.89	9.85	67																																									
Fixture flux	8157lm																																															
Luminous efficacy	103lm/W																																															

Related codes

Screen



CODE	DIMENSIONS
------	------------

A001ML1	L=6m
---------	------

A001ML2	L=9m
---------	------

A001ML3	L=15m
---------	-------

UGR19 screen (Direct Emission).

For LOGICO EASY System 57 - UGR19.



CODE	DIMENSIONS
------	------------

A002ML1	L=6m
---------	------

A002ML2	L=9m
---------	------

A002ML3	L=15m
---------	-------

OPAL screen (Direct Emission).

For LOGICO EASY System 57 - OPAL.

Accessories

Electrical Connector



CODE	COLOUR	DRIVER
------	--------	--------

A014MELW	○	ON-OFF
----------	---	--------

L-shaped blind joint.

Sizes 818x818x80mm.
For LOGICO EASY System 57.

End Caps



CODE	COLOUR
------	--------

A003M2W	○
---------	---

End caps (2 pieces).

For LOGICO EASY System 57 - OPAL / UGR19.

Canopy



CODE	COLOUR
------	--------

A004W	○
-------	---

Canopy with 5 poles terminal block.
Feeding cable not included.

Cover Panel



CODE	COLOUR
A005MW	○



Joint for screens.

To be used for configurations longer than 15 meters.

For LOGICO EASY System 57.

Bracket



CODE
A007M

Bracket with adjustment system for suspended installation (2 pieces).

Two brackets needed for each lighting module.

For LOGICO EASY 57.

Suspension



CODE	VERSION
A008T	L = 6m
A008U	L = 5m
A008V	L = 4m
A008W	L = 3m
A008X	L = 2m
A008Y	L = 1m
A008Z	L = 0,5m

Suspension cable (2 pieces).

Terminal Box



CODE	VERSION
A009Z	3 Poli ON-OFF

Terminal block (plug/socket).

One for each power supply.

A009Z - For LOGICO EASY 37 | 57 | 100.