

Ceiling, Suspensions and Wall

CCTLED PENDANT



TARGETTI

CCTLED PENDANT

GENERAL INFO

Suspension with diffused
downlight for high output
LED lamps.
Ø317mm

LED

Chip on Board
From 2756lm to 3755lm
3000K – 4000K
Ra80 - Ra90

PRODUCT EFFICACY

Up to 84lm/W

OPTICS

FL

POWER SUPPLY

Electronic – DALI -
Emergency - DALI
Emergency
Casambi control system
available using a dedicated
accessory (only for DALI
version products).

MATERIAL

Black painted metal
canopy and black painted
die-cast aluminium heat
sink. Microprismatic
transparent polycarbonate
dome refractor optic.

ON DEMAND



Easy Custom Colour



Ra97



2700K - 3500K

A professional suspension fixture from the CCTLED range. Available with a faceted transparent polycarbonate optic for diffused lighting, complete with micro prismatic dome refractor to screen the source and to distribute the light softly.




Indoor

CCTLED PENDANT



Ambient



LED / 18W / FL



	Kg	Driver	3000K	4000K
	2	EL.	1T3274	1T3275
	2	DALI	1T3298	1T3299
	2.7	EL. EM.	1T3322	1T3323
	2.7	DALI EM.	1T3346	1T3347

LED / 25W / FL



	Kg	Driver	3000K	4000K
	2	EL.	1T3272	1T3273
	2	DALI	1T3296	1T3297
	2.7	EL. EM.	1T3320	1T3321
	2.7	DALI EM.	1T3344	1T3345

Note

Ra90: to order this version it is necessary to add the suffix “90” at the end of the standard code (Ra80).

Accessories

Decorative Ring



	Colour	Code
		1T4061
		1T4062

Dissipator cover.

Control systems



	Code
	1T5349

Wireless control unit for DALI fixtures.

It generates a local DALI bus that can control individual fixtures.

The module can be connected to an existing DALI network.

The module is wireless controlled using a Casambi app for smartphones and tablets using Bluetooth 4.0 technology.

The devices create a wireless mesh network that can control up to 128 fixtures.

IP20.

LxHxP=56.5x22.3x35.8mm.



Code
1T5352

IP20 Extender for wireless control of DALI fixtures.

It generates a local DALI bus with the capacity to drive up to 64 fixtures.

Can control DALI fixtures in indoor applications via the Casambi application.

It is also equipped with a relay that can control non-dimmable fixtures up to a maximum of 6A.

LxHxP=129x30x42mm.

Requisites and information

All fixtures of the Targetti collection have been designed and produced to comply with European Standard EN60598-1 relative to the safety requisite of light fixtures.



All fixtures comply with the following directives:

- EMC Directive 2014/30/EU
- LV Directive 2014/35/EU
- RoHS Directive 2011/65/EU

Unless specified otherwise

- all fixtures are supplied without lamps;
- all fixtures are sold separately;
- all measurements are expressed in millimeters;
- all fixtures at low voltage are supplied without transformer;
- For products in Class III performance is only guaranteed using the electronic power supplies and drivers indicated in the catalogue.

Consorzio ecolight

Targetti Sankey Spa is a member of the Ecolight consortium that was set up in 2004 (D.Lgs. 49/2014) to comply with the provisions of the European Directive that was adopted in Italy as the European Directive 2012/19/EU for WEEE on managing, recovering and treating waste electrical and electronic equipment, used batteries and accumulators in compliance with all applicable legislation.

The colors of the products illustrated are reproduced as faithfully as possible compatibly with the technical limitations of the printed medium. The company reserves the right to make changes to the production without notice. Reproduction of this catalogue or any part of it is prohibited. The products illustrated in this catalogue are covered by one or more Italian or international patents. The company will take legal action against any imitators.



TARGETTI SANKEY SpA

Certificated ISO 9001 n° 9130. TAR1
Certificated ISO 14001 n° IT319206

The Enec mark, ISO9001 and ISO14001 certifications and the CE marking all guarantee that the activities carried out internally in the company are governed and controlled by procedures which assure constant level of quality.

Accredited laboratory in accordance with ISO 17025.

Light beam apertures

from	to	beam	
5°	10°	Narrow Spot	NSP
11°	25°	Spot	SP
26°	40°	Flood	FL
41°	50°	Medium Wide Flood	MWFL
51°	70°	Wide Flood	WFL
71°	120°	Very Wide Flood	VWFL
		Wall Washer	WW
		Narrow Asymmetric	N. ASYM
		Asymmetric	ASYM

Icons legend

	Class I luminaire in which the protection against electrical shock is guaranteed by the connections of the conductive elements accessible to a protective conductor (earth connection).
	Luminaire in which the connection to a protective conductor (earth connection) guarantees the immunity to radio noises.
	Class II luminaire (double insulation), protected against the accidental contact with parts under tension from the user.
	Class III luminaire, suitable for connection to very low voltage circuits.
	Solid particle and liquid ingress protection degree.
	Protection degree - Recessed part . Protection degree - Exposed part.
	Impact protection degree.
	ENEC European Norms Electrical Certification.

Particular symbols

	Weight of the single fixture.
	Cable length.
	Walk-over.
	Driver-over safe.
	Fixtures that have parameters below the minimum visibility threshold $PstLM \leq 1$ and $SVM \leq 0.4$ (IEC TR 61547-1 and IEC TR 63158).
DBS	Dynamic Beam Shaper optical technology with remote management of the beam opening.
	LED with $Ra_{\text{---}}$ where not present in the catalogue, available on request.
	Different colour temperatures available on request.
	Custom finish of your choice from the Targetti Colours range and RAL indicated in the colour chart can be downloaded on line from the download section.
	Treatment carried out on request.
	Supplied on request with an integrated or remote 110-277Vac power supply as indicated for the standard model.
	LED version with a different "Tunable White" tone available on request.

Note

- ➔ Please contact us for on demand treatments and versions.
- ➔ The performances reported on the products refer to the use of the recommended drivers.
- ➔ The drivers selected by Targetti make the fixtures "Safe Flicker".

