


LIGHTING SYSTEMS

Ivy Single projector

Code

1E4197EL

LIGHT COLOUR	LIGHT DISTRIBUTION	OUTPUT
3000K 90	WFL 53°	6.6W 554lm
POWER SUPPLY CONTROL	COLOUR	
48Vdc	○	



The figures on the drawing are expressed in mm.



	3000K	H(m)	D(m)	E _{max} (lx)		
	Ra90		53°			
	Fixture Power	7W	1	1.00	684	
	Source Flux	786lm	2	2.00	171	
	Fixture Flux	554lm	3	3.01	76	
	Efficacy	84lm/W	4	4.01	43	
	TS1647	I _{max} =871cd/klm	I _{max}	684cd	5	5.01

Technical Data

Concept

Adjustable LED 1x light module, powered at low voltage, to be installed into the installation profile.

Source

High efficiency Chip on Board LED Ra90.

Energy efficiency class	F
Nominal power	5,9W
Nominal flux	786lm
Colour rendering index	90
R _f	92
R _g	101
CCT nominal	3000K
SDCM	3
Lifetime (L80/B10)	52000h tq +25°C
Lifetime (L90/B10)	52000h tq +25°C

TARGETTI

CCIAA Firenze
Share Capital: € 500.000,00
VAT N. (IT): 01537660480
R.E.A: FI-275656

Targetti Sankey S.r.l.
Via Giuseppe Garibaldi, 82
50041 Calenzano (FI)
Italy

Tel: +39 055 37911
targetti.com
targetti@targetti.com

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.
Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.

Technical Data

Illuminotechnical characteristics

WFL beams. Optic equipped with an acrylic collimator lens and integrated holographic diffusive filter.

Optic	WFL
Beam angles	WFL
Optical efficiency	70.55%
Fixture flux	554lm
Luminous efficacy	84lm/W
Photobiological safety	Compliant with RG1 low risk group

Mechanical characteristics

Cylindrical aluminium body obtained through CNC machining process and protected with a layer of black anodization with a minimum thickness of 15μ. Powder painted white. Tempered extra clear front glass. Aluminium joint with locking system. Adjustability of the optical unit of 90° on the vertical plane (friction locking system) and 355° on the horizontal plane with the possibility of mechanical aiming locking through no tools system. Electronic components hosted inside a polymeric plastic box sealed by a silicone rubber gasket.

Colour and finish	White
Dimensions	AxBxH 148x60x135mm
Weight	0.45Kg
Version	ON-OFF
Degree of protection	IP65

Electrical characteristics

Fixture Power	6.6W
Power supply	48Vdc
Insulation Class	CLASS 3
Ambient temperature	-25°C / +35°C

Installation

Fast connection system of the modules through anodized aluminium clips. Free positioning all over the installation profile according to installation needs with mechanical lock through Hex Key. Designed for connection in series through H05RN-F (0.15m + 0.15m) cable completed with male/female miniaturised IP65 connectors.

Notes

Electronic ON-OFF version.

Warranty

5 years.

Warning

Luminaire designed for disposal/recycling at end-of-life. Replaceable (LED only) light source by a professional. Replaceable control gear by a professional.

TARGETTI

CCIAA Firenze
Share Capital: € 500.000,00
VAT N. (IT): 01537660480
R.E.A: FI-275656

Targetti Sankey S.r.l.
Via Giuseppe Garibaldi, 82
50041 Calenzano (FI)
Italy

Tel: +39 055 37911
targetti.com
targetti@targetti.com

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.
Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.

Related codes

Power Supply



CODE	COLOUR	DRIVER
1E4169	●	ON-OFF

48Vdc driver box (IP65).

L=450mm 90W.

Equipped with connection cable H05RN-F (0.15m + 0.15m) complete with male/female IP65 connectors for 220V and miniaturized female IP65 connector for 48V.



CODE	COLOUR	DRIVER
1E4175	●	ON-OFF

48Vdc driver box (IP65).

L=450mm 150W.

Equipped with connection cable H05RN-F (0.15m + 0.15m) complete with male/female IP65 connectors for 220V and miniaturized female IP65 connector for 48V.



CODE	IP	OUTPUT VOLTAGE	POWER SUPPLY	POWER	LXHXP
1E2320	IP67	48Vdc	220-240Vac	70W	225x51x65mm
1E2321	IP67	48Vdc	220-240Vac	150W	225x51x65mm

Electronic ON-OFF power supply.

Cable length 0.5m (IN and OUT).

To be completed with Connection kit 1E4184.



CODE	IP	OUTPUT VOLTAGE	POWER SUPPLY	POWER	LXHXP
1T6917EL	IP20	48Vdc	220-240Vac	60W	225x36x60mm
1T6916EL	IP20	48Vdc	220-240Vac	130W	240x49x60mm

Electronic ON-OFF power supply.

To be completed with Connection kit 1E4184.

Accessories

Cable



CODE	L
1E4270	500mm
1E4181	1000mm
1E4182	2000mm
1E4183	3000mm

Connection cable complete with male/female connectors.

TARGETTI

CCIAA Firenze
Share Capital: € 500.000,00
VAT N. (IT): 01537660480
R.E.A: FI-275656

Targetti Sankey S.r.l.
Via Giuseppe Garibaldi, 82
50041 Calenzano (FI)
Italy

Tel: +39 055 37911
targetti.com
targetti@targetti.com

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.
Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.

Accessories

Tool



CODE

1E4171

Microscrewdriver with hexagonal head (diameter 0.9mm) for wiring 1E4184 connection kit.

Connector



CODE

1E4184

Connection kit 24/48V.

Wire not included.
Maximum cable diameter 7.5mm.
To be used for lengths >3m.



CODE

1E2769

Linear connection box IP66/IP68.
5 poles max. wire section 1.5mm².
Cable diameter range from 7 to 12mm.