

WALL MOUNTED LUMINAIRES


CCTEvo Tube 140

Wall - Direct/Indirect

Code

1T9748EL

LIGHT COLOUR	LIGHT DISTRIBUTION	OUTPUT
2700K 90	VWFL 72°	26.1W 1804lm
POWER SUPPLY CONTROL	COLOUR	
230Vac 50Hz ON-OFF		



The figures on the drawing are expressed in mm.



	2700K		H(m)	D(m)	Emax(lx)	
	Ra90			75*		
	Fixture Power	26W	1	1.52	690	
	Source Flux	3250lm	2	3.04	172	
	Fixture Flux	1804lm	3	4.57	77	
	Efficacy	69lm/W	4	6.09	43	
TS1541	Imax=241cd/klm	Imax	784cd	5	7.61	28

Technical Data

Concept

LED wall mounted fixture with direct/indirect light emission.

Source

High efficiency Chip on Board LED Ra90. Ra80 on request.

Energy efficiency class	E
Nominal power	2x11,6W
Nominal flux	3250lm
Colour rendering index	90
Rf	92
Rg	99
CCT nominal	2700K
Lifetime (L80/B10)	72000h tq +25°C
Lifetime (L90/B10)	72000h tq +25°C

TARGETTI

CCIAA Firenze
Share Capital: € 500.000,00
VAT N. (IT): 01537660480
R.E.A: FI-275656

Targetti Sankey S.r.l.
Via Giuseppe Garibaldi, 82
50041 Calenzano (FI)
Italy

Tel: +39 055 37911
targetti.com
targetti@targetti.com

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.
Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.

Technical Data

Illuminotechnical characteristics

Decorative cut-off ring in thermoplastic material. Optic composed of a thermoplastic reflector with metallic gray finish, tempered sandblasted front glass, internal recuperator in highly reflective white thermoplastic.

Emission	Direct/Indirect
Optic	VWFL
Beam angles	VWFL
Optical efficiency	55.51%
Fixture flux	1804lm
Luminous efficacy	69lm/W
Photobiological safety	Compliant with RG1 low risk group

Mechanical characteristics

Painted aluminium body. Galvanized steel Internal structure and passive heat sink in die-cast aluminum with protective cathoporesis treatment.

Colour and finish	Plaster white
Dimensions	ØxH 137x535mm
Weight	2.65Kg
Degree of protection	IP20

Electrical characteristics

Driver integrated in the body of the fixture, available in the electronic ON-OFF version. Luminaire compliant with EN 60598-2-22 for power supply from a centralised emergency system CPSS (Central Power Supply System), not incorporated in the luminaire - high risk areas excluded. The default power and flux are 100% in AC and 100% in DC.

Fixture Power	26.1W
Power supply	230Vac 50Hz
Insulation Class	CLASS 1
Type of driver / Control	ON-OFF
Driver included	YES
SAFE FLICKER	PstLM=<1 and SVM=<0.4 (IEC TR 61547-1 and IEC TR 63158), to ensure a more comfortable and safe light
Ambient temperature	0°C / +25°C

Installation

Kit with fixing plate for wall installation already included.

Warranty

5 years.

Warning

Luminaire designed for disposal/recycling at end-of-life. Replaceable (LED only) light source by a professional. Replaceable control gear by a professional.

TARGETTI

CCIAA Firenze
Share Capital: € 500.000,00
VAT N. (IT): 01537660480
R.E.A: FI-275656

Targetti Sankey S.r.l.
Via Giuseppe Garibaldi, 82
50041 Calenzano (FI)
Italy

Tel: +39 055 37911
targetti.com
targetti@targetti.com

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.
Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.