IN-GROUND LUMINAIRES


Jedi Compact Outdoor RGBW Recessed - Remote driver - L. 905mm

Code
1E4327



LIGHT COLOUR	LIGHT DISTRIBUTION	OUTPUT
RGBW	FL 33°	36W 1891lm

POWER SUPPLY CONTROL	COLOUR
500mA	



The figures on the drawing are expressed in mm.



The fixture's photometric values can be found on the following pages

Technical Data

Concept

Powerful recessed linear RGBW LED projector.

Source

Linear Mid Power Quad-chip RGBW LED board. Color temperature of the white source: 3000K.	
Energy efficiency class	G
Nominal power	36W
Nominal flux	See photometries
Colour rendering index	
CCT nominal	See photometries
Lifetime (L80/B10)	100000h tq +25°C
Lifetime (L90/B10)	72000h tq +25°C

TARGETTI

CCIAA Firenze
Share Capital: € 500.000,00
VAT N. (IT): 01537660480
R.E.A: FI-275656

Targetti Sankey S.r.l.
Via Giuseppe Garibaldi, 82
50041 Calenzano (FI)
Italy

Tel: +39 055 37911
targetti.com
targetti@targetti.com

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.
Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.

Technical Data

Illuminotechnical characteristics

Internal optical system composed of a primary cylindrical glass lens, a high reflectance anodised aluminium reflector and an integrated holographic filter. Flood version.

Optic	FL
Beam angles	FL
Optical efficiency	70.26%
Fixture flux	See photometries
Luminous efficacy	See photometries
Photobiological safety	Compliant with RG1 low risk group

Mechanical characteristics

Extruded anodised aluminium 15µ body. Extra clear 5mm thick glass flat screen.

Colour and finish	Aluminium
Dimensions	AxBxH 905x53x43mm
Weight	2.6Kg
Version	Remote driver
Degree of protection	IP66,IP67,IP68,IP69
Mechanical Resistance	IK08

Electrical characteristics

Remote driver version. Controlled using DMX-RDM protocols that allow to programme the fixture remotely (no dip-switch) using the DMX data line. Precabled with 1m 8x0.5mm² cable (Ø 8.5mm). Programming the fixtures is done using the USB-RDM programmer that is available as an accessory.

Fixture Power	See photometries
Power supply	500mA
Insulation Class	CLASS 3
Driver included	NO
Ambient temperature	-25°C / +35°C

Installation

To be completed with an anodised aluminium outer casing suitable for in-line installation and external looping.

Notes

LMS Casambi wireless control available on request. Photometrics show the maximum emission values of fixtures. Uses the "Waterblock Smart" technical solution that involves resin coating the connection cables, limiting the risk of humidity reaching the driver or the fixture. Values related to the power consumption of the fixture do not take into account the consumption of the accessory driver, which depends on the choice of driver. IP68: the projector is not suitable for permanent underwater installation but can withstand temporary accidental immersion to a depth of 2 metres (max.24h). IP69: IEC/EN 60529 standard compliant. Commissioning of the control system via free APP; the intervention of a specialist technician can be quoted on request.

Regulations and Certifications

CE

Warranty

5 years.

Technical Data

Warning

Luminaire designed for disposal/recycling at end-of-life. Replaceable (LED only) light source by a professional.

TARGETTI

CCIAA Firenze
Share Capital: € 500.000,00
VAT N. (IT): 01537660480
R.E.A: FI-275656

Targetti Sankey S.r.l.
Via Giuseppe Garibaldi, 82
50041 Calenzano (FI)
Italy

Tel: +39 055 37911
targetti.com
targetti@targetti.com


Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.
Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.

Photometries

RGBW


Fixture Power	36W
Nominal flux	2691lm
Fixture flux	1891lm
Luminous efficacy	53lm/W



-		H(m)	D1(m)	D2(m)	Emax(lx)
-			83°	33°	
Fixture Power	36W	1	1.76	0.59	1814
Source Flux	2691lm	2	3.51	1.17	454
Fixture Flux	1891lm	3	5.27	1.76	202
Efficacy	53lm/W	4	7.03	2.34	113
TS1740 Imax=674cd/klm	Imax 1814cd	5	8.78	2.93	73

RGB


Fixture Power	26W
Nominal flux	1533lm
Fixture flux	1077lm
Luminous efficacy	41lm/W



-		H(m)	D1(m)	D2(m)	Emax(lx)
-			83°	33°	
Fixture Power	26W	1	1.76	0.59	1034
Source Flux	1533lm	2	3.51	1.17	258
Fixture Flux	1077lm	3	5.27	1.76	115
Efficacy	41lm/W	4	7.03	2.34	65
TS1740 Imax=674cd/klm	Imax 1034cd	5	8.78	2.93	41

WHITE


CCT nominal	3000K
Fixture Power	9.5W
Nominal flux	1312lm
Fixture flux	922lm
Luminous efficacy	97lm/W



3000K		H(m)	D1(m)	D2(m)	Emax(lx)
-			83°	33°	
Fixture Power	10W	1	1.76	0.59	885
Source Flux	1312lm	2	3.51	1.17	221
Fixture Flux	922lm	3	5.27	1.76	98
Efficacy	97lm/W	4	7.03	2.34	55
TS1740 Imax=674cd/klm	Imax 885cd	5	8.78	2.93	35

RED


Fixture Power	6.9W
Nominal flux	472lm
Fixture flux	332lm
Luminous efficacy	48lm/W



-		H(m)	D1(m)	D2(m)	Emax(lx)
-			83°	33°	
Fixture Power	7W	1	1.76	0.59	318
Source Flux	472lm	2	3.51	1.17	80
Fixture Flux	332lm	3	5.27	1.76	35
Efficacy	48lm/W	4	7.03	2.34	20
TS1740 Imax=674cd/klm	Imax 318cd	5	8.78	2.93	13

GREEN


Fixture Power	9.8W
Nominal flux	965lm
Fixture flux	678lm
Luminous efficacy	69lm/W



-		H(m)	D1(m)	D2(m)	Emax(lx)
-			83°	33°	
Fixture Power	10W	1	1.76	0.59	651
Source Flux	965lm	2	3.51	1.17	163
Fixture Flux	678lm	3	5.27	1.76	72
Efficacy	69lm/W	4	7.03	2.34	41
TS1740 Imax=674cd/klm	Imax 651cd	5	8.78	2.93	26

BLUE

Fixture Power	9.5W
Nominal flux	190lm
Fixture flux	133lm
Luminous efficacy	14lm/W



-		H(m)	D1(m)	D2(m)	Emax(lx)
-			83°	33°	
Fixture Power	10W	1	1.76	0.59	128
Source Flux	190lm	2	3.51	1.17	32
Fixture Flux	133lm	3	5.27	1.76	14
Efficacy	14lm/W	4	7.03	2.34	8
TS1740 Imax=674cd/klm	Imax 128cd	5	8.78	2.93	5

TARGETTI

CCIAA Firenze
Share Capital: € 500.000,00
VAT N. (IT): 01537660480
R.E.A: FI-275656

Targetti Sankey S.r.l.
Via Giuseppe Garibaldi, 82
50041 Calenzano (FI)
Italy


Tel: +39 055 37911
targetti.com
targetti@targetti.com

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.
Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.

Related codes


Power Supply



CODE
1E4271

DMX RDM 4 channel RGBW driver - 500mA.
50W, LxHxP=250x82x140mm, 120-277Vac.
IP68 gray powder coated aluminum box.

Insertion Box



CODE	P	H	L
1E3731	94mm	58mm	909mm

Aluminium outer casing for Jedi Compact with remote driver.

Accessories

Connector



CODE
1E4362

Linear connection box IP66/IP68.
8 poles.

Tool



CODE
1E3305

Tightening wrench for the connector kit.

Control systems



CODE
1E2767

USB-RDM Programmer code.
DMX-RDM (Remote Device Management) address planner.
Used with the "RDM Targetti" software that can be downloaded for free from the Targetti website download section.
To be used with all RGBW products.
The USB-RDM programmer manages to direct DMX-RDM fixtures if there are no BUFFER or Splitter DMXs on the section.
Please refer to the instructions for more details.

TARGETTI

CCIAA Firenze
Share Capital: € 500.000,00
VAT N. (IT): 01537660480
R.E.A: FI-275656

Targetti Sankey S.r.l.
Via Giuseppe Garibaldi, 82
50041 Calenzano (FI)
Italy

Tel: +39 055 37911
targetti.com
targetti@targetti.com

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.
Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.



CODE

A077

my-SCENARIO Show Store.
Programmable DMX interface that integrates the latest innovations in lighting control in architectural and entertainment applications.
It features USB Type-C and Ethernet ports for programming and remote control.
The unit can be fully programmed with ESA Pro 2 software (available for Windows and Mac users) or via mobile applications such as Arcolis (available for iOS or Android devices).
It can be fully customised: pixel mapping, triggering management, patch configuration and much more.
The system offers great possibilities for the control of your lighting installation: multi zone control (allowing the management of up to 5 indipendent zones), extended triggers (time/date, Sunrise/Sunset, input ports, TCP/UDP commands), 16-bit channels management, full recovery after power loss, up to 99 total scenes, and 1024+ DMX channels.
The intuitive backlit keyboard comes with 10 preset buttons for a user friendly experience.



CODE

1T6499

myScenario Wall.
DMX controller with a glass touch sensitive screen for architectural applications.
It can control two different DMX universes (2x 512 channels).
Stand alone function or connected to a computer using a USB port.
Software for creating scenarios (that can be downloaded from the Targetti website) included.
It can manage 10 different lighting zones and 50 scenarios per zone.
The touch keys on the front make it possible to modify and recall programmed scenarios.
USB cable included.
To be used with all RGBW products.

TARGETTI

CCIAA Firenze
Share Capital: € 500.000,00
VAT N. (IT): 01537660480
R.E.A: FI-275656

Targetti Sankey S.r.l.
Via Giuseppe Garibaldi, 82
50041 Calenzano (FI)
Italy

Tel: +39 055 37911
targetti.com
targetti@targetti.com

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.
Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.