


LIGHTING SYSTEMS

Oz Lighting module - Single adjustable - 50x50mm

Code

1T7414DD

LIGHT COLOUR	LIGHT DISTRIBUTION	OUTPUT
4000K 90	FL 27°	7.1W 793lm
POWER SUPPLY CONTROL	COLOUR	
48Vdc	○	



The figures on the drawing are expressed in mm.



	4000K	H(m)	D(m)	E _{max} (lx)
Ra90			27°	
Fixture Power	7W	1	0.49	2597
Source Flux	1060lm	2	0.98	649
Fixture Flux	793lm	3	1.47	289
Efficacy	112lm/W	4	1.95	162
TS1126	I _{max} =2450cd/klm	I _{max}	2597cd	5
			2.44	104

Technical Data

Concept

Adjustable magnetic LED light module, powered at low voltage.

Source

High efficiency Chip on Board LED Ra90.

Energy efficiency class	E
Nominal power	6,5W
Nominal flux	1060lm
Colour rendering index	90
R _f	90
R _g	98
CCT nominal	4000K
SDCM	2
Lifetime (L80/B10)	72000h tq +25°C
Lifetime (L90/B10)	72000h tq +25°C

TARGETTI

CCIAA Firenze
Share Capital: € 500.000,00
VAT N. (IT): 01537660480
R.E.A: FI-275656

Targetti Sankey S.r.l.
Via Giuseppe Garibaldi, 82
50041 Calenzano (FI)
Italy

Tel: +39 055 37911
targetti.com
targetti@targetti.com

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.
Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.

Technical Data

Illuminotechnical characteristics

The flood optical system consists of a metallised polycarbonate precision optic, a holographic diffuser filter and a black polycarbonate frame. The light is suitable for installation in work environments UGR<19 (EN12464-1).

Optic	FL
Beam angles	FL
Optical efficiency	74.8%
Fixture flux	793lm
Luminous efficacy	112lm/W
Photobiological safety	Compliant with RG1 low risk group

Mechanical characteristics

White painted die-cast aluminium body. Adjustable fixture, 50x50mm. Tiltability of the optical unit from 0° to +90° on the vertical plane and of 358° on the horizontal plane.

Colour and finish	Plaster white
Dimensions	AxBxH 50x50x104mm
Weight	0.2Kg
Version	Adjustable - Digital Dimming
Degree of protection	IP20

Electrical characteristics

Fixture Power	7.1W
Power supply	48Vdc
Insulation Class	CLASS 3
Ambient temperature	0°C / +25°C

Installation

Extremely rapid, versatile and simple mechanical and electrical coupling system using magnets which support the fixture on the Power Track and feed power inside the fixture on all versions.

Notes

Digital Dimming version. 110-277Vac version available on request.

Warranty

5 years.

Warning

Luminaire designed for disposal/recycling at end-of-life. Replaceable (LED only) light source by a professional. Replaceable control gear by a professional.

TARGETTI

CCIAA Firenze
Share Capital: € 500.000,00
VAT N. (IT): 01537660480
R.E.A: FI-275656

Targetti Sankey S.r.l.
Via Giuseppe Garibaldi, 82
50041 Calenzano (FI)
Italy

Tel: +39 055 37911
targetti.com
targetti@targetti.com

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.
Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.