

PROYECTORES

Jedi Nova 55
Proyector Comfort
900

Código
E0533GRH840D2BC

TEMPERATURA DE COLOR	DISTRIBUCIÓN LUMINOSA	OUTPUT
4000K 80	Grazing 17° / 74°	34,3W 3441lm
ALIMENTACIÓN CONTROL	COLOR	
220-240Vac DALI2		



Los datos mostrados en el dibujo están expresados en mm.



The diagram shows a light beam with a beam spread of 17°. The beam diameter at 1m is 0.30m, and at 2m it is 0.61m. The beam diameter at 3m is 0.91m, and at 4m it is 1.21m. The beam diameter at 5m is 1.52m. The beam diameter at 6m is 1.83m. The beam diameter at 7m is 2.14m. The beam diameter at 8m is 2.45m. The beam diameter at 9m is 2.76m. The beam diameter at 10m is 3.07m. The beam diameter at 11m is 3.38m. The beam diameter at 12m is 3.69m. The beam diameter at 13m is 4.00m. The beam diameter at 14m is 4.31m. The beam diameter at 15m is 4.62m. The beam diameter at 16m is 4.93m. The beam diameter at 17m is 5.24m. The beam diameter at 18m is 5.55m. The beam diameter at 19m is 5.86m. The beam diameter at 20m is 6.17m. The beam diameter at 21m is 6.48m. The beam diameter at 22m is 6.79m. The beam diameter at 23m is 7.10m. The beam diameter at 24m is 7.41m. The beam diameter at 25m is 7.72m. The beam diameter at 26m is 8.03m. The beam diameter at 27m is 8.34m. The beam diameter at 28m is 8.65m. The beam diameter at 29m is 8.96m. The beam diameter at 30m is 9.27m. The beam diameter at 31m is 9.58m. The beam diameter at 32m is 9.89m. The beam diameter at 33m is 10.20m. The beam diameter at 34m is 10.51m. The beam diameter at 35m is 10.82m. The beam diameter at 36m is 11.13m. The beam diameter at 37m is 11.44m. The beam diameter at 38m is 11.75m. The beam diameter at 39m is 12.06m. The beam diameter at 40m is 12.37m. The beam diameter at 41m is 12.68m. The beam diameter at 42m is 12.99m. The beam diameter at 43m is 13.30m. The beam diameter at 44m is 13.61m. The beam diameter at 45m is 13.92m. The beam diameter at 46m is 14.23m. The beam diameter at 47m is 14.54m. The beam diameter at 48m is 14.85m. The beam diameter at 49m is 15.16m. The beam diameter at 50m is 15.47m. The beam diameter at 51m is 15.78m. The beam diameter at 52m is 16.09m. The beam diameter at 53m is 16.40m. The beam diameter at 54m is 16.71m. The beam diameter at 55m is 17.02m. The beam diameter at 56m is 17.33m. The beam diameter at 57m is 17.64m. The beam diameter at 58m is 17.95m. The beam diameter at 59m is 18.26m. The beam diameter at 60m is 18.57m. The beam diameter at 61m is 18.88m. The beam diameter at 62m is 19.19m. The beam diameter at 63m is 19.50m. The beam diameter at 64m is 19.81m. The beam diameter at 65m is 20.12m. The beam diameter at 66m is 20.43m. The beam diameter at 67m is 20.74m. The beam diameter at 68m is 21.05m. The beam diameter at 69m is 21.36m. The beam diameter at 70m is 21.67m. The beam diameter at 71m is 21.98m. The beam diameter at 72m is 22.29m. The beam diameter at 73m is 22.60m. The beam diameter at 74m is 22.91m. The beam diameter at 75m is 23.22m. The beam diameter at 76m is 23.53m. The beam diameter at 77m is 23.84m. The beam diameter at 78m is 24.15m. The beam diameter at 79m is 24.46m. The beam diameter at 80m is 24.77m. The beam diameter at 81m is 25.08m. The beam diameter at 82m is 25.39m. The beam diameter at 83m is 25.70m. The beam diameter at 84m is 26.01m. The beam diameter at 85m is 26.32m. The beam diameter at 86m is 26.63m. The beam diameter at 87m is 26.94m. The beam diameter at 88m is 27.25m. The beam diameter at 89m is 27.56m. The beam diameter at 90m is 27.87m. The beam diameter at 91m is 28.18m. The beam diameter at 92m is 28.49m. The beam diameter at 93m is 28.80m. The beam diameter at 94m is 29.11m. The beam diameter at 95m is 29.42m. The beam diameter at 96m is 29.73m. The beam diameter at 97m is 30.04m. The beam diameter at 98m is 30.35m. The beam diameter at 99m is 30.66m. The beam diameter at 100m is 30.97m. The beam diameter at 101m is 31.28m. The beam diameter at 102m is 31.59m. The beam diameter at 103m is 31.90m. The beam diameter at 104m is 32.21m. The beam diameter at 105m is 32.52m. The beam diameter at 106m is 32.83m. The beam diameter at 107m is 33.14m. The beam diameter at 108m is 33.45m. The beam diameter at 109m is 33.76m. The beam diameter at 110m is 34.07m. The beam diameter at 111m is 34.38m. The beam diameter at 112m is 34.69m. The beam diameter at 113m is 35.00m. The beam diameter at 114m is 35.31m. The beam diameter at 115m is 35.62m. The beam diameter at 116m is 35.93m. The beam diameter at 117m is 36.24m. The beam diameter at 118m is 36.55m. The beam diameter at 119m is 36.86m. The beam diameter at 120m is 37.17m. The beam diameter at 121m is 37.48m. The beam diameter at 122m is 37.79m. The beam diameter at 123m is 38.10m. The beam diameter at 124m is 38.41m. The beam diameter at 125m is 38.72m. The beam diameter at 126m is 39.03m. The beam diameter at 127m is 39.34m. The beam diameter at 128m is 39.65m. The beam diameter at 129m is 39.96m. The beam diameter at 130m is 40.27m. The beam diameter at 131m is 40.58m. The beam diameter at 132m is 40.89m. The beam diameter at 133m is 41.20m. The beam diameter at 134m is 41.51m. The beam diameter at 135m is 41.82m. The beam diameter at 136m is 42.13m. The beam diameter at 137m is 42.44m. The beam diameter at 138m is 42.75m. The beam diameter at 139m is 43.06m. The beam diameter at 140m is 43.37m. The beam diameter at 141m is 43.68m. The beam diameter at 142m is 43.99m. The beam diameter at 143m is 44.30m. The beam diameter at 144m is 44.61m. The beam diameter at 145m is 44.92m. The beam diameter at 146m is 45.23m. The beam diameter at 147m is 45.54m. The beam diameter at 148m is 45.85m. The beam diameter at 149m is 46.16m. The beam diameter at 150m is 46.47m. The beam diameter at 151m is 46.78m. The beam diameter at 152m is 47.09m. The beam diameter at 153m is 47.40m. The beam diameter at 154m is 47.71m. The beam diameter at 155m is 48.02m. The beam diameter at 156m is 48.33m. The beam diameter at 157m is 48.64m. The beam diameter at 158m is 48.95m. The beam diameter at 159m is 49.26m. The beam diameter at 160m is 49.57m. The beam diameter at 161m is 49.88m. The beam diameter at 162m is 50.19m. The beam diameter at 163m is 50.50m. The beam diameter at 164m is 50.81m. The beam diameter at 165m is 51.12m. The beam diameter at 166m is 51.43m. The beam diameter at 167m is 51.74m. The beam diameter at 168m is 52.05m. The beam diameter at 169m is 52.36m. The beam diameter at 170m is 52.67m. The beam diameter at 171m is 52.98m. The beam diameter at 172m is 53.29m. The beam diameter at 173m is 53.60m. The beam diameter at 174m is 53.91m. The beam diameter at 175m is 54.22m. The beam diameter at 176m is 54.53m. The beam diameter at 177m is 54.84m. The beam diameter at 178m is 55.15m. The beam diameter at 179m is 55.46m. The beam diameter at 180m is 55.77m. The beam diameter at 181m is 56.08m. The beam diameter at 182m is 56.39m. The beam diameter at 183m is 56.70m. The beam diameter at 184m is 57.01m. The beam diameter at 185m is 57.32m. The beam diameter at 186m is 57.63m. The beam diameter at 187m is 57.94m. The beam diameter at 188m is 58.25m. The beam diameter at 189m is 58.56m. The beam diameter at 190m is 58.87m. The beam diameter at 191m is 59.18m. The beam diameter at 192m is 59.49m. The beam diameter at 193m is 59.80m. The beam diameter at 194m is 60.11m. The beam diameter at 195m is 60.42m. The beam diameter at 196m is 60.73m. The beam diameter at 197m is 61.04m. The beam diameter at 198m is 61.35m. The beam diameter at 199m is 61.66m. The beam diameter at 200m is 61.97m. The beam diameter at 201m is 62.28m. The beam diameter at 202m is 62.59m. The beam diameter at 203m is 62.90m. The beam diameter at 204m is 63.21m. The beam diameter at 205m is 63.52m. The beam diameter at 206m is 63.83m. The beam diameter at 207m is 64.14m. The beam diameter at 208m is 64.45m. The beam diameter at 209m is 64.76m. The beam diameter at 210m is 65.07m. The beam diameter at 211m is 65.38m. The beam diameter at 212m is 65.69m. The beam diameter at 213m is 66.00m. The beam diameter at 214m is 66.31m. The beam diameter at 215m is 66.62m. The beam diameter at 216m is 66.93m. The beam diameter at 217m is 67.24m. The beam diameter at 218m is 67.55m. The beam diameter at 219m is 67.86m. The beam diameter at 220m is 68.17m. The beam diameter at 221m is 68.48m. The beam diameter at 222m is 68.79m. The beam diameter at 223m is 69.10m. The beam diameter at 224m is 69.41m. The beam diameter at 225m is 69.72m. The beam diameter at 226m is 70.03m. The beam diameter at 227m is 70.34m. The beam diameter at 228m is 70.65m. The beam diameter at 229m is 70.96m. The beam diameter at 230m is 71.27m. The beam diameter at 231m is 71.58m. The beam diameter at 232m is 71.89m. The beam diameter at 233m is 72.20m. The beam diameter at 234m is 72.51m. The beam diameter at 235m is 72.82m. The beam diameter at 236m is 73.13m. The beam diameter at 237m is 73.44m. The beam diameter at 238m is 73.75m. The beam diameter at 239m is 74.06m. The beam diameter at 240m is 74.37m. The beam diameter at 241m is 74.68m. The beam diameter at 242m is 74.99m. The beam diameter at 243m is 75.30m. The beam diameter at 244m is 75.61m. The beam diameter at 245m is 75.92m. The beam diameter at 246m is 76.23m. The beam diameter at 247m is 76.54m. The beam diameter at 248m is 76.85m. The beam diameter at 249m is 77.16m. The beam diameter at 250m is 77.47m. The beam diameter at 251m is 77.78m. The beam diameter at 252m is 78.09m. The beam diameter at 253m is 78.40m. The beam diameter at 254m is 78.71m. The beam diameter at 255m is 79.02m. The beam diameter at 256m is 79.33m. The beam diameter at 257m is 79.64m. The beam diameter at 258m is 79.95m. The beam diameter at 259m is 80.26m. The beam diameter at 260m is 80.57m. The beam diameter at 261m is 80.88m. The beam diameter at 262m is 81.19m. The beam diameter at 263m is 81.50m. The beam diameter at 264m is 81.81m. The beam diameter at 265m is 82.12m. The beam diameter at 266m is 82.43m. The beam diameter at 267m is 82.74m. The beam diameter at 268m is 83.05m. The beam diameter at 269m is 83.36m. The beam diameter at 270m is 83.67m. The beam diameter at 271m is 83.98m. The beam diameter at 272m is 84.29m. The beam diameter at 273m is 84.60m. The beam diameter at 274m is 84.91m. The beam diameter at 275m is 85.22m. The beam diameter at 276m is 85.53m. The beam diameter at 277m is 85.84m. The beam diameter at 278m is 86.15m. The beam diameter at 279m is 86.46m. The beam diameter at 280m is 86.77m. The beam diameter at 281m is 87.08m. The beam diameter at 282m is 87.39m. The beam diameter at 283m is 87.70m. The beam diameter at 284m is 88.01m. The beam diameter at 285m is 88.32m. The beam diameter at 286m is 88.63m. The beam diameter at 287m is 88.94m. The beam diameter at 288m is 89.25m. The beam diameter at 289m is 89.56m. The beam diameter at 290m is 89.87m. The beam diameter at 291m is 90.18m. The beam diameter at 292m is 90.49m. The beam diameter at 293m is 90.80m. The beam diameter at 294m is 91.11m. The beam diameter at 295m is 91.42m. The beam diameter at 296m is 91.73m. The beam diameter at 297m is 92.04m. The beam diameter at 298m is 92.35m. The beam diameter at 299m is 92.66m. The beam diameter at 300m is 92.97m. The beam diameter at 301m is 93.28m. The beam diameter at 302m is 93.59m. The beam diameter at 303m is 93.90m. The beam diameter at 304m is 94.21m. The beam diameter at 305m is 94.52m. The beam diameter at 306m is 94.83m. The beam diameter at 307m is 95.14m. The beam diameter at 308m is 95.45m. The beam diameter at 309m is 95.76m. The beam diameter at 310m is 96.07m. The beam diameter at 311m is 96.38m. The beam diameter at 312m is 96.69m. The beam diameter at 313m is 97.00m. The beam diameter at 314m is 97.31m. The beam diameter at 315m is 97.62m. The beam diameter at 316m is 97.93m. The beam diameter at 317m is 98.24m. The beam diameter at 318m is 98.55m. The beam diameter at 319m is 98.86m. The beam diameter at 320m is 99.17m. The beam diameter at 321m is 99.48m. The beam diameter at 322m is 99.79m. The beam diameter at 323m is 100.10m. The beam diameter at 324m is 100.41m. The beam diameter at 325m is 100.72m. The beam diameter at 326m is 101.03m. The beam diameter at 327m is 101.34m. The beam diameter at 328m is 101.65m. The beam diameter at 329m is 101.96m. The beam diameter at 330m is 102.27m. The beam diameter at 331m is 102.58m. The beam diameter at 332m is 102.89m. The beam diameter at 333m is 103.20m. The beam diameter at 334m is 103.51m. The beam diameter at 335m is 103.82m. The beam diameter at 336m is 104.13m. The beam diameter at 337m is 104.44m. The beam diameter at 338m is 104.75m. The beam diameter at 339m is 105.06m. The beam diameter at 340m is 105.37m. The beam diameter at 341m is 105.68m. The beam diameter at 342m is 105.99m. The beam diameter at 343m is 106.30m. The beam diameter at 344m is 106.61m. The beam diameter at 345m is 106.92m. The beam diameter at 346m is 107.23m. The beam diameter at 347m is 107.54m. The beam diameter at 348m is 107.85m. The beam diameter at 349m is 108.16m. The beam diameter at 350m is 108.47m. The beam diameter at 351m is 108.78m. The beam diameter at 352m is 109.09m. The beam diameter at 353m is 109.40m. The beam diameter at 354m is 109.71m. The beam diameter at 355m is 110.02m. The beam diameter at 356m is 110.33m. The beam diameter at 357m is 110.64m. The beam diameter at 358m is 110.95m. The beam diameter at 359m is 111.26m. The beam diameter at 360m is 111.57m. The beam diameter at 361m is 111.88m. The beam diameter at 362m is 112.19m. The beam diameter at 363m is 112.50m. The beam diameter at 364m is 112.81m. The beam diameter at 365m is 113.12m. The beam diameter at 366m is 113.43m. The beam diameter at 367m is 113.74m. The beam diameter at 368m is 114.05m. The beam diameter at 369m is 114.36m. The beam diameter at 370m is 114.67m. The beam diameter at 371m is 114.98m. The beam diameter at 372m is 115.29m. The beam diameter at 373m is 115.60m. The beam diameter at 374m is 115.91m. The beam diameter at 375m is 116.22m. The beam diameter at 376m is 116.53m. The beam diameter at 377m is 116.84m. The beam diameter at 378m is 117.15m. The beam diameter at 379m is 117.46m. The beam diameter at 380m is 117.77m. The beam diameter at 381m is 118.08m. The beam diameter at 382m is 118.39m. The beam diameter at 383m is 118.70m. The beam diameter at 384m is 119.01m. The beam diameter at 385m is 119.32m. The beam diameter at 386m is 119.63m. The beam diameter at 387m is 119.94m. The beam diameter at 388m is 120.25m. The beam diameter at 389m is 120.56m. The beam diameter at 390m is 120.87m. The beam diameter at 391m is 121.18m. The beam diameter at 392m is 121.49m. The beam diameter at 393m is 121.80m. The beam diameter at 394m is 122.11m. The beam diameter at 395m is 122.42m. The beam diameter at 396m is 122.73m. The beam diameter at 397m is 123.04m. The beam diameter at 398m is 123.35m. The beam diameter at 399m is 123.66m. The beam diameter at 400m is 123.97m. The beam diameter at 401m is 124.28m. The beam diameter at 402m is 124.59m. The beam diameter at 403m is 124.90m. The beam diameter at 404m is 125.21m. The beam diameter at 405m is 125.52m. The beam diameter at 406m is 125.83m. The beam diameter at 407m is 126.14m. The beam diameter at 408m is 126.45m. The beam diameter at 409m is 126.76m. The beam diameter at 410m is 127.07m. The beam diameter at 411m is 127.38m. The beam diameter at 412m is 127.69m. The beam diameter at 413m is 128.00m. The beam diameter at 414m is 128.31m. The beam diameter at 415m is 128.62m. The beam diameter at 416m is 128.93m. The beam diameter at 417m is 129.24m. The beam diameter at 418m is 129.55m. The beam diameter at 419m is 129.86m. The beam diameter at 420m is 130.17m. The beam diameter at 421m is 130.48m. The beam diameter at 422m is 130.79m. The beam diameter at 423m is 131.10m. The beam diameter at 424m is 131.41m. The beam diameter at 425m is 131.72m. The beam diameter at 426m is 132.03m. The beam diameter at 427m is 132.34m. The beam diameter at 428m is 132.65m. The beam diameter at 429m is 132.96m. The beam diameter at 430m is 133.27m. The beam diameter at 431m is 133.58m. The beam diameter at 432m is 133.89m. The beam diameter at 433m is 134.20m. The beam diameter at 434m is 134.51m. The beam diameter at 435m is 134.82m. The beam diameter at 436m is 135.13m. The beam diameter at 437m is 135.44m. The beam diameter at 438m is 135.75m. The beam diameter at 439m is 136.06m. The beam diameter at 440m is 136.37m. The beam diameter at 441m is 136.68m. The beam diameter at 442m is 136.99m. The beam diameter at 443m is 137.30m. The beam diameter at 444m is 137.61m. The beam diameter at 445m is 137.92m. The beam diameter at 446m is 138.23m. The beam diameter at 447m is 138.54m. The beam diameter at 448m is 138.85m. The beam diameter at 449m is 139.16m. The beam diameter at 450m is 139.47m. The beam diameter at 451m is 139.78m. The beam diameter at 452m is 140.09m. The beam diameter at 453m is 140.40m. The beam diameter at 454m is 140.71m. The beam diameter at 455m is 141.02m. The beam diameter at 456m is 141.33m. The beam diameter at 457m is 141.64m. The beam diameter at 458m is 141.95m. The beam diameter at 459m is 142.26m. The beam diameter at 460m is 142.57m. The beam diameter at 461m is 142.88m. The beam diameter at 462m is 143.19m. The beam diameter at 463m is 143.50m. The beam diameter at 464m is 143.81m. The beam diameter at 465m is 144.12m. The beam diameter at 466m is 144.43m. The beam diameter at 467m is 144.74m. The beam diameter at 468m is 145.05m. The beam diameter at 469m is 145.36m. The beam diameter at 470m is 145.67m. The beam diameter at 471m is 145.98m. The beam diameter at 472m is 146.29m. The beam diameter at 473m is 146.60m. The beam diameter at 474m is 146.91m. The beam diameter at 475m is 147.22m. The beam diameter at 476m is 147.53m. The beam diameter at 477m is 147.84m. The beam diameter at 478m is 148.15m. The beam diameter at 479m is 148.46m. The beam diameter at 480m is 148.77m. The beam diameter at 481m is 149.08m. The beam diameter at 482m is 149.39m. The beam diameter at 483m is 149.70m. The beam diameter at 484m is 150.01m. The beam diameter at 485m is 150.32m. The beam diameter at 486m is 150.63m. The beam diameter at 487m is 150.94m. The beam diameter at 488m is 151.25m. The beam diameter at 489m is 151.56m. The beam diameter at 490m is 151.87m. The beam diameter at 491m is 152.18m. The beam diameter at 492m is 152.49m. The beam diameter at 493m is 152.80m. The beam diameter at 494m is 153.11m. The beam diameter at 495m is 153.42m. The beam diameter at 496m is 153.73m. The beam diameter at 497m is 154.04m. The beam diameter at 498m is 154.35m. The beam diameter at 499m is 154.66m. The beam diameter at 500m is 154.97m. The beam diameter at 501m is 155.28m. The beam diameter at 502m is 155.59m. The beam diameter at 503m is 155.90m. The beam diameter at 504m is 156.21m. The beam diameter at 505m is 156.52m. The beam diameter at 506m is 156.83m. The beam diameter at 507m is 157.14m. The beam diameter at 508m is 157.45m. The beam diameter at 509m is 157.76m. The beam diameter at 510m is 158.07m. The beam diameter at 511m is 158.38m. The beam diameter at 512m is 158.69m. The beam diameter at 513m is 159.00m. The beam diameter at 514m is 159.31m. The beam diameter at 515m is 159.62m. The beam diameter at 516m is 159.93m. The beam diameter at 517m is 160.24m. The beam diameter at 518m is 160.55m. The beam diameter at 519m is 160.86m. The beam diameter at 520m is 161.17m. The beam diameter at 521m is 161.48m. The beam diameter at 522m is 161.79m. The beam diameter at 523m is 162.10m. The beam diameter at 524m is 162.41m. The beam diameter at 525m is 162.72m. The beam diameter at 526m is 163.03m. The beam diameter at 527m is 163.34m. The beam diameter at 528m is 163.65m. The beam diameter at 529m is 163.96m. The beam diameter at 530m is 164.27m. The beam diameter at 531m is 164.58m. The beam diameter at 532m is 164.89m. The beam diameter at 533m is 165.20m. The beam diameter at 534m is 165.51m. The beam diameter at 535m is 165.82m. The beam diameter at 536m is 166.13m. The beam diameter at 537m is 166.44m. The beam diameter at 538m is 166.75m. The beam diameter at 539m is 167.06m. The beam diameter at 540m is 167.37m. The beam diameter at 541m is 167.68m. The beam diameter at 542m is 167.99m. The beam diameter at 543m is 168.30m. The beam diameter at 544m is 168.61m. The beam diameter at 545m is 168.92m. The beam diameter at 546m is 169.23m. The beam diameter at 547m is 169.54m. The beam diameter at 548m is 169.85m. The beam diameter at 549m is 170.16m. The beam diameter at 550m is 170.47m. The beam diameter at 551m is 170.78m. The beam diameter at 552m is 171.09m. The beam diameter at 553m is 171.40m. The beam diameter at 554m is 171.71m. The beam diameter at 555m is 172.02m. The beam diameter at 556m is 172.33m. The beam diameter at 557m is 172.64m. The beam diameter at 558m is 172.95m. The beam diameter at 559m is 173.26m. The beam diameter at 560m is 173.57m. The beam diameter at 561m is 173.88m. The beam diameter at 562m is 174.19m. The beam diameter at 563m is 174.50m. The beam diameter at 564m is 174.81m. The beam diameter at 565m is 175.12m. The beam diameter at 566m is 175.43m. The beam diameter at 567m is 175.74m. The beam diameter at 568m is 176.05m. The beam diameter at 569m is 176.36m. The beam diameter at 570m is 176.67m. The beam diameter at 571m is 176.98m. The beam diameter at 572m is 177.29m. The beam diameter at 573m is 177.60m. The beam diameter at 574m is 177.91m. The beam diameter at 575m is 178.22m. The beam diameter at 576m is 178.53m. The beam diameter at 577m is 178.84m. The beam diameter at 578m is 179.15m. The beam diameter at 579m is 179.46m. The beam diameter at 580m is 179.77m. The beam diameter at 581m is 180.08m. The beam diameter at 582m is 180.39m. The beam diameter at 583m is 180.70m. The beam diameter at 584m is 181.01m. The beam diameter at 585m is 181.32m. The beam diameter at 586m is 181.63m. The beam diameter at 587m is 181.94m. The beam diameter at 588m is 182.25m. The beam diameter at 589m is 182.56m. The beam diameter at 590m is 182.87m. The beam diameter at 591m is 183.18m. The beam diameter at 592m is 183.49m. The beam diameter at 593m is 183.80m. The beam diameter at 594m is 184.11m. The beam diameter at 595m is 184.42m. The beam diameter at 596m is 184.73m. The beam diameter at 597m is 185.04m. The beam diameter at 598m is 185.35m. The beam diameter at 599m is 185.66m. The beam diameter at 600m is 185.97m. The beam diameter at 601m is 186.28m. The beam diameter at 602m is 186.59m. The beam diameter at 603m is 186.90m. The beam diameter at 604m is 187.21m. The beam diameter at 605m is 187.52m. The beam diameter at 606m is 187.83m. The beam diameter at 607m is 188.14m. The beam diameter at 608m is 188.45m. The beam diameter at 609m is 188.76m. The beam diameter at 610m is 189.07m. The beam diameter at 611m is 189.38m. The beam diameter at 612m is 189.69m. The beam diameter at 613m is 190.00m. The beam diameter at 614m is 190.31m. The beam diameter at 615m is 190.62m. The beam diameter at 616m is 190.93m. The beam diameter at 617m is 191.24m. The beam diameter at 618m is 191.55m. The beam diameter at 619m is 191.86m. The beam diameter at 620m is 192.17m. The beam diameter at 621m is 192.48m. The beam diameter at 622m is 192.79m. The beam diameter at 623m is 193.10m. The beam diameter at 624m is 193.41m. The beam diameter at 625m is 193.72m. The beam diameter at 626m is 194.03m. The beam diameter at 627m is 194.34m. The beam diameter at 628m is 194.65m. The beam diameter at 629m is 194.96m. The beam diameter at 630m is 195.27m. The beam diameter at 631m is 195.58m. The beam diameter at 632m is 195.89m. The beam diameter at 633m is 196.20m. The beam diameter at 634m is 196.51m. The beam diameter at 635m is 196.82m. The beam diameter at 636m is 197.13m. The beam diameter at 637m is 197.44m. The beam diameter at 638m is 197.75m. The beam diameter at 639m is 198.06m. The beam diameter at 640m is 198.37m. The beam diameter at 641m is 198.68m. The beam diameter at 642m is 198.99m. The beam diameter at 643m is 199.30m. The beam diameter at 644m is 199.61m. The beam diameter at 645m is 199.92m. The beam diameter at 646m is 200.23m. The beam diameter at 647m is 200.54m. The beam diameter at 648m is 200.85m. The beam diameter at 649m is 201.16m. The beam diameter at 650m is 201.47m. The beam diameter at 651m is 201.78m. The beam diameter at 652m is 202.09m. The beam diameter at 653m is 202.40m. The beam diameter at 654m is 202.71m. The beam diameter at 655m is 203.02m. The beam diameter at 656m is 203.33m. The beam diameter at 657m is 203.64m. The beam diameter at 658m is 203.95m. The beam diameter at 659m is 204.26m. The beam diameter at 660m is 204.57m. The beam diameter at 661m is 204.88m. The beam diameter at 662m is 205.19m. The beam diameter at 663m is 205.50m. The beam diameter at 664m is 205.81m. The beam diameter at 665m is 206.12m. The beam diameter at 666m is 206.43m. The beam diameter at 667m is 206.74m. The beam diameter at 668m is 207.05m. The beam diameter at 669m is 207.36m. The beam diameter at 670m is 207.67m. The beam diameter at 671m is 207.98m. The beam diameter at 672m is 208.29m. The beam diameter at 673m is 208.60m. The beam diameter at 674m is 208.91m. The beam diameter at 6

Datos técnicos

Concept

Proyector lineal orientable de LED.

Lámpara

Tarjetas lineales LED Mid Power High Efficiency Ra80.

Clase de eficiencia energética	B
Potencia nominal	30.9
Flujo nominal	5754lm
Índice de reproducción cromática	80
CCT nominal	4000K
Duración útil (L80/B10)	100000h tq +25°C
Duración útil (L90/B10)	59000h tq +25°C

TARGETTI

CCIAA Firenze
Capital Social: € 500.000,00
NIF (IT): 01537660480
R.E.A: FI-275656

Targetti Sankey S.r.l.
Via Giuseppe Garibaldi, 82
50041 Calenzano (FI)
Italy

Tel: +39 055 37911
targetti.com
targetti@targetti.com

En función de la continua evolución tecnológica de los componentes electrónicos, los datos indicados están sujetos a actualización por lo que es necesario solicitar confirmación al hacer el pedido.
El flujo luminoso y la potencia eléctrica presentan tolerancias +/-10% respecto al valor indicado. tq +25°C (CIE 121).

Nos reservamos el derecho de realizar cambios técnicos.

Datos técnicos

Características luminotécnicas

Grupo óptico compuesto por una lente primaria cilíndrica de PMMA, reflector de aluminio anodizado de alta reflectancia y filtro holográfico. Versión comfort con accesorio óptico integrado: pantalla antideslumbramiento longitudinal de acero pintado negro.

Óptica	Grazing
Apertura del haz de luz	GRZ 20°x75°
Eficiencia óptica	59,8%
Flujo luminaria	3441lm
Rendimiento luminoso	100lm/W
Seguridad fotobiológica	Conforme al grupo de riesgo RG1 (Riesgo Bajo)

Características mecánicas

Cuerpo de aluminio extruido anodizado 15µ. Pantalla plana de cristal extra claro de 5mm de espesor. Cuerpo de la luminaria orientable respecto a la superficie de instalación mediante estribos accesorios.

Color y acabado	Cobre bruñido
Dimensiones	AxBxH 868x55x90mm
Peso	4,4Kg
Versión	Comfort
Grado de protección	IP66,IP67,IP68
Resistencia mecánica	IK07

Características eléctricas

Driver integrado, en la versión DALI2 (posicionado debajo del cuerpo óptico). Equipado con cableado pasante con conectores IN/OUT para instalación de panel con sellado longitudinal (el sellado limita el riesgo de ascenso de la humedad hacia el driver / cuerpo óptico). Luminaria compatible con EN 60598-2-22 para suministro de energía desde un sistema de emergencia centralizado CPSS (Central Power Supply System), no incorporado en la luminaria - áreas de alto riesgo excluidas. La potencia y el flujo predeterminados son 100% en CA y 100% en CC.

Potencia luminaria	34,3W
Alimentación	220-240Vac 50/60Hz
Clase de aislamiento	CLASE 1
Tipo driver / Control	DALI2 - PUSH
Driver incluido	SÍ
SAFE FLICKER	PstLM=<1 e SVM=<0,4 (IEC TR 61547-1 e IEC TR 63158), garantizando una luz más cómoda y segura
Temperatura ambiente	-25°C / +35°C

Instalación

A completar con estribos de fijación fijos u orientables de acero inoxidable pintado con pintura en polvo (disponible en diferentes longitudes).

Notas

Sistema de control Casambi disponible como accesorio. Disponible bajo petición la versión 110-277Vac. Puesta en servicio del sistema de control por APP gratuita; la intervención de un técnico especializado puede presupuestarse previa solicitud.

Garantía

5 años.

Datos técnicos

Advertencias

Luminaria diseñada para su eliminación/reciclaje al final de su vida útil. Fuente luminosa reemplazable (solo LED) por un profesional. Equipo de control reemplazable por un profesional.

TARGETTI

CCIAA Florencia
Capital Social: € 500.000,00
NIF (IT): 01537660480
R.E.A: FI-275656

Targetti Sankey S.r.l.
Via Giuseppe Garibaldi, 82
50041 Calenzano (FI)
Italy

Tel: +39 055 37911
targetti.com
targetti@targetti.com

En función de la continua evolución tecnológica de los componentes electrónicos, los datos indicados están sujetos a actualización por lo que es necesario solicitar confirmación al hacer el pedido.
El flujo luminoso y la potencia eléctrica presentan tolerancias +/-10% respecto al valor indicado, tq +25°C (CIE 121).

Nos reservamos el derecho de realizar cambios técnicos.

Códigos para completar

Estribo



CÓDIGO	COLOR
A108BT	

Kit estribos fijo en acero inoxidable, pintado en polvo para instalación en superficie (2 unidades).



CÓDIGO	COLOR	VERSIÓN	L
A109BC		Corta	57mm

Kit estribos orientable en acero inoxidable, pintado en polvo para instalación en superficie (2 unidades).
Rotación +/-90°.



CÓDIGO	COLOR	VERSIÓN	L
A110BC		Mediana	157mm

Kit estribos orientable en acero inoxidable, pintado en polvo para instalación en superficie (2 unidades).
Rotación +/-90°.



CÓDIGO	COLOR	VERSIÓN	L
A111ZBC		Larga	303mm
A111YBC		Larga	453mm
A111XBC		Larga	603mm

Kit estribos orientable en acero inoxidable, pintado en polvo para instalación en superficie (2 unidades).
Rotación +/-90°.

Sistema de fijación



CÓDIGO	COLOR	H
A112		181mm

Piqueta para terreno.
Acero inoxidable pintado con pintura en polvo.
Para uso con A108, A109, A110.

Accesorios

Conector



CÓDIGO
A117

Conector hembra IP66/IP68.
5 polos (STANDARD 3G2,5mm² MAX, DALI 5G1,5mm² MAX).
Diámetro del cable de 7 a 12mm.

Accesorios

Conector



CÓDIGO

A118

kit de conectores IP66/IP68 macho/hembra.
5 polos (STANDARD 3G2,5mm² MAX, DALI 5G1,5mm² MAX).
Diámetro del cable de 7 a 12mm.



CÓDIGO

A119

Caja de conexión múltiple IP68.
1 IN - 2 OUT 5 polos (STANDARD 3G2,5mm² MAX, DALI 5G1,5mm² MAX).
Diámetro del cable de 7 a 12mm.

Cable



CÓDIGO

L

A120Z

1000mm

A120Y

2000mm

A120X

3000mm

Cable de conexión.
Equipado con conectores 5 polos.
Para versión ON-OFF y DALI.

Sistemas de control



CÓDIGO

1E3048

Unidad de control inalámbrico IP67 con interfaz DALI.
Genera un bus DALI2 local, que permite conectarse directamente a un driver LED con una interfaz DALI.
El módulo se puede usar solo en un sistema cerrado y no se puede conectar a redes DALI ya existentes.
El módulo se controla de modo inalámbrico mediante la aplicación Casambi para smartphone y tablet mediante la tecnología Bluetooth 5.0.
Los dispositivos crean automáticamente una red de malla inalámbrica flexible, robusta y confiable, la cual permite administrar de manera fácil y eficiente una gran cantidad de productos.
La unidad de control está preconfigurada con el perfil DALI 1CH, es decir, el dispositivo puede controlar un solo controlador DALI con comandos broadcast.
Además de DALI broadcast, también están disponibles otras modalidades de funcionamiento, como:

- Botón (normalmente abierto)
- Unidad de control 0/1-10V
- Unidad de control DALI Tunable White DT8
- Sensor de presencia

Si es diferente a la modalidad preimpostada, el perfil de funcionamiento deseado debe ser configurado directamente por el usuario antes de emparejar la unidad de control con la red Casambi.
LxHxP=108x28x65mm.

TARGETTI

CCIAA Florencia
Capital Social: € 500.000,00
NIF (IT): 01537660480
R.E.A: FI-275656

Targetti Sankey S.r.l.
Via Giuseppe Garibaldi, 82
50041 Calenzano (FI)
Italy

Tel: +39 055 37911
targetti.com
targetti@targetti.com

En función de la continua evolución tecnológica de los componentes electrónicos, los datos indicados están sujetos a actualización por lo que es necesario solicitar confirmación al hacer el pedido.
El flujo luminoso y la potencia eléctrica presentan tolerancias +/-10% respecto al valor indicado. tq +25°C (CIE 121).

Nos reservamos el derecho de realizar cambios técnicos.

Accesorios

Sistemas de control



CÓDIGO
1E4369

Extensor IP67: unidad de control inalámbrica para driver LED con interfaz de atenuación DALI basada en la tecnología Casambi. Dispone de una salida DALI2 a través de la cual se pueden controlar hasta 40 luminarias. Añadiendo una ulterior fuente de alimentación DALI BUS externa, se pueden controlar hasta 64 dispositivos. El extensor IP67 está preajustado al perfil DALI broadcast, es decir, todas las luminarias conectadas a él son regulables al mismo nivel. Además del DALI broadcast, hay otras modalidades de operación disponibles, como:

- EXTENDER DALI 8CH
- EXTENDER DALI Tunable White
- EXTENDER DALI 4CH
- EXTENDER DALI DT8 Tunable White


Si es diferente a la modalidad preconfigurada, el perfil de funcionamiento deseado debe ser configurado directamente por el usuario antes de emparejar la unidad de control con la red Casambi.
LxHxP=148x40x150mm.

Parasol



CÓDIGO	COLOR	L
A148YBC		868mm

Paraluce estetico e antiabbagliamento in alluminio verniciato. Versione per proiettore standard e side box.



CÓDIGO	COLOR	L
A156YBC		868mm

Paraluce estetico e antiabbagliamento in alluminio verniciato. Versione per proiettore standard.