

LIGHTING SYSTEMS

Fortyeight Label 6 - Short arm

Code
1T9059DA

LIGHT COLOUR	LIGHT DISTRIBUTION	OUTPUT
3000K 90	MWFL 41°	15W 1597lm
POWER SUPPLY CONTROL	COLOUR	
48Vdc		



The figures on the drawing are expressed in mm.



--

Technical Data

Concept

Low voltage adjustable LED professional projector.

Source

High efficiency Chip on Board LED Ra90. 3500K on request.

Energy efficiency class	D
Nominal power	14W
Nominal flux	1866lm
Colour rendering index	90
R _f	92
R _g	101
CCT nominal	3000K
SDCM	1.5
Lifetime (L80/B10)	72000h tq +25°C
Lifetime (L90/B10)	72000h tq +25°C

TARGETTI

CCIAA Firenze
Share Capital: € 500.000,00
VAT N. (IT): 01537660480
R.E.A: FI-275656

Targetti Sankey S.r.l.
Via Giuseppe Garibaldi, 82
50041 Calenzano (FI)
Italy

Tel: +39 055 37911
targetti.com
targetti@targetti.com

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.
Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.

Technical Data

Illuminotechnical characteristics

MWFL - precision optics with a black silicone cut off ring. Version with a transparent PMMA lens.

Optic	MWFL
Beam angles	MWFL
Optical efficiency	85.6%
Fixture flux	1597lm
Luminous efficacy	106lm/W
Photobiological safety	Compliant with RG1 low risk group

Mechanical characteristics

Painted die-cast aluminium body. The optical unit can be adjusted from 0° a 90° on the vertical plane and 360° on the horizontal plane with friction locking system.

Colour and finish	Plaster white
Dimensions	ØxH 59x105mm
Weight	0.2Kg
Version	Short arm - DALI
Degree of protection	IP20

Electrical characteristics

DALI version with track power supply. Casambi control system available using a dedicated accessory.

Fixture Power	15W
Power supply	48Vdc
Insulation Class	CLASS 3
SAFE FLICKER	PstLM=<1 and SVM=<0.4 (IEC TR 61547-1 and IEC TR 63158), to ensure a more comfortable and safe light
Ambient temperature	0°C / +25°C

Installation

Quick coupling system for mounting the product on the track.

Notes

Not polarized fixture. The arm is and the adapter are supplied in the same colour as the body of the projector. 110-277Vac version available on request. Commissioning of the control system via free APP; the intervention of a specialist technician can be quoted on request.

Warranty

5 years.

Warning

Luminaire designed for disposal/recycling at end-of-life. Replaceable (LED only) light source by a professional. Replaceable control gear by a professional.

TARGETTI

CCIAA Firenze
Share Capital: € 500.000,00
VAT N. (IT): 01537660480
R.E.A: FI-275656

Targetti Sankey S.r.l.
Via Giuseppe Garibaldi, 82
50041 Calenzano (FI)
Italy

Tel: +39 055 37911
targetti.com
targetti@targetti.com

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.
Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.

Accessories

Filter



CODE	Ø
1T4721	50mm

PMMA holographic filter with blade effect to ovalize the light beam; more evident when combined with spot and flood optics.

Grid



CODE	Ø
1T4322	50mm

Anti-glare louver.
Black painted metal honeycomb structure.
Complete with holographic diffusion filter.