
TRACK PROJECTORS


Zeno 105



Code
T041NSL740ELPW


LIGHT COLOUR	LIGHT DISTRIBUTION	OUTPUT
4000K 97	NSP 10°	10.6W 810lm

POWER SUPPLY CONTROL	COLOUR
220-240Vac ON-OFF	



The figures on the drawing are expressed in mm.





4000K		H(m)	D(m)	Emax(lx)
Ra97			10°	
Fixture Power	11W	1	0.17	21480
Source Flux	921lm	2	0.34	5370
Fixture Flux	810lm	3	0.51	2387
Efficacy	76lm/W	4	0.68	1343
Imax	21480cd	5	0.85	859

Technical Data

Concept

Professional adjustable LED projector.

Source

High efficiency Chip on Board LED Ra97.	
Energy efficiency class	F
Nominal power	9,2W
Nominal flux	921lm
Colour rendering index	97
Rf	92
Rg	102
CCT nominal	4000K
Lifetime (L80/B10)	52000h tq +25°C
Lifetime (L90/B10)	52000h tq +25°C

TARGETTI

CCIAA Firenze
Share Capital: € 500.000,00
VAT N. (IT): 01537660480
R.E.A: FI-275656

Targetti Sankey S.r.l.
Via Giuseppe Garibaldi, 82
50041 Calenzano (FI)
Italy

Tel: +39 055 37911
targetti.com
targetti@targetti.com

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.
Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.

Technical Data

Illuminotechnical characteristics

Narrow Spot version with optical grade PMMA TIR lenses.

Optic	NSP
Beam angles	NSP
Optical efficiency	87.93%
Fixture flux	810lm
Luminous efficacy	76lm/W
Photobiological safety	Compliant with RG1 low risk group

Mechanical characteristics

Die-cast painted aluminium body. The optical unit can be adjusted from 0 to -90° on the vertical plane; and 355° on the horizontal plane with aiming blocking system.

Colour and finish	Plaster white
Dimensions	ØxH 105x59mm
Weight	0.61Kg
Degree of protection	IP20

Electrical characteristics

ON-OFF electronic driver integrated into the track adapter.

Fixture Power	10.6W
Power supply	220-240Vac 50/60Hz
Insulation Class	CLASS 2
Type of driver / Control	ON-OFF
Driver included	YES
Ambient temperature	0°C / +25°C

Installation

Electrified track mounting. Mechanical and optic accessories available, to be installed with holder ring (necessary).

Notes

110-277Vac version available on request.

Regulations and Certifications

CE

Warranty

5 years.

Warning


Luminaire designed for disposal/recycling at end-of-life. Replaceable (LED only) light source by a professional. Replaceable control gear by a professional.

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.
Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.

Accessories

Filter



CODE
1T6572

Blade of light filter.
Methacrylate holographic filter.
This makes the beam take on an oval shape and when combined with spotlights, the light blade appears more prominent.
To be completed with a dedicated holder ring.

Grid



CODE	COLOUR
1T6573	●

Anti-glare louver.
Black lacquered aluminium honeycomb structure.
To be completed with a dedicated holder ring.

Cut-off



CODE	COLOUR
1T6574	●

Black painted steel cut-off.
To be completed with a dedicated holder ring.



CODE	COLOUR
1T6575	●

Black painted steel asymmetric cut-off.
To be completed with a dedicated holder ring.


Ray Shade



CODE	COLOUR
1T6576	●

Adjustable barn doors flaps made of black painted steel.
To be completed with a dedicated holder ring.

Holder Ring




CODE	COLOUR
1T6571	●

Black painted aluminium accessory holder ring.

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.
Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.

Bracket



CODE	COLOUR
A058PW	○
A058DB	●

Rigid support bracket for projectors with Eurostandard Plus track attachment.
For compatibility and use please refer to the assembly instructions for the projectors.

For installation of Zeno 105 projectors on wall vertical tracks.

TARGETTI

CCIAA Firenze
Share Capital: € 500.000,00
VAT N. (IT): 01537660480
R.E.A: FI-275656

Targetti Sankey S.r.l.
Via Giuseppe Garibaldi, 82
50041 Calenzano (FI)
Italy

Tel: +39 055 37911
targetti.com
targetti@targetti.com

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.
Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.