
CEILING LUMINAIRES | PENDANT LUMINAIRES


Logico Easy Stand Alone 37 - UGR19



Code
T018BY840D2PW

LIGHT COLOUR	LIGHT DISTRIBUTION	OUTPUT
4000K 80	UGR19	46W 5451lm

POWER SUPPLY CONTROL	COLOUR
220-240Vac DALI2	



The figures on the drawing are expressed in mm.

2.85 | IP40 | IK02 | CE



4000K		H(m)	D1(m)	D2(m)	Emax(lx)
Ra80			66°	64°	
Fixture Power	46W	1	1.29	1.26	2419
Source Flux	5451lm	2	2.58	2.52	605
Fixture Flux	5452lm	3	3.86	3.78	269
Efficacy	119lm/W	4	5.15	5.04	151
Imax	2737cd	5	6.44	6.30	97

Technical Data

Concept

Linear stand alone LED fixture for ceiling mounted or suspension installation.

Source

LED Engine made of linear LED boards Ra80.	
Energy efficiency class	C, D
Nominal power	39W
Nominal flux	5451lm
Colour rendering index	80
Rf	84
Rg	95
CCT nominal	4000K
Lifetime (L80/B10)	100000h tq +25°C
Lifetime (L90/B10)	50000h tq +25°C

TARGETTI

CCIAA Firenze
Share Capital: € 500.000,00
VAT N. (IT): 01537660480
R.E.A: FI-275656

Targetti Sankey S.r.l.
Via Giuseppe Garibaldi, 82
50041 Calenzano (FI)
Italy

Tel: +39 055 37911
targetti.com
targetti@targetti.com

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.
Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.

Technical Data

Illuminotechnical characteristics

Direct/indirect emission. Controlled light. UGR19 Optics: optical system made of lenses with differentiated facets for optimizing the direction of the luminous flux and cellular optics in white anti-glare polycarbonate (UGR<19 and L65<1500 cd/m² EN-12464-1).

Emission	Direct/Indirect
Optic	UGR19
Optical efficiency	100%
Fixture flux	5451lm
Luminous efficacy	119lm/W
Photobiological safety	Compliant with RG0 exempt risk group

Mechanical characteristics

Painted extruded aluminium body with 37mm section and polycarbonate end caps. Upper closing screen in translucent polycarbonate.

Colour and finish	White
Dimensions	AxBxH 1404x37x80mm
Weight	2.85Kg
Version	Linear
Degree of protection	IP40
Mechanical Resistance	IK02

Electrical characteristics

Integrated electronic DALI2 driver. Luminaire compliant with EN 60598-2-22 for power supply from a centralised emergency system CPSS (Central Power Supply System), not incorporated in the luminaire - high risk areas excluded. The default power and flux are 100% in AC and 15% in DC.

Fixture Power	46W
Power supply	220-240Vac 50/60Hz
Insulation Class	CLASS 1
Type of driver / Control	DALI2
Driver included	YES
SAFE FLICKER	PstLM=<1 and SVM=<0.4 (IEC TR 61547-1 and IEC TR 63158), to ensure a more comfortable and safe light
Ambient temperature	0°C / +25°C
Relative humidity UR	<85%

Installation

To be completed with mounting systems for surface or suspended application.

Regulations and Certifications

CE

Warranty

5 years.

Technical Data

Warning

Luminaire designed for disposal/recycling at end-of-life. Replaceable (LED only) light source by a professional. Replaceable control gear by a professional.

TARGETTI

CCIAA Firenze
Share Capital: € 500.000,00
VAT N. (IT): 01537660480
R.E.A: FI-275656

Targetti Sankey S.r.l.
Via Giuseppe Garibaldi, 82
50041 Calenzano (FI)
Italy

Tel: +39 055 37911
targetti.com
targetti@targetti.com

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.
Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.

Accessories

Canopy



CODE	COLOUR
A004W	◯

Canopy with 5 poles terminal block.
Feeding cable not included.

Bracket



CODE
A007S

Bracket with adjustment system for suspended installation (2 pieces).
Two brackets needed for each lighting module.

For LOGICO EASY 37.

Suspension



CODE	VERSION
A008T	L=6m
A008U	L=5m
A008V	L=4m
A008W	L=3m
A008X	L=2m
A008Y	L=1m
A008Z	L=0,5m

Suspension cable (2 pieces).

TARGETTI

CCIAA Firenze
Share Capital: € 500.000,00
VAT N. (IT): 01537660480
R.E.A: FI-275656

Targetti Sankey S.r.l.
Via Giuseppe Garibaldi, 82
50041 Calenzano (FI)
Italy

Tel: +39 055 37911
targetti.com
targetti@targetti.com

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.
Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.