


PROJECTORS

Jedi Compact  
Outdoor Projector  
Louvre - Remote  
driver - L. 873,5mm

Code  
1E3339

| LIGHT COLOUR         | LIGHT DISTRIBUTION | OUTPUT        |
|----------------------|--------------------|---------------|
| 2700K<br>80          | Wall Washer        | 36W<br>2747lm |
| POWER SUPPLY CONTROL | COLOUR             |               |
| 500mA                |                    |               |



The figures on the drawing are expressed in mm.



Technical Data

Concept

Adjustable linear LED projector.

TARGETTI

CCIAA Firenze  
Share Capital: € 500.000,00  
VAT N. (IT): 01537660480  
R.E.A: FI-275656

Targetti Sankey S.r.l.  
Via Giuseppe Garibaldi, 82  
50041 Calenzano (FI)  
Italy  
  
Tel: +39 055 37911  
targetti.com  
targetti@targetti.com

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.  
Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).  
  
We reserve the right to make technical changes.

## Technical Data

### Source

High Power High Efficiency Ra80 linear LED board. Ra90 on request.

|                         |                  |
|-------------------------|------------------|
| Energy efficiency class | E                |
| Nominal power           | 36W              |
| Nominal flux            | 4845lm           |
| Colour rendering index  | 80               |
| Rf                      | 83               |
| Rg                      | 97.3             |
| CCT nominal             | 2700K            |
| SDCM                    | 3                |
| Lifetime (L80/B10)      | 100000h tq +25°C |
| Lifetime (L90/B10)      | 59000h tq +25°C  |

### Illuminotechnical characteristics

Internal optical system composed of a primary cylindrical glass lens, a high reflectance anodised aluminium reflector and an integrated holographic filter. Wall Washer version. Version with an integrated Louver effect grid.

|                        |                                   |
|------------------------|-----------------------------------|
| Optic                  | Wall Washer                       |
| Beam angles            | WW                                |
| Optical efficiency     | 56.7%                             |
| Fixture flux           | 2747lm                            |
| Luminous efficacy      | 76lm/W                            |
| Photobiological safety | Compliant with RG1 low risk group |

### Mechanical characteristics

Extruded anodised aluminium 15μ body. Extra clear 5mm thick glass flat screen. The body of the fixture is adjustable and can be installed away from the mounting surface using accessory snap brackets.

|                       |                        |
|-----------------------|------------------------|
| Colour and finish     | Aluminium              |
| Dimensions            | AxBxH 874x53x43mm      |
| Weight                | 2.6Kg                  |
| Version               | Louvre - Remote driver |
| Degree of protection  | IP66,IP67              |
| Mechanical Resistance | IK08                   |

### Electrical characteristics

Remote driver version. The optical unit is pre-cabled with a 1 metre 3x1mm<sup>2</sup> H07RN-F cable. Electronic ON-OFF or DALI power supply, pre-cabled with a 1 metre 3x1mm<sup>2</sup> H07RN-F cable for the connection to the optical unit and a 3x1mm<sup>2</sup> or 5x1mm<sup>2</sup> cable for the connection to the mains and to the DALI.

|                     |               |
|---------------------|---------------|
| Fixture Power       | 36W           |
| Power supply        | 500mA         |
| Insulation Class    | CLASS 1       |
| Driver included     | NO            |
| Ambient temperature | -25°C / +35°C |

# TARGETTI

CCIAA Firenze  
Share Capital: € 500.000,00  
VAT N. (IT): 01537660480  
R.E.A: FI-275656

Targetti Sankey S.r.l.  
Via Giuseppe Garibaldi, 82  
50041 Calenzano (FI)  
Italy

Tel: +39 055 37911  
targetti.com  
targetti@targetti.com

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.  
Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.

## Technical Data

## Installation

To be completed with stainless steel adjustable brackets.

## Notes

Casambi control system available as an accessory (only for DALI versions). Uses the "Waterblock Smart" technical solution that involves resin coating the connection cables, limiting the risk of humidity reaching the driver or the fixture. 110-277Vac version available on request. Values related to the power consumption of the fixture do not take into account the consumption of the accessory driver, which depends on the choice of driver. Commissioning of the control system via free APP; the intervention of a specialist technician can be quoted on request.

## Warranty

5 years.

## Warning

Luminaire designed for disposal/recycling at end-of-life. Replaceable (LED only) light source by a professional.

# TARGETTI

CCIAA Firenze  
Share Capital: € 500.000,00  
VAT N. (IT): 01537660480  
R.E.A: FI-275656

Targetti Sankey S.r.l.  
Via Giuseppe Garibaldi, 82  
50041 Calenzano (FI)  
Italy

Tel: +39 055 37911  
targetti.com  
targetti@targetti.com

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.  
Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.

## Related codes

## Bracket



## CODE

**1E3304**

Stainless steel short bracket kit for surface installation (2 pieces).  
Rotation +/-90°.



## CODE

**1E3306**

Stainless steel long bracket kit for surface installation (2 pieces).  
Rotation +/-90°.


## Power Supply



## CODE

**1E3558**

ON-OFF power supply kit made of an aluminium watertight box (LxHxP=486x49.5x44mm) complete with power supply input cable (1 metre, type HO7RN8-F, 3G1mm<sup>2</sup>) and an output cable to the fixture (1 metre, type HO7RN8-F, 3G1mm<sup>2</sup>).  
For the L 593.5/625/873.5/905/1153.5/1185mm versions.



## CODE

**1E3560**

DALI power supply version kit composed of an aluminium watertight box (LxHxP=486x49.5x44mm) complete with power supply input cable (1 metre, type HO7RN8-F, 5G1mm<sup>2</sup>) and an output cable to the fixture (1 metre, type HO7RN8-F, 3G1mm<sup>2</sup>).  
For the L 873.5/905/1153.5/1185mm versions.

## Accessories

## Tool



## CODE

**1E3305**

Tightening wrench for the connector kit.

## Connector



## CODE

**1E2769**

Linear connection box IP66/IP68.  
5 poles max. wire section 1.5mm<sup>2</sup>.  
Cable diameter range from 7 to 12mm.

## Accessories

## Connector



## CODE

1E2494

Multiple connection box IP68.  
1 IN - 3 OUT 4 poles max. wire section 2.5mm<sup>2</sup>.  
Cable diameter range from 6 to 12mm.



## CODE

1E3184

IP68 4-way cable connector (5 pole).

## Control systems



## CODE

1E3048

IP67 wireless control unit with DALI interface.  
It generates a local DALI2 bus, enabling a direct connection to a DALI interface LED driver.  
The module can only be used in a closed system and cannot be connected to an existing DALI network.  
The module is wireless controlled using a Casambi app for smartphones and tablets using Bluetooth 5.0 technology.  
The devices automatically create an adaptive, robust, and reliable wireless mesh network, allowing for the easy and efficient management of a high number of fixtures.  
The control unit is preset to the DALI 1CH profile, meaning the device can control a single DALI driver with broadcast commands.  
In addition to the DALI broadcast, other operating modes are available, such as:

- Button (normally open)
- Control unit 0/1-10V
- Control unit DALI Tunable White DT8
- Presence sensor

If different from the preset mode, the desired operating profile must be set directly by the user before coupling the control unit to the Casambi network.  
LxHxP=108x28x65mm.



## CODE

1E4369

IP67 Extender for wireless control of LED driver with dimming DALI interface based on Casambi technology.  
It has a DALI2 output with the capacity to control up to 40 lighting fixtures.  
With the addition of a further external BUS DALI power supply it is possible to control up to 64 fixtures.  
IP67 Extender is preset to the DALI broadcast profile, meaning all the luminaires connected to it are dimmable at the same level.  
In addition to the DALI broadcast other operating modes are available, such as:

- EXTENDER DALI 8CH
- EXTENDER DALI Tunable White
- EXTENDER DALI 4CH
- EXTENDER DALI DT8 Tunable White

If different from the preset mode, the desired operating profile must be set directly by the user before coupling the extender to the Casambi network.  
LxHxP=148x40x150mm.

# TARGETTI

CCIAA Firenze  
Share Capital: € 500.000,00  
VAT N. (IT): 01537660480  
R.E.A: FI-275656

Targetti Sankey S.r.l.  
Via Giuseppe Garibaldi, 82  
50041 Calenzano (FI)  
Italy

Tel: +39 055 37911  
targetti.com  
targetti@targetti.com

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.  
Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.

## Accessories

## Surge protector



## CODE

A013A

Surge protector compatible with CLASS I lighting fixtures.  
Operating voltage 230-277Vac.  
SPD type 2+3.  
Max surge protection 10kV.  
CLASS I  
IP67

**TARGETTI**

CCIAA Firenze  
Share Capital: € 500.000,00  
VAT N. (IT): 01537660480  
R.E.A: FI-275656

Targetti Sankey S.r.l.  
Via Giuseppe Garibaldi, 82  
50041 Calenzano (FI)  
Italy

Tel: +39 055 37911  
targetti.com  
targetti@targetti.com

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.  
Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.