

- IN-GROUND LUMINAIRES
- RECESSED CEILING LUMINAIRES
- WALL RECESSED LUMINAIRES

Keplero Quantum 130

Adjustable

Code

E065ZML830CSS

| LIGHT COLOUR         | LIGHT DISTRIBUTION                                                                | OUTPUT               |
|----------------------|-----------------------------------------------------------------------------------|----------------------|
| 3000K<br>80          | Zoom<br>16°-42°                                                                   | 13.8W<br>1194-1239lm |
| POWER SUPPLY CONTROL | COLOUR                                                                            |                      |
| 700mA                |  |                      |



The figures on the drawing are expressed in mm.



The fixture's photometric values  
can be found on the following pages

Technical Data

Concept

Recessed professional projector with an adjustable optical unit.

Source

High efficiency Chip on Board LED. 3000K (Ra80) colour temperature.

|                         |                 |
|-------------------------|-----------------|
| Energy efficiency class | C               |
| Nominal power           | 12W             |
| Nominal flux            | 1974lm          |
| Colour rendering index  | 80              |
| Rf                      | 84              |
| Rg                      | 97              |
| CCT nominal             | 3000K           |
| Lifetime (L80/B10)      | 56000h tq +25°C |
| Lifetime (L90/B10)      | 56000h tq +25°C |

TARGETTI

CCIAA Firenze  
Share Capital: € 500.000,00  
VAT N. (IT): 01537660480  
R.E.A: FI-275656

Targetti Sankey S.r.l.  
Via Giuseppe Garibaldi, 82  
50041 Calenzano (FI)  
Italy  
  
Tel: +39 055 37911  
targetti.com  
targetti@targetti.com

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.  
Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).  
  
We reserve the right to make technical changes.

## Technical Data

### Illuminotechnical characteristics

Optical system made of a double optical grade PMMA lens and a holographic diffusing filter for continuous adjustment of the beam angle (from Spot to Medium Wide Flood). Adjustability of the optical unit up to 20° on the vertical plane. Tilting of the optical unit and adjustment of the beam angle made through external regulations without opening the product.

|                        |                                   |
|------------------------|-----------------------------------|
| Optic                  | Zoom                              |
| Beam angles            | SP-MWFL                           |
| Optical efficiency     | See photometries                  |
| Fixture flux           | See photometries                  |
| Luminous efficacy      | See photometries                  |
| Photobiological safety | Compliant with RG1 low risk group |

### Mechanical characteristics

Die-cast aluminium body with 2 layers of protection: cataphoresis and black paint. Ultra flat decorative ring with a flared edge, made of brushed stainless steel (AISI 316) in a natural finish. Extra clear protective glass.

|                       |                         |
|-----------------------|-------------------------|
| Colour and finish     | Brushed stainless steel |
| Dimensions            | ØxH 130x94mm            |
| Weight                | 1Kg                     |
| Version               | Extra-clear glass       |
| Degree of protection  | IP66,IP67,IP68          |
| Mechanical Resistance | IK10                    |

### Electrical characteristics

Constant current power supply. ON-OFF or DALI2 remote driver to be ordered separately. Precabled with 1,5m 2x0,5mm² cable. Casambi control system available via accessory (for products with DALI2 driver only).

|                     |               |
|---------------------|---------------|
| Fixture Power       | 13.8W         |
| Power supply        | 700mA         |
| Insulation Class    | CLASS 3       |
| Driver included     | NO            |
| Ambient temperature | -25°C / +50°C |

### Installation

In-ground installation by a reinforced nylon sleeve, to be ordered separately. Sleeves are available for flush or trim installation. 20kN resistance to static load. Wall/ceiling installation by the accessory mounting systems.

### Notes

IP68: the fixture is not suitable for permanent underwater installation but can withstand temporary accidental immersion to a depth of 1.5 metres (max.1h). All the Keplero Quantum 130 versions meet the drive-over and walk-over requirements set out in the EN 60598-2-13 standard. It features the "Waterblock Smart" technical solution which involves resin-sealing the connection cables to minimize the risk of moisture rising into the fixture. Commissioning of the control system via free APP; the intervention of a specialist technician can be quoted on request.

### Warranty

5 years.

### Warning

Luminaire designed for disposal/recycling at end-of-life. Replaceable (LED only) light source by a professional. Non-replaceable control gear.

# TARGETTI

CCIAA Firenze  
Share Capital: € 500.000,00  
VAT N. (IT): 01537660480  
R.E.A: FI-275656

Targetti Sankey S.r.l.  
Via Giuseppe Garibaldi, 82  
50041 Calenzano (FI)  
Italy

Tel: +39 055 37911  
targetti.com  
targetti@targetti.com

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.  
Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.

Photometries

|    |                    |        |
|----|--------------------|--------|
| SP | Fixture flux       | 1239lm |
|    | Luminous efficacy  | 90lm/W |
|    | Optical efficiency | 62.78% |



|     |                    |        |
|-----|--------------------|--------|
| WFL | Fixture flux       | 1194lm |
|     | Luminous efficacy  | 87lm/W |
|     | Optical efficiency | 60.49% |



## Related codes

## Sleeve



| CODE | P     | H     | L     |
|------|-------|-------|-------|
| A121 | 317mm | 125mm | 317mm |

Reinforced nylon installation sleeve.  
The sleeve is designed for the trim installation of the fixture.  
Complete with a cover element to protect the recessed housing during concrete pouring.  
AxB 317x317 H. 125



| CODE   | COLOUR                                                                            | P     | H     | L     |
|--------|-----------------------------------------------------------------------------------|-------|-------|-------|
| A122SS |  | 317mm | 127mm | 317mm |

Reinforced nylon installation sleeve.  
The sleeve is designed for the flush installation of the fixture.  
Complete with a cover element to protect the recessed housing during concrete pouring.  
AxB 317x317 H. 127

## Mounting System



| CODE |
|------|
| A123 |


Steel spring kit for wall and ceiling installations.

## Power Supply



| CODE   | IP   | OUTPUT CURRENT | POWER SUPPLY | POWER   | LXHXP       |
|--------|------|----------------|--------------|---------|-------------|
| A140EL | IP67 | 700mA          | 220-240Vac   | 25W MAX | 114x32x44mm |

Electronic ON-OFF power supply.



| CODE   | IP   | OUTPUT CURRENT | POWER SUPPLY | POWER   | LXHXP       |
|--------|------|----------------|--------------|---------|-------------|
| A140D2 | IP67 | 700mA          | 220-240Vac   | 25W MAX | 114x32x44mm |

DALI2 power supply.

## Accessories

## Connector



| CODE   |
|--------|
| 1E2493 |

Linear connection box IP68.  
4 poles max. wire section 2.5mm².  
Cable diameter range from 7 to 12mm.

# TARGETTI

CCIAA Firenze  
Share Capital: € 500.000,00  
VAT N. (IT): 01537660480  
R.E.A: FI-275656

Targetti Sankey S.r.l.  
Via Giuseppe Garibaldi, 82  
50041 Calenzano (FI)  
Italy

Tel: +39 055 37911  
targetti.com  
targetti@targetti.com

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.  
Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.

## Accessories

### Connector

**CODE****1E2494**

Multiple connection box IP68.  
1 IN - 3 OUT 4 poles max. wire section 2.5mm<sup>2</sup>.  
Cable diameter range from 6 to 12mm.

### Tool

**CODE****1E3305**

Tightening wrench for the connector kit.