PROJECTORS


Dart Round Small RGBW



Code
1E4060

LIGHT COLOUR	LIGHT DISTRIBUTION	OUTPUT
RGBW	NSP 10°	11.4W 455lm

POWER SUPPLY CONTROL	COLOUR
850mA	



The figures on the drawing are expressed in mm.

1 IP66 IK10 1.5M CE

The fixture's photometric values can be found on the following pages

Technical Data

Concept

Professional adjustable LED projector.

Source

RGBW light module made of RGBW LED multichip. Color temperature of the white source: 6500K.

Energy efficiency class	F
Nominal power	11,4W
Nominal flux	See photometries
Colour rendering index	
CCT nominal	See photometries
Lifetime (L80/B10)	100000h tq +25°C
Lifetime (L90/B10)	72000h tq +25°C

TARGETTI

CCIAA Firenze
Share Capital: € 500.000,00
VAT N. (IT): 01537660480
R.E.A: FI-275656

Targetti Sankey S.r.l.
Via Giuseppe Garibaldi, 82
50041 Calenzano (FI)
Italy

Tel: +39 055 37911
targetti.com
targetti@targetti.com

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.
Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.

Technical Data

Illuminotechnical characteristics

Equipped with precision methacrylate lens.

Optic	NSP
Beam angles	NSP
Optical efficiency	87.12%
Fixture flux	See photometries
Luminous efficacy	See photometries
Photobiological safety	Compliant with RG1 low risk group

Mechanical characteristics

Painted die-cast anodised aluminium body and painted stainless steel mounting bracket. Tempered extra clear front glass.

Colour and finish	Ferrite
Dimensions	ØxH 88x148mm
Weight	1Kg
Degree of protection	IP66
Mechanical Resistance	IK10

Electrical characteristics

Remote DMX-RDM electronic driver with 4 independent constant current outputs. The driver is housed inside an IP68 box and allows to control from 1 to 4 fixtures. Controlled using DMX-RDM protocols that make it possible to programme the fixture remotely (no dip-switch) using the DMX data line. Programming the fixtures is done using the USB-RDM programmer that is available as an accessory. All versions are pre-wired with a 1.5m long 8-pole feeding cable (to be connected to the IP68 driver box).

Fixture Power	See photometries
Power supply	850mA
Insulation Class	CLASS 3
Driver included	NO
Ambient temperature	-25°C / +35°C

Installation

Mounting bracket with aiming adjustability. Adjustable up to ±60° on the horizontal pane and +90°/-45° on the vertical plane.

Notes

Uses the "Waterblock Smart" technical solution that involves resin coating the connection cables, limiting the risk of humidity reaching the driver or the fixture. It is possible to subject the product to Cataphoresis treatment on request. 110-277Vac version available on request. Photometrics show the maximum emission values of fixtures. Values related to the power consumption of the fixture do not take into account the consumption of the accessory driver, which depends on the choice of driver. Commissioning of the control system via free APP; the intervention of a specialist technician can be quoted on request.

Regulations and Certifications

CE

Warranty

5 years.

Technical Data

Warning

Luminaire designed for disposal/recycling at end-of-life. Replaceable (LED only) light source by a professional.

TARGETTI

CCIAA Firenze
Share Capital: € 500.000,00
VAT N. (IT): 01537660480
R.E.A: FI-275656

Targetti Sankey S.r.l.
Via Giuseppe Garibaldi, 82
50041 Calenzano (FI)
Italy

Tel: +39 055 37911
targetti.com
targetti@targetti.com


Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.
Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.

Photometries

RGBW


Fixture Power	11.4W
Nominal flux	522lm
Fixture flux	455lm
Luminous efficacy	40lm/W



	-		H(m)	D(m)	Emax(lx)
	-			10°	
Fixture Power	11W	1		0.18	10482
Source Flux	522lm	2		0.35	2621
Fixture Flux	455lm	3		0.53	1165
Efficacy	40lm/W	4		0.71	655
TS1664 Imax=20066cd/klm	Imax	10482cd	5	0.88	419

RGB


Fixture Power	6.6W
Nominal flux	271lm
Fixture flux	236lm
Luminous efficacy	36lm/W



	-		H(m)	D(m)	Emax(lx)
	-			10°	
Fixture Power	7W	1		0.18	5445
Source Flux	271lm	2		0.35	1361
Fixture Flux	236lm	3		0.53	605
Efficacy	36lm/W	4		0.71	340
TS1664 Imax=20066cd/klm	Imax	5445cd	5	0.88	218

WHITE


CCT nominal	6500K
Fixture Power	3.1W
Nominal flux	287lm
Fixture flux	250lm
Luminous efficacy	81lm/W



	6500K		H(m)	D(m)	Emax(lx)
	-			10°	
Fixture Power	3W	1		0.18	5754
Source Flux	287lm	2		0.35	1438
Fixture Flux	250lm	3		0.53	639
Efficacy	81lm/W	4		0.71	360
TS1664 Imax=20066cd/klm	Imax	5754cd	5	0.88	230

RED


Fixture Power	2.3W
Nominal flux	106lm
Fixture flux	92lm
Luminous efficacy	40lm/W



	-		H(m)	D(m)	Emax(lx)
	-			10°	
Fixture Power	2W	1		0.18	2128
Source Flux	106lm	2		0.35	532
Fixture Flux	92lm	3		0.53	236
Efficacy	40lm/W	4		0.71	133
TS1664 Imax=20066cd/klm	Imax	2128cd	5	0.88	85

GREEN


Fixture Power	3.3W
Nominal flux	191lm
Fixture flux	166lm
Luminous efficacy	50lm/W



	-		H(m)	D(m)	Emax(lx)
	-			10°	
Fixture Power	3W	1		0.18	3834
Source Flux	191lm	2		0.35	958
Fixture Flux	166lm	3		0.53	426
Efficacy	50lm/W	4		0.71	240
TS1664 Imax=20066cd/klm	Imax	3834cd	5	0.88	153

BLUE

Fixture Power	2.9W
Nominal flux	37lm
Fixture flux	32lm
Luminous efficacy	11lm/W



	-		H(m)	D(m)	Emax(lx)
	-			10°	
Fixture Power	3W	1		0.18	747
Source Flux	37lm	2		0.35	187
Fixture Flux	32lm	3		0.53	83
Efficacy	11lm/W	4		0.71	47
TS1664 Imax=20066cd/klm	Imax	747cd	5	0.88	30

TARGETTI

CCIAA Firenze
Share Capital: € 500.000,00
VAT N. (IT): 01537660480
R.E.A: FI-275656

Targetti Sankey S.r.l.
Via Giuseppe Garibaldi, 82
50041 Calenzano (FI)
Italy


Tel: +39 055 37911
targetti.com
targetti@targetti.com

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.
Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.

Related codes

Power Supply




CODE
1E3883

DMX 4 channel driver - 850mA.
50W, LxHxP=220x80x120mm, 120-277Vac.
IP68 gray powder coated aluminum box.

Accessories


Filter



CODE	COLOUR
1E4002	

Blade of light filter.
PMMA holographic filter for a blade of light effect.
Completed with powder coated aluminum alloy holder ring.


Grid



CODE	COLOUR
1E4005	

Anti-glare louver.
The central elements can be adjusted +/- 60° for a perfect glare control.
Powder coated stainless steel.

Screen




CODE	COLOUR
1E4003	

Asymmetric screen.
Powder coated stainless steel.



CODE	COLOUR
1E4004	

Cylindrical screen.
Powder coated stainless steel.
Short version.



CODE	COLOUR
1E4057	

Cylindrical screen.
Powder coated stainless steel.
Long version.

Mounting System



CODE	COLOUR
1E3015	

Plate for fixture rotation.
Powder coated stainless steel.



CODE	COLOUR	ØXH
1E3016		70x182mm

Earthspike.
Powder coated stainless steel.

Control systems



CODE

1E2767

USB-RDM Programmer code.
DMX-RDM (Remote Device Management) address planner.
Used with the "RDM Targetti" software that can be downloaded for free from the Targetti website download section.
To be used with all RGBW products.
The USB-RDM programmer manages to direct DMX-RDM fixtures if there are no BUFFER or Splitter DMXs on the section.
Please refer to the instructions for more details.



CODE

A077

my-SCENARIO Show Store.
Programmable DMX interface that integrates the latest innovations in lighting control in architectural and entertainment applications.
It features USB Type-C and Ethernet ports for programming and remote control.
The unit can be fully programmed with ESA Pro 2 software (available for Windows and Mac users) or via mobile applications such as Arcolis (available for iOS or Android devices).
It can be fully customised: pixel mapping, triggering management, patch configuration and much more.
The system offers great possibilities for the control of your lighting installation: multi zone control (allowing the management of up to 5 indipendent zones), extended triggers (time/date, Sunrise/Sunset, input ports, TCP/UDP commands), 16-bit channels management, full recovery after power loss, up to 99 total scenes, and 1024+ DMX channels.
The intuitive backlit keyboard comes with 10 preset buttons for a user friendly experience.



CODE

1T6499

myScenario Wall.
DMX controller with a glass touch sensitive screen for architectural applications.
It can control two different DMX universes (2x 512 channels).
Stand alone function or connected to a computer using a USB port.
Software for creating scenarios (that can be downloaded from the Targetti website) included.
It can manage 10 different lighting zones and 50 scenarios per zone.
The touch keys on the front make it possible to modify and recall programmed scenarios.
USB cable included.
To be used with all RGBW products.

TARGETTI

CCIAA Firenze
Share Capital: € 500.000,00
VAT N. (IT): 01537660480
R.E.A: FI-275656

Targetti Sankey S.r.l.
Via Giuseppe Garibaldi, 82
50041 Calenzano (FI)
Italy

Tel: +39 055 37911
targetti.com
targetti@targetti.com

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.
Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.