

TRACK PROJECTORS

Zeno 180

Code

T037SPH930ELPW

| LIGHT COLOUR         | LIGHT DISTRIBUTION | OUTPUT          |
|----------------------|--------------------|-----------------|
| 3000K<br>90          | SP<br>17°          | 41.6W<br>2743lm |
| POWER SUPPLY CONTROL | COLOUR             |                 |
| 220-240Vac<br>ON-OFF |                    |                 |



The figures on the drawing are expressed in mm.

|                                                                                      |               |                              |                  |                       |       |      |
|--------------------------------------------------------------------------------------|---------------|------------------------------|------------------|-----------------------|-------|------|
|  | 3000K         | H(m)                         | D(m)             | E <sub>max</sub> (lx) |       |      |
|                                                                                      | Ra90          |                              | 17°              |                       |       |      |
|                                                                                      | Fixture Power | 42W                          | 1                | 0.30                  | 26079 |      |
|                                                                                      | Source Flux   | 4853lm                       | 2                | 0.60                  | 6520  |      |
|                                                                                      | Fixture Flux  | 2743lm                       | 3                | 0.89                  | 2898  |      |
|                                                                                      | Efficacy      | 66lm/W                       | 4                | 1.19                  | 1630  |      |
|                                                                                      | TS1228        | I <sub>max</sub> =5374cd/klm | I <sub>max</sub> | 26079cd               | 5     | 1.49 |

Technical Data

Concept

Professional adjustable LED projector.

Source

High efficiency Chip on Board LED Ra90. Ra97 on request.

|                         |                 |
|-------------------------|-----------------|
| Energy efficiency class | E               |
| Nominal power           | 36W             |
| Nominal flux            | 4853lm          |
| Colour rendering index  | 90              |
| R <sub>f</sub>          | 92              |
| R <sub>g</sub>          | 101             |
| CCT nominal             | 3000K           |
| Lifetime (L80/B10)      | 72000h tq +25°C |
| Lifetime (L90/B10)      | 72000h tq +25°C |

TARGETTI

CCIAA Firenze  
Share Capital: € 500.000,00  
VAT N. (IT): 01537660480  
R.E.A: FI-275656

Targetti Sankey S.r.l.  
Via Giuseppe Garibaldi, 82  
50041 Calenzano (FI)  
Italy  
  
Tel: +39 055 37911  
targetti.com  
targetti@targetti.com

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.  
Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).  
  
We reserve the right to make technical changes.

## Technical Data

### Illuminotechnical characteristics

Spot version with hybrid optics composed of a specular anodised aluminium reflector, an optical glass lens, a black anodised aluminium lens holder and a PMMA holographic screen.

|                        |                                   |
|------------------------|-----------------------------------|
| Optic                  | SP                                |
| Beam angles            | SP                                |
| Optical efficiency     | 56.51%                            |
| Fixture flux           | 2743lm                            |
| Luminous efficacy      | 66lm/W                            |
| Photobiological safety | Compliant with RG1 low risk group |

### Mechanical characteristics

Die-cast painted aluminium optical unit. The optical unit can be adjusted from 0 to -90° on the vertical plane; and 355° on the horizontal plane with aiming blocking system.

|                      |               |
|----------------------|---------------|
| Colour and finish    | Plaster white |
| Dimensions           | ØxH 184x85mm  |
| Weight               | 1.5Kg         |
| Degree of protection | IP20          |

### Electrical characteristics

ON-OFF electronic driver integrated into the track adapter.

|                          |                    |
|--------------------------|--------------------|
| Fixture Power            | 41.6W              |
| Power supply             | 220-240Vac 50/60Hz |
| Insulation Class         | CLASS 2            |
| Type of driver / Control | ON-OFF             |
| Driver included          | YES                |
| Ambient temperature      | 0°C / +25°C        |

### Installation

Electrified track mounting. Mechanical and optic accessories available, to be installed with holder ring (necessary).

### Notes

110-277Vac version available on request.

### Warranty

5 years.

### Warning

Luminaire designed for disposal/recycling at end-of-life. Replaceable (LED only) light source by a professional. Replaceable control gear by a professional.

# TARGETTI

CCIAA Firenze  
Share Capital: € 500.000,00  
VAT N. (IT): 01537660480  
R.E.A: FI-275656

Targetti Sankey S.r.l.  
Via Giuseppe Garibaldi, 82  
50041 Calenzano (FI)  
Italy


Tel: +39 055 37911  
targetti.com  
targetti@targetti.com

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.  
Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.

## Accessories

## Filter



## CODE

1T6054

Blade of light filter.  
Methacrylate holographic filter.  
This makes the beam take on an oval shape and when combined with spotlights, the light blade appears more prominent.  
To be completed with a dedicated holder ring.

It cannot be used with NSP and Wall Washer optics.

## Grid



## CODE

1T6055

## COLOUR



Anti-glare louver.  
Black lacquered aluminium honeycomb structure.  
To be completed with a dedicated holder ring.

It cannot be used with NSP and Wall Washer optics.

## Cut-off



## CODE

1T6056

## COLOUR



Black painted steel cut-off.  
To be completed with a dedicated holder ring.

It cannot be used with NSP and Wall Washer optics.



## CODE

1T6057

## COLOUR



Black painted steel asymmetric cut-off.  
To be completed with a dedicated holder ring.

It cannot be used with NSP and Wall Washer optics.

## Ray Shade



## CODE

1T6058

## COLOUR



Adjustable barn doors flaps made of black painted steel.  
To be completed with a dedicated holder ring.

They cannot be used with NSP and Wall Washer optics.

## Holder Ring



## CODE

1T6053

## COLOUR



Black painted aluminium accessory holder ring.