

LIGHTING SYSTEMS


Oz Power Track

Code
1T7435

POWER SUPPLY
CONTROL

48Vdc

COLOUR



The figures on the drawing are expressed in mm.



Technical Data

Concept

Power Track with 2 low voltage conductors.

Mechanical characteristics

Black polycarbonate Power Track with 2 stainless steel tracks that feed electricity to the fixture and provide magnetic field support. Different configurations are possible with more Power Tracks using special connections that make it possible to build a simple system that is also versatile and safe for all project needs.

Colour and finish	Deep black
Dimensions	AxBxH 2000x27x6mm
Weight	0.694Kg
Version	Power Track
Degree of protection	IP20

Electrical characteristics

Power feed possible using a remote power supply with an electrification device on the magnetic Power Track or using an integrated power supply in a special magnetic box applied directly to the Power Track.

Power supply	48Vdc
Insulation Class	CLASS 3
Driver included	NO

TARGETTI

CCIAA Firenze
Share Capital: € 500.000,00
VAT N. (IT): 01537660480
R.E.A: FI-275656

Targetti Sankey S.r.l.
Via Giuseppe Garibaldi, 82
50041 Calenzano (FI)
Italy

Tel: +39 055 37911
targetti.com
targetti@targetti.com

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.
Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.

Technical Data

Installation

Length 2m, to be installed in the following ways: - wall/ceiling mounted Power Track can be installed using screws; - the suspension, ceiling, recessed and trimless Power Track to be inserted into a special profile to be ordered separately.

Warranty

5 years.

Warning

Luminaire designed for disposal/recycling at end-of-life.

TARGETTI

CCIAA Firenze
Share Capital: € 500.000,00
VAT N. (IT): 01537660480
R.E.A: FI-275656

Targetti Sankey S.r.l.
Via Giuseppe Garibaldi, 82
50041 Calenzano (FI)
Italy


Tel: +39 055 37911
targetti.com
targetti@targetti.com

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.
Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.

Related codes

End Caps



CODE	COLOUR
------	--------

1T7027	●
--------	---

Kit containing 2 profile end caps.


Power Supply



CODE	COLOUR	LXHXP
------	--------	-------

1T7025	●	71x27x25mm
--------	---	------------

Power head.




CODE	COLOUR	VERSION	LXHXP
------	--------	---------	-------

1T9604DD	●	REMOTE DIMM	71x27x26mm
----------	---	-------------	------------

1T9605DD	●	DIMM ON BOARD	71x27x26mm
----------	---	---------------	------------


Digital dimming power head.



CODE	COLOUR	DRIVER
------	--------	--------

1T7029EL	●	ON-OFF
----------	---	--------


48Vdc driver box with magnetic coupling.
LxHxP=240x54x26mm, 90W.



CODE	COLOUR	DRIVER
------	--------	--------

1T7172EL	●	ON-OFF
----------	---	--------

48Vdc driver box for ceiling installation.
Complete with 2.5m of cable.
LxHxP=243x58x30mm, 90W.



CODE	IP	OUTPUT VOLTAGE	POWER SUPPLY	POWER	LXHXP
1T6917EL	IP20	48Vdc	220-240Vac	60W	225x36x60mm
1T6916EL	IP20	48Vdc	220-240Vac	130W	240x49x60mm
1T7403EL	IP67	48Vdc	110-277Vac	210W	251x37x90mm

Electronic ON-OFF power supply.

TARGETTI

CCIAA Firenze
Share Capital: € 500.000,00
VAT N. (IT): 01537660480
R.E.A: FI-275656

Targetti Sankey S.r.l.
Via Giuseppe Garibaldi, 82
50041 Calenzano (FI)
Italy


Tel: +39 055 37911
targetti.com
targetti@targetti.com

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.
Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.

Accessories

Electrical Connector




CODE

COLOUR

1T7020



Linear electrical connector.
5 the maximum joints for each driver source.




CODE

COLOUR

1T7021



Electrical L connector.
5 the maximum joints for each driver source.




CODE

COLOUR

1T7022



Electrical T connector.
5 the maximum joints for each driver source.




CODE

COLOUR

1T7023



Electrical X connector.
5 the maximum joints for each driver source.



CODE

COLOUR

1T9525



Adjustable 2 way electric connector.
Using a special accessory element it is possible to connect up to 8 Power Tracks.



CODE

COLOUR

1T9580



Accessory element for adjustable electric connector (1T9524 and 1T9525).



CODE

COLOUR

1T7440



L-angle electrical coupling.
5 the maximum joints for each driver source.

TARGETTI

CCIAA Firenze
Share Capital: € 500.000,00
VAT N. (IT): 01537660480
R.E.A: FI-275656

Targetti Sankey S.r.l.
Via Giuseppe Garibaldi, 82
50041 Calenzano (FI)
Italy


Tel: +39 055 37911
targetti.com
targetti@targetti.com

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.
Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.

Accessories

Mounting System



CODE

COLOUR

1T9593



L shaped support that offers the possibility to attach modules to the Power Track at 90°. The support allows for zenithal lighting for example when the power track is installed on the wall.

Only for single 25x25mm light modules.

Cover Panel



CODE

COLOUR

L


1T7942



2000mm

Cover for Power Track (5 pieces).


Mounting System



CODE

1T7098

Double-sided adhesive roller, 10m long, for fixing Power Track on any surface.




CODE

1T9523

Bracket for ceiling installation of the Power Track in modular suspended ceilings.

Control systems



CODE

1T9594D

1-10V (DIMM ON BOARD) controller for remote installation.

Each 1-10V controller can drive several products for a maximum of 96W per circuit.



CODE

1T8173CA

Bridge DALI/Casambi: a fixture that allows fixtures equipped with mesh Bluetooth Casambi to interface with a traditional DALI system and to be adjusted by a DALI control unit. Inside the usual DALI circuit it is possible to have a maximum of 64 cabled DALI and Casambi wireless devices.

It only works with Casambi Evolution networks.

The DALI Bridge is transparent in the DALI system, and therefore does not require an address.

There is no need for a power supply given that it is supplied directly by the DALI bus.

To provide IP68 rating to the fixture complete with code 1E3184.

LxHxP=40.4x14x36.3mm.

TARGETTI

CCIAA Firenze
Share Capital: € 500.000,00
VAT N. (IT): 01537660480
R.E.A: FI-275656

Targetti Sankey S.r.l.
Via Giuseppe Garibaldi, 82
50041 Calenzano (FI)
Italy

Tel: +39 055 37911
targetti.com
targetti@targetti.com

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.
Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.