


PROJECTORS

Jedi Compact
Outdoor Projector -
Remote driver - L.
873,5mm

Code
1E3817

LIGHT COLOUR	LIGHT DISTRIBUTION	OUTPUT
3500K 80	SP 11°	35W 3982lm
POWER SUPPLY CONTROL	COLOUR	
500mA		



The figures on the drawing are expressed in mm.



	3500K	H(m)	D(m)	E _{max} (lx)		
	Ra80		11°			
	Fixture Power	35W	1	0.20	61210	
	Source Flux	4806lm	2	0.40	15302	
	Fixture Flux	3982lm	3	0.59	6801	
	Efficacy	114lm/W	4	0.79	3826	
TS1340	I _{max} =12736cd/klm	I _{max}	61210cd	5	0.99	2448

Technical Data

Concept

Adjustable linear LED projector.

TARGETTI

CCIAA Firenze
Share Capital: € 500.000,00
VAT N. (IT): 01537660480
R.E.A: FI-275656

Targetti Sankey S.r.l.
Via Giuseppe Garibaldi, 82
50041 Calenzano (FI)
Italy

Tel: +39 055 37911
targetti.com
targetti@targetti.com

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.
Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.

Technical Data

Source

High Power High Efficiency Ra80 linear LED board. Ra90 on request.

Energy efficiency class	E
Nominal power	35W
Nominal flux	4806lm
Colour rendering index	80
Rf	85
Rg	99.5
CCT nominal	3500K
SDCM	3
Lifetime (L80/B10)	100000h tq +25°C
Lifetime (L90/B10)	100000h tq +25°C

Illuminotechnical characteristics

Acrylic lenses with an integrated holographic filter.

Optic	SP
Beam angles	SP
Optical efficiency	82.86%
Fixture flux	3982lm
Luminous efficacy	114lm/W
Photobiological safety	Compliant with RG1 low risk group

Mechanical characteristics

Extruded anodised aluminium 15μ body. Extra clear 5mm thick glass flat screen. The body of the fixture is adjustable and can be installed away from the mounting surface using accessory snap brackets.

Colour and finish	Aluminium
Dimensions	AxBxH 874x53x43mm
Weight	2.5Kg
Version	Remote driver
Degree of protection	IP66,IP67
Mechanical Resistance	IK08

Electrical characteristics

Remote driver version. The optical unit is pre-cabled with a 1 metre 3x1mm² H07RN-F cable. Electronic ON-OFF or DALI power supply, pre-cabled with a 1 metre 3x1mm² H07RN-F cable for the connection to the optical unit and a 3x1mm² or 5x1mm² cable for the connection to the mains and to the DALI.

Fixture Power	35W
Power supply	500mA
Insulation Class	CLASS 1
Driver included	NO
Ambient temperature	-25°C / +35°C

TARGETTI

CCIAA Firenze
Share Capital: € 500.000,00
VAT N. (IT): 01537660480
R.E.A: FI-275656

Targetti Sankey S.r.l.
Via Giuseppe Garibaldi, 82
50041 Calenzano (FI)
Italy

Tel: +39 055 37911
targetti.com
targetti@targetti.com

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.
Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.

Technical Data

Installation

To be completed with stainless steel adjustable brackets.

Notes

Casambi control system available as an accessory (only for DALI versions). Uses the "Waterblock Smart" technical solution that involves resin coating the connection cables, limiting the risk of humidity reaching the driver or the fixture. 110-277Vac version available on request. Values related to the power consumption of the fixture do not take into account the consumption of the accessory driver, which depends on the choice of driver. Commissioning of the control system via free APP; the intervention of a specialist technician can be quoted on request.

Warranty

5 years.

Warning

Luminaire designed for disposal/recycling at end-of-life. Replaceable (LED only) light source by a professional.

TARGETTI

CCIAA Firenze
Share Capital: € 500.000,00
VAT N. (IT): 01537660480
R.E.A: FI-275656

Targetti Sankey S.r.l.
Via Giuseppe Garibaldi, 82
50041 Calenzano (FI)
Italy


Tel: +39 055 37911
targetti.com
targetti@targetti.com

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.
Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.

Related codes


Bracket



CODE

1E3304

Stainless steel short bracket kit for surface installation (2 pieces).
Rotation +/-90°.



CODE

1E3306

Stainless steel long bracket kit for surface installation (2 pieces).
Rotation +/-90°.

Power Supply



CODE

1E3558

ON-OFF power supply kit made of an aluminium watertight box (LxHxP=486x49.5x44mm) complete with power supply input cable (1 metre, type H07RN8-F, 3G1mm²) and an output cable to the fixture (1 metre, type H07RN8-F, 3G1mm²).
For the L 593.5/625/873.5/905/1153.5/1185mm versions.



CODE

1E3560

DALI power supply version kit composed of an aluminium watertight box (LxHxP=486x49.5x44mm) complete with power supply input cable (1 metre, type H07RN8-F, 5G1mm²) and an output cable to the fixture (1 metre, type H07RN8-F, 3G1mm²).
For the L 873.5/905/1153.5/1185mm versions.

Accessories

Grid



CODE

1E3902

COLOUR

●

P

57mm

H

48mm

L

840mm

Symmetric grid in stainless steel, powder-painted.
External mounting respect to fixture.
To be used with SPOT, FLOOD and GRAZING optics.



CODE

1E3906

COLOUR

●

P

57mm

H

48mm

L

840mm

Asymmetric grid in stainless steel, powder-painted.
External mounting respect to fixture.

Ray Shade



CODE

1E3910

COLOUR

●

P

59mm

H

48mm

L

850mm

Hood in stainless steel, powder-painted.
External mounting respect to fixture.

CCIAA Firenze
Share Capital: € 500.000,00
VAT N. (IT): 01537660480
R.E.A: FI-275656

Italy
Tel: +39 055 37911
targetti.com
targetti@targetti.com

Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.

Accessories

Ray Shade



CODE	COLOUR	H	L
1E3914	●	54mm	856mm

Adjustable hood in stainless steel, powder-painted.
External mounting respect to fixture.

Tool



CODE
1E3305

Tightening wrench for the connector kit.

Connector



CODE
1E2769

Linear connection box IP66/IP68.
5 poles max. wire section 1.5mm².
Cable diameter range from 7 to 12mm.



CODE
1E2494

Multiple connection box IP68.
1 IN - 3 OUT 4 poles max. wire section 2.5mm².
Cable diameter range from 6 to 12mm.



CODE
1E3184

IP68 4-way cable connector (5 pole).

Accessories

Control systems



CODE

1E3048

IP67 wireless control unit with DALI interface.

It generates a local DALI2 bus, enabling a direct connection to a DALI interface LED driver. The module can only be used in a closed system and cannot be connected to an existing DALI network.

The module is wireless controlled using a Casambi app for smartphones and tablets using Bluetooth 5.0 technology.

The devices automatically create an adaptive, robust, and reliable wireless mesh network, allowing for the easy and efficient management of a high number of fixtures.

The control unit is preset to the DALI 1CH profile, meaning the device can control a single DALI driver with broadcast commands.

In addition to the DALI broadcast, other operating modes are available, such as:

- Button (normally open)
- Control unit 0/1-10V
- Control unit DALI Tunable White DT8
- Presence sensor

If different from the preset mode, the desired operating profile must be set directly by the user before coupling the control unit to the Casambi network.

LxHxP=108x28x65mm.



CODE

1E4369

IP67 Extender for wireless control of LED driver with dimming DALI interface based on Casambi technology.

It has a DALI2 output with the capacity to control up to 40 lighting fixtures.

With the addition of a further external BUS DALI power supply it is possible to control up to 64 fixtures.

IP67 Extender is preset to the DALI broadcast profile, meaning all the luminaires connected to it are dimmable at the same level.


In addition to the DALI broadcast other operating modes are available, such as:

- EXTENDER DALI 8CH
- EXTENDER DALI Tunable White
- EXTENDER DALI 4CH
- EXTENDER DALI DT8 Tunable White

If different from the preset mode, the desired operating profile must be set directly by the user before coupling the extender to the Casambi network.

LxHxP=148x40x150mm.

Surge protector



CODE

A013A

Surge protector compatible with CLASS I lighting fixtures.

Operating voltage 230-277Vac.

SPD type 2+3.

Max surge protection 10kV.

CLASS I

IP67