

STRAHLER

Jedi Nova 55 Strahler Side Box Comfort 900

Art.-Nr.
E0553GRH840ELFW

LICHTFARBE	LICHTVERTEILUNG	OUTPUT
4000K 80	Grazing 17° / 74°	34,3W 3441lm
BETRIEBSGERÄT STEUERUNG	FARBE	
220-240Vac ON-OFF		



Alle Daten auf der Maßzeichnung sind in mm angegeben.



The diagram illustrates the light distribution of the TS2139 fixture. It features a central beam with a diameter of 17° and a wider spread of 74°. The beam diameter is 0.30m at 1m height and 3.01m at 2m height. The illuminance (E_{max}) is 6519 lx at 1m and 1630 lx at 2m. The fixture power is 34W, source flux is 5754lm, and fixture flux is 3441lm. The efficacy is 100lm/W. The beam diameter is 0.91m at 3m height and 4.52m at 4m height. The illuminance (E_{max}) is 724 lx at 3m and 407 lx at 4m. The beam diameter is 1.21m at 5m height and 6.02m at 6m height. The illuminance (E_{max}) is 261 lx at 5m and 152 lx at 6m. The beam diameter is 1.52m at 7m height and 7.53m at 8m height. The illuminance (E_{max}) is 152 lx at 7m and 152 lx at 8m. The beam diameter is 1.52m at 9m height and 7.53m at 10m height. The illuminance (E_{max}) is 152 lx at 9m and 152 lx at 10m. The beam diameter is 1.52m at 11m height and 7.53m at 12m height. The illuminance (E_{max}) is 152 lx at 11m and 152 lx at 12m. The beam diameter is 1.52m at 13m height and 7.53m at 14m height. The illuminance (E_{max}) is 152 lx at 13m and 152 lx at 14m. The beam diameter is 1.52m at 15m height and 7.53m at 16m height. The illuminance (E_{max}) is 152 lx at 15m and 152 lx at 16m. The beam diameter is 1.52m at 17m height and 7.53m at 18m height. The illuminance (E_{max}) is 152 lx at 17m and 152 lx at 18m. The beam diameter is 1.52m at 19m height and 7.53m at 20m height. The illuminance (E_{max}) is 152 lx at 19m and 152 lx at 20m. The beam diameter is 1.52m at 21m height and 7.53m at 22m height. The illuminance (E_{max}) is 152 lx at 21m and 152 lx at 22m. The beam diameter is 1.52m at 23m height and 7.53m at 24m height. The illuminance (E_{max}) is 152 lx at 23m and 152 lx at 24m. The beam diameter is 1.52m at 25m height and 7.53m at 26m height. The illuminance (E_{max}) is 152 lx at 25m and 152 lx at 26m. The beam diameter is 1.52m at 27m height and 7.53m at 28m height. The illuminance (E_{max}) is 152 lx at 27m and 152 lx at 28m. The beam diameter is 1.52m at 29m height and 7.53m at 30m height. The illuminance (E_{max}) is 152 lx at 29m and 152 lx at 30m. The beam diameter is 1.52m at 31m height and 7.53m at 32m height. The illuminance (E_{max}) is 152 lx at 31m and 152 lx at 32m. The beam diameter is 1.52m at 33m height and 7.53m at 34m height. The illuminance (E_{max}) is 152 lx at 33m and 152 lx at 34m. The beam diameter is 1.52m at 35m height and 7.53m at 36m height. The illuminance (E_{max}) is 152 lx at 35m and 152 lx at 36m. The beam diameter is 1.52m at 37m height and 7.53m at 38m height. The illuminance (E_{max}) is 152 lx at 37m and 152 lx at 38m. The beam diameter is 1.52m at 39m height and 7.53m at 40m height. The illuminance (E_{max}) is 152 lx at 39m and 152 lx at 40m. The beam diameter is 1.52m at 41m height and 7.53m at 42m height. The illuminance (E_{max}) is 152 lx at 41m and 152 lx at 42m. The beam diameter is 1.52m at 43m height and 7.53m at 44m height. The illuminance (E_{max}) is 152 lx at 43m and 152 lx at 44m. The beam diameter is 1.52m at 45m height and 7.53m at 46m height. The illuminance (E_{max}) is 152 lx at 45m and 152 lx at 46m. The beam diameter is 1.52m at 47m height and 7.53m at 48m height. The illuminance (E_{max}) is 152 lx at 47m and 152 lx at 48m. The beam diameter is 1.52m at 49m height and 7.53m at 50m height. The illuminance (E_{max}) is 152 lx at 49m and 152 lx at 50m. The beam diameter is 1.52m at 51m height and 7.53m at 52m height. The illuminance (E_{max}) is 152 lx at 51m and 152 lx at 52m. The beam diameter is 1.52m at 53m height and 7.53m at 54m height. The illuminance (E_{max}) is 152 lx at 53m and 152 lx at 54m. The beam diameter is 1.52m at 55m height and 7.53m at 56m height. The illuminance (E_{max}) is 152 lx at 55m and 152 lx at 56m. The beam diameter is 1.52m at 57m height and 7.53m at 58m height. The illuminance (E_{max}) is 152 lx at 57m and 152 lx at 58m. The beam diameter is 1.52m at 59m height and 7.53m at 60m height. The illuminance (E_{max}) is 152 lx at 59m and 152 lx at 60m. The beam diameter is 1.52m at 61m height and 7.53m at 62m height. The illuminance (E_{max}) is 152 lx at 61m and 152 lx at 62m. The beam diameter is 1.52m at 63m height and 7.53m at 64m height. The illuminance (E_{max}) is 152 lx at 63m and 152 lx at 64m. The beam diameter is 1.52m at 65m height and 7.53m at 66m height. The illuminance (E_{max}) is 152 lx at 65m and 152 lx at 66m. The beam diameter is 1.52m at 67m height and 7.53m at 68m height. The illuminance (E_{max}) is 152 lx at 67m and 152 lx at 68m. The beam diameter is 1.52m at 69m height and 7.53m at 70m height. The illuminance (E_{max}) is 152 lx at 69m and 152 lx at 70m. The beam diameter is 1.52m at 71m height and 7.53m at 72m height. The illuminance (E_{max}) is 152 lx at 71m and 152 lx at 72m. The beam diameter is 1.52m at 73m height and 7.53m at 74m height. The illuminance (E_{max}) is 152 lx at 73m and 152 lx at 74m. The beam diameter is 1.52m at 75m height and 7.53m at 76m height. The illuminance (E_{max}) is 152 lx at 75m and 152 lx at 76m. The beam diameter is 1.52m at 77m height and 7.53m at 78m height. The illuminance (E_{max}) is 152 lx at 77m and 152 lx at 78m. The beam diameter is 1.52m at 79m height and 7.53m at 80m height. The illuminance (E_{max}) is 152 lx at 79m and 152 lx at 80m. The beam diameter is 1.52m at 81m height and 7.53m at 82m height. The illuminance (E_{max}) is 152 lx at 81m and 152 lx at 82m. The beam diameter is 1.52m at 83m height and 7.53m at 84m height. The illuminance (E_{max}) is 152 lx at 83m and 152 lx at 84m. The beam diameter is 1.52m at 85m height and 7.53m at 86m height. The illuminance (E_{max}) is 152 lx at 85m and 152 lx at 86m. The beam diameter is 1.52m at 87m height and 7.53m at 88m height. The illuminance (E_{max}) is 152 lx at 87m and 152 lx at 88m. The beam diameter is 1.52m at 89m height and 7.53m at 90m height. The illuminance (E_{max}) is 152 lx at 89m and 152 lx at 90m. The beam diameter is 1.52m at 91m height and 7.53m at 92m height. The illuminance (E_{max}) is 152 lx at 91m and 152 lx at 92m. The beam diameter is 1.52m at 93m height and 7.53m at 94m height. The illuminance (E_{max}) is 152 lx at 93m and 152 lx at 94m. The beam diameter is 1.52m at 95m height and 7.53m at 96m height. The illuminance (E_{max}) is 152 lx at 95m and 152 lx at 96m. The beam diameter is 1.52m at 97m height and 7.53m at 98m height. The illuminance (E_{max}) is 152 lx at 97m and 152 lx at 98m. The beam diameter is 1.52m at 99m height and 7.53m at 100m height. The illuminance (E_{max}) is 152 lx at 99m and 152 lx at 100m. The beam diameter is 1.52m at 101m height and 7.53m at 102m height. The illuminance (E_{max}) is 152 lx at 101m and 152 lx at 102m. The beam diameter is 1.52m at 103m height and 7.53m at 104m height. The illuminance (E_{max}) is 152 lx at 103m and 152 lx at 104m. The beam diameter is 1.52m at 105m height and 7.53m at 106m height. The illuminance (E_{max}) is 152 lx at 105m and 152 lx at 106m. The beam diameter is 1.52m at 107m height and 7.53m at 108m height. The illuminance (E_{max}) is 152 lx at 107m and 152 lx at 108m. The beam diameter is 1.52m at 109m height and 7.53m at 110m height. The illuminance (E_{max}) is 152 lx at 109m and 152 lx at 110m. The beam diameter is 1.52m at 111m height and 7.53m at 112m height. The illuminance (E_{max}) is 152 lx at 111m and 152 lx at 112m. The beam diameter is 1.52m at 113m height and 7.53m at 114m height. The illuminance (E_{max}) is 152 lx at 113m and 152 lx at 114m. The beam diameter is 1.52m at 115m height and 7.53m at 116m height. The illuminance (E_{max}) is 152 lx at 115m and 152 lx at 116m. The beam diameter is 1.52m at 117m height and 7.53m at 118m height. The illuminance (E_{max}) is 152 lx at 117m and 152 lx at 118m. The beam diameter is 1.52m at 119m height and 7.53m at 120m height. The illuminance (E_{max}) is 152 lx at 119m and 152 lx at 120m. The beam diameter is 1.52m at 121m height and 7.53m at 122m height. The illuminance (E_{max}) is 152 lx at 121m and 152 lx at 122m. The beam diameter is 1.52m at 123m height and 7.53m at 124m height. The illuminance (E_{max}) is 152 lx at 123m and 152 lx at 124m. The beam diameter is 1.52m at 125m height and 7.53m at 126m height. The illuminance (E_{max}) is 152 lx at 125m and 152 lx at 126m. The beam diameter is 1.52m at 127m height and 7.53m at 128m height. The illuminance (E_{max}) is 152 lx at 127m and 152 lx at 128m. The beam diameter is 1.52m at 129m height and 7.53m at 130m height. The illuminance (E_{max}) is 152 lx at 129m and 152 lx at 130m. The beam diameter is 1.52m at 131m height and 7.53m at 132m height. The illuminance (E_{max}) is 152 lx at 131m and 152 lx at 132m. The beam diameter is 1.52m at 133m height and 7.53m at 134m height. The illuminance (E_{max}) is 152 lx at 133m and 152 lx at 134m. The beam diameter is 1.52m at 135m height and 7.53m at 136m height. The illuminance (E_{max}) is 152 lx at 135m and 152 lx at 136m. The beam diameter is 1.52m at 137m height and 7.53m at 138m height. The illuminance (E_{max}) is 152 lx at 137m and 152 lx at 138m. The beam diameter is 1.52m at 139m height and 7.53m at 140m height. The illuminance (E_{max}) is 152 lx at 139m and 152 lx at 140m. The beam diameter is 1.52m at 141m height and 7.53m at 142m height. The illuminance (E_{max}) is 152 lx at 141m and 152 lx at 142m. The beam diameter is 1.52m at 143m height and 7.53m at 144m height. The illuminance (E_{max}) is 152 lx at 143m and 152 lx at 144m. The beam diameter is 1.52m at 145m height and 7.53m at 146m height. The illuminance (E_{max}) is 152 lx at 145m and 152 lx at 146m. The beam diameter is 1.52m at 147m height and 7.53m at 148m height. The illuminance (E_{max}) is 152 lx at 147m and 152 lx at 148m. The beam diameter is 1.52m at 149m height and 7.53m at 150m height. The illuminance (E_{max}) is 152 lx at 149m and 152 lx at 150m. The beam diameter is 1.52m at 151m height and 7.53m at 152m height. The illuminance (E_{max}) is 152 lx at 151m and 152 lx at 152m. The beam diameter is 1.52m at 153m height and 7.53m at 154m height. The illuminance (E_{max}) is 152 lx at 153m and 152 lx at 154m. The beam diameter is 1.52m at 155m height and 7.53m at 156m height. The illuminance (E_{max}) is 152 lx at 155m and 152 lx at 156m. The beam diameter is 1.52m at 157m height and 7.53m at 158m height. The illuminance (E_{max}) is 152 lx at 157m and 152 lx at 158m. The beam diameter is 1.52m at 159m height and 7.53m at 160m height. The illuminance (E_{max}) is 152 lx at 159m and 152 lx at 160m. The beam diameter is 1.52m at 161m height and 7.53m at 162m height. The illuminance (E_{max}) is 152 lx at 161m and 152 lx at 162m. The beam diameter is 1.52m at 163m height and 7.53m at 164m height. The illuminance (E_{max}) is 152 lx at 163m and 152 lx at 164m. The beam diameter is 1.52m at 165m height and 7.53m at 166m height. The illuminance (E_{max}) is 152 lx at 165m and 152 lx at 166m. The beam diameter is 1.52m at 167m height and 7.53m at 168m height. The illuminance (E_{max}) is 152 lx at 167m and 152 lx at 168m. The beam diameter is 1.52m at 169m height and 7.53m at 170m height. The illuminance (E_{max}) is 152 lx at 169m and 152 lx at 170m. The beam diameter is 1.52m at 171m height and 7.53m at 172m height. The illuminance (E_{max}) is 152 lx at 171m and 152 lx at 172m. The beam diameter is 1.52m at 173m height and 7.53m at 174m height. The illuminance (E_{max}) is 152 lx at 173m and 152 lx at 174m. The beam diameter is 1.52m at 175m height and 7.53m at 176m height. The illuminance (E_{max}) is 152 lx at 175m and 152 lx at 176m. The beam diameter is 1.52m at 177m height and 7.53m at 178m height. The illuminance (E_{max}) is 152 lx at 177m and 152 lx at 178m. The beam diameter is 1.52m at 179m height and 7.53m at 180m height. The illuminance (E_{max}) is 152 lx at 179m and 152 lx at 180m. The beam diameter is 1.52m at 181m height and 7.53m at 182m height. The illuminance (E_{max}) is 152 lx at 181m and 152 lx at 182m. The beam diameter is 1.52m at 183m height and 7.53m at 184m height. The illuminance (E_{max}) is 152 lx at 183m and 152 lx at 184m. The beam diameter is 1.52m at 185m height and 7.53m at 186m height. The illuminance (E_{max}) is 152 lx at 185m and 152 lx at 186m. The beam diameter is 1.52m at 187m height and 7.53m at 188m height. The illuminance (E_{max}) is 152 lx at 187m and 152 lx at 188m. The beam diameter is 1.52m at 189m height and 7.53m at 190m height. The illuminance (E_{max}) is 152 lx at 189m and 152 lx at 190m. The beam diameter is 1.52m at 191m height and 7.53m at 192m height. The illuminance (E_{max}) is 152 lx at 191m and 152 lx at 192m. The beam diameter is 1.52m at 193m height and 7.53m at 194m height. The illuminance (E_{max}) is 152 lx at 193m and 152 lx at 194m. The beam diameter is 1.52m at 195m height and 7.53m at 196m height. The illuminance (E_{max}) is 152 lx at 195m and 152 lx at 196m. The beam diameter is 1.52m at 197m height and 7.53m at 198m height. The illuminance (E_{max}) is 152 lx at 197m and 152 lx at 198m. The beam diameter is 1.52m at 199m height and 7.53m at 200m height. The illuminance (E_{max}) is 152 lx at 199m and 152 lx at 200m. The beam diameter is 1.52m at 201m height and 7.53m at 202m height. The illuminance (E_{max}) is 152 lx at 201m and 152 lx at 202m. The beam diameter is 1.52m at 203m height and 7.53m at 204m height. The illuminance (E_{max}) is 152 lx at 203m and 152 lx at 204m. The beam diameter is 1.52m at 205m height and 7.53m at 206m height. The illuminance (E_{max}) is 152 lx at 205m and 152 lx at 206m. The beam diameter is 1.52m at 207m height and 7.53m at 208m height. The illuminance (E_{max}) is 152 lx at 207m and 152 lx at 208m. The beam diameter is 1.52m at 209m height and 7.53m at 210m height. The illuminance (E_{max}) is 152 lx at 209m and 152 lx at 210m. The beam diameter is 1.52m at 211m height and 7.53m at 212m height. The illuminance (E_{max}) is 152 lx at 211m and 152 lx at 212m. The beam diameter is 1.52m at 213m height and 7.53m at 214m height. The illuminance (E_{max}) is 152 lx at 213m and 152 lx at 214m. The beam diameter is 1.52m at 215m height and 7.53m at 216m height. The illuminance (E_{max}) is 152 lx at 215m and 152 lx at 216m. The beam diameter is 1.52m at 217m height and 7.53m at 218m height. The illuminance (E_{max}) is 152 lx at 217m and 152 lx at 218m. The beam diameter is 1.52m at 219m height and 7.53m at 220m height. The illuminance (E_{max}) is 152 lx at 219m and 152 lx at 220m. The beam diameter is 1.52m at 221m height and 7.53m at 222m height. The illuminance (E_{max}) is 152 lx at 221m and 152 lx at 222m. The beam diameter is 1.52m at 223m height and 7.53m at 224m height. The illuminance (E_{max}) is 152 lx at 223m and 152 lx at 224m. The beam diameter is 1.52m at 225m height and 7.53m at 226m height. The illuminance (E_{max}) is 152 lx at 225m and 152 lx at 226m. The beam diameter is 1.52m at 227m height and 7.53m at 228m height. The illuminance (E_{max}) is 152 lx at 227m and 152 lx at 228m. The beam diameter is 1.52m at 229m height and 7.53m at 230m height. The illuminance (E_{max}) is 152 lx at 229m and 152 lx at 230m. The beam diameter is 1.52m at 231m height and 7.53m at 232m height. The illuminance (E_{max}) is 152 lx at 231m and 152 lx at 232m. The beam diameter is 1.52m at 233m height and 7.53m at 234m height. The illuminance (E_{max}) is 152 lx at 233m and 152 lx at 234m. The beam diameter is 1.52m at 235m height and 7.53m at 236m height. The illuminance (E_{max}) is 152 lx at 235m and 152 lx at 236m. The beam diameter is 1.52m at 237m height and 7.53m at 238m height. The illuminance (E_{max}) is 152 lx at 237m and 152 lx at 238m. The beam diameter is 1.52m at 239m height and 7.53m at 240m height. The illuminance (E_{max}) is 152 lx at 239m and 152 lx at 240m. The beam diameter is 1.52m at 241m height and 7.53m at 242m height. The illuminance (E_{max}) is 152 lx at 241m and 152 lx at 242m. The beam diameter is 1.52m at 243m height and 7.53m at 244m height. The illuminance (E_{max}) is 152 lx at 243m and 152 lx at 244m. The beam diameter is 1.52m at 245m height and 7.53m at 246m height. The illuminance (E_{max}) is 152 lx at 245m and 152 lx at 246m. The beam diameter is 1.52m at 247m height and 7.53m at 248m height. The illuminance (E_{max}) is 152 lx at 247m and 152 lx at 248m. The beam diameter is 1.52m at 249m height and 7.53m at 250m height. The illuminance (E_{max}) is 152 lx at 249m and 152 lx at 250m. The beam diameter is 1.52m at 251m height and 7.53m at 252m height. The illuminance (E_{max}) is 152 lx at 251m and 152 lx at 252m. The beam diameter is 1.52m at 253m height and 7.53m at 254m height. The illuminance (E_{max}) is 152 lx at 253m and 152 lx at 254m. The beam diameter is 1.52m at 255m height and 7.53m at 256m height. The illuminance (E_{max}) is 152 lx at 255m and 152 lx at 256m. The beam diameter is 1.52m at 257m height and 7.53m at 258m height. The illuminance (E_{max}) is 152 lx at 257m and 152 lx at 258m. The beam diameter is 1.52m at 259m height and 7.53m at 260m height. The illuminance (E_{max}) is 152 lx at 259m and 152 lx at 260m. The beam diameter is 1.52m at 261m height and 7.53m at 262m height. The illuminance (E_{max}) is 152 lx at 261m and 152 lx at 262m. The beam diameter is 1.52m at 263m height and 7.53m at 264m height. The illuminance (E_{max}) is 152 lx at 263m and 152 lx at 264m. The beam diameter is 1.52m at 265m height and 7.53m at 266m height. The illuminance (E_{max}) is 152 lx at 265m and 152 lx at 266m. The beam diameter is 1.52m at 267m height and 7.53m at 268m height. The illuminance (E_{max}) is 152 lx at 267m and 152 lx at 268m. The beam diameter is 1.52m at 269m height and 7.53m at 270m height. The illuminance (E_{max}) is 152 lx at 269m and 152 lx at 270m. The beam diameter is 1.52m at 271m height and 7.53m at 272m height. The illuminance (E_{max}) is 152 lx at 271m and 152 lx at 272m. The beam diameter is 1.52m at 273m height and 7.53m at 274m height. The illuminance (E_{max}) is 152 lx at 273m and 152 lx at 274m. The beam diameter is 1.52m at 275m height and 7.53m at 276m height. The illuminance (E_{max}) is 152 lx at 275m and 152 lx at 276m. The beam diameter is 1.52m at 277m height and 7.53m at 278m height. The illuminance (E_{max}) is 152 lx at 277m and 152 lx at 278m. The beam diameter is 1.52m at 279m height and 7.53m at 280m height. The illuminance (E_{max}) is 152 lx at 279m and 152 lx at 280m. The beam diameter is 1.52m at 281m height and 7.53m at 282m height. The illuminance (E_{max}) is 152 lx at 281m and 152 lx at 282m. The beam diameter is 1.52m at 283m height and 7.53m at 284m height. The illuminance (E_{max}) is 152 lx at 283m and 152 lx at 284m. The beam diameter is 1.52m at 285m height and 7.53m at 286m height. The illuminance (E_{max}) is 152 lx at 285m and 152 lx at 286m. The beam diameter is 1.52m at 287m height and 7.53m at 288m height. The illuminance (E_{max}) is 152 lx at 287m and 152 lx at 288m. The beam diameter is 1.52m at 289m height and 7.53m at 290m height. The illuminance (E_{max}) is 152 lx at 289m and 152 lx at 290m. The beam diameter is 1.52m at 291m height and 7.53m at 292m height. The illuminance (E_{max}) is 152 lx at 291m and 152 lx at 292m. The beam diameter is 1.52m at 293m height and 7.53m at 294m height. The illuminance (E_{max}) is 152 lx at 293m and 152 lx at 294m. The beam diameter is 1.52m at 295m height and 7.53m at 296m height. The illuminance (E_{max}) is 152 lx at 295m and 152 lx at 296m. The beam diameter is 1.52m at 297m height and 7.53m at 298m height. The illuminance (E_{max}) is 152 lx at 297m and 152 lx at 298m. The beam diameter is 1.52m at 299m height and 7.53m at 300m height. The illuminance (E_{max}) is 152 lx at 299m and 152 lx at 300m. The beam diameter is 1.52m at 301m height and 7.53m at 302m height. The illuminance (E_{max}) is 152 lx at 301m and 152 lx at 302m. The beam diameter is 1.52m at 303m height and 7.53m at 304m height. The illuminance (E_{max}) is 152 lx at 303m and 152 lx at 304m. The beam diameter is 1.52m at 305m height and 7.53m at 306m height. The illuminance (E_{max}) is 152 lx at 305m and 152 lx at 306m. The beam diameter is 1.52m at 307m height and 7.53m at 308m height. The illuminance (E_{max}) is 152 lx at 307m and 152 lx at 308m. The beam diameter is 1.52m at 309m height and 7.53m at 310m height. The illuminance (E_{max}) is 152 lx at 309m and 152 lx at 310m. The beam diameter is 1.52m at 311m height and 7.53m at 312m height. The illuminance (E_{max}) is 152 lx at 311m and 152 lx at 312m. The beam diameter is 1.52m at 313m height and 7.53m at 314m height. The illuminance (E_{max}) is 152 lx at 313m and 152 lx at 314m. The beam diameter is 1.52m at 315m height and 7.53m at 316m height. The illuminance (E_{max}) is 152 lx at 315m and 152 lx at 316m. The beam diameter is 1.52m at 317m height and 7.53m at 318m height. The illuminance (E_{max}) is 152 lx at 317m and 152 lx at 318m. The beam diameter is 1.52m at 319m height and 7.53m at 320m height. The illuminance (E_{max}) is 152 lx at 319m and 152 lx at 320m. The beam diameter is 1.52m at 321m height and 7.53m at 322m height. The illuminance (E_{max}) is 152 lx at 321m and 152 lx at 322m. The beam diameter is 1.52m at 323m height and 7.53m at 324m height. The illuminance (E_{max}) is 152 lx at 323m and 152 lx at 324m. The beam diameter is 1.52m at 325m height and 7.53m at 326m height. The illuminance (E_{max}) is 152 lx at 325m and 152 lx at 326m. The beam diameter is 1.52m at 327m height and 7.53m at 328m height. The illuminance (E_{max}) is 152 lx at 327m and 152 lx at 328m. The beam diameter is 1.52m at 329m height and 7.53m at 330m height. The illuminance (E_{max}) is 152 lx at 329m and 152 lx at 330m. The beam diameter is 1.52m at 331m height and 7.53m at 332m height. The illuminance (E_{max}) is 152 lx at 331m and 152 lx at 332m. The beam diameter is 1.52m at 333m height and 7.53m at 334m height. The illuminance (E_{max}) is 152 lx at 333m and 152 lx at 334m. The beam diameter is 1.52m at 335m height and 7.53m at 336m height. The illuminance (E_{max}) is 152 lx at 335m and 152 lx at 336m. The beam diameter is 1.52m at 337m height and 7.53m at 338m height. The illuminance (E_{max}) is 152 lx at 337m and 152 lx at 338m. The beam diameter is 1.52m at 339m height and 7.53m at 340m height. The illuminance (E_{max}) is 152 lx at 339m and 152 lx at 340m. The beam diameter is 1.52m at 341m height and 7.53m at 342m height. The illuminance (E_{max}) is 152 lx at 341m and 152 lx at 342m. The beam diameter is 1.52m at 343m height and 7.53m at 344m height. The illuminance (E_{max}) is 152 lx at 343m and 152 lx at 344m. The beam diameter is 1.52m at 345m height and 7.53m at 346m height. The illuminance (E_{max}) is 152 lx at 345m and 152 lx at 346m. The beam diameter is 1.52m at 347m height and 7.53m at 348m height. The illuminance (E_{max}) is 152 lx at 347m and 152 lx at 348m. The beam diameter is 1.52m at 349m height and 7.53m at 350m height. The illuminance (E_{max}) is 152 lx at 349m and 152 lx at 350m. The beam diameter is 1.52m at 351m height and 7.53m at 352m height. The illuminance (E_{max}) is 152 lx at 351m and 152 lx at 352m. The beam diameter is 1.52m at 353m height and 7.53m at 354m height. The illuminance (E_{max}) is 152 lx at 353m and 152 lx at 354m. The beam diameter is 1.52m at 355m height and 7.53m at 356m height. The illuminance (E_{max}) is 152 lx at 355m and 152 lx at 356m. The beam diameter is 1.52m at 357m height and 7.53m at 358m height. The illuminance (E_{max}) is 152 lx at 357m and 152 lx at 358m. The beam diameter is 1.52m at 359m height and 7.53m at 360m height. The illuminance (E_{max}) is 152 lx at 359m and 152 lx at 360m. The beam diameter is 1.52m at 361m height and 7.53m at 362m height. The illuminance (E_{max}) is 152 lx at 361m and 152 lx at 362m. The beam diameter is 1.52m at

Technische Daten

Konzept

Linearer ausrichtbarer LED-Einbaustrahler.

Lichtquelle

Lineare Mid-Power-LED-Module mit hoher Effizienz Ra80.

Die Energieeffizienzklasse des Produkts	B
Nennleistung	30.9
Nenn-Lichtstrom	5754lm
Farbwiedergabeindex	80
Ähnliche Farbtemperatur	4000K
Lebensdauer (L80/B10)	100000h tq +25°C
Lebensdauer (L90/B10)	59000h tq +25°C

TARGETTI

CCIAA Firenze
Share Capital: € 500.000,00
USt.-ID. (IT): 01537660480
Handelsregistereintrag: FI-275656

Targetti Sankey S.r.l.
Via Giuseppe Garibaldi, 82
50041 Calenzano (FI)
Italy

Tel: +39 055 37911
targetti.com
targetti@targetti.com

Aus Gründen der technologischen Entwicklung der elektronischen Bauteile unterliegen die aufgeführten Daten eventuellen Aktualisierungen. Daher muss bei der Bestellung eine Bestätigung angefordert werden. Der Lichtstrom und die elektrische Leistung weisen einen Toleranzbereich von +/-10% im Vergleich zum angezeigten Wert auf. Tq bei +25 °C auf (CIE 121).

Technische Änderungen vorbehalten.

Technische Daten

Beleuchtungstechnische Merkmale

Optikeinheit, die aus einer primären zylindrischen PMMA-Linse, einem hochreflektierenden, eloxierten Aluminiumreflektor sowie einer holografischem Filter besteht. Komfortausführung mit integriertem optischem Zubehör: längsgerichtete Entblendungsblende aus schwarz beschichtetem Stahl.

Optik	Grazing
Abstrahlwinkel	GRZ 20°x75°
Optische Effizienz	59,8%
Leuchten-Lichtstrom	3441lm
Lichtausbeute	100lm/W
Fotobiologische Sicherheit	Risikogruppe 1 (RG 1 = geringes Risiko)

Mechanische Merkmale

Gehäuse aus eloxiertem extrudiertem Aluminium 15µ. Flache Abdeckung aus 5mm dickem extra klarem Glas. Gehäuse, dessen Ausrichtung gegenüber der Installationsfläche durch zusätzliche Halterungen variiert werden kann.

Farbe und Oberfläche	Florentinweiß
Abmessungen	AxBxH 868x110x45mm
Gewicht	4,4Kg
Version	Comfort
Schutzart	IP66,IP67,IP68
Mechanische Belastbarkeit	IK07

Elektrische Merkmale

Integrierter Treiber, verfügbar als ON-OFF Version (seitlich am Leuchtengehäuse positioniert). Die Durchgangverkabelung ist mit IN/OUT-Einbausteckverbindern mit Längsabdichtung ausgestattet (Die Abdichtung reduziert das Risiko, dass Feuchtigkeit in Richtung Treiber bzw. Leuchtengehäuse eindringt). Leuchten gemäß EN 60598-2-22 für die Stromversorgung über ein zentrales Notstromsystem CPSS (Central Power Supply System); Bereiche mit hohem Risiko ausgeschlossen. Die voreingestellte Leistungsaufnahme und der voreingestellte Lichtstrom betragen 100% an AC und 100% an DC.

Leistungsaufnahme der Leuchte	34,3W
Betriebsgerät	220-240Vac 50/60Hz
Schutzklasse	SCHUTZKLASSE 1
Treiberart / Steuerung	ON-OFF - PUSH
einschließlich Treiber	JA
SAFE FLICKER	PstLM=<1 und SVM=<0,4 (IEC TR 61547-1 und IEC TR 63158), um ein angenehmeres und sicheres Licht zu garantieren
Umgebungstemperaturen	-25°C / +35°C

Installation

Zu komplettieren mit starren oder verstellbaren Befestigungsbügeln (in verschiedenen Längen verfügbar) aus pulverbeschichtetem Edelstahl.

Hinweise

Die 110-277Vac Version ist auf Anfrage erhältlich.

Garantie

5 Jahre.

TARGETTI

CCIAA Firenze
Share Capital: € 500.000,00
USt.-ID. (IT): 01537660480
Handelsregistereintrag: FI-275656

Targetti Sankey S.r.l.
Via Giuseppe Garibaldi, 82
50041 Calenzano (FI)
Italy

Tel: +39 055 37911
targetti.com
targetti@targetti.com

Aus Gründen der technologischen Entwicklung der elektronischen Bauteile unterliegen die aufgeführten Daten eventuellen Aktualisierungen. Daher muss bei der Bestellung eine Bestätigung angefordert werden. Der Lichtstrom und die elektrische Leistung weisen einen Toleranzbereich von +/-10% im Vergleich zum angezeigten Wert auf. Tq bei +25 °C auf (CIE 121).

Technische Änderungen vorbehalten.

Technische Daten

Hinweise

Leuchte für die Entsorgung/Recycling am Ende der Lebensdauer konzipiert. Austauschbare (nur LED) Lichtquelle durch einen Fachmann. Austauschbare Vorschaltgeräte durch einen Fachmann.

TARGETTI

CCIAA Firenze
Share Capital: € 500.000,00
USt.-ID. (IT): 01537660480
Handelsregistereintrag: FI-275656

Targetti Sankey S.r.l.
Via Giuseppe Garibaldi, 82
50041 Calenzano (FI)
Italy

Tel: +39 055 37911
targetti.com
targetti@targetti.com

Aus Gründen der technologischen Entwicklung der elektronischen Bauteile unterliegen die aufgeführten Daten eventuellen Aktualisierungen. Daher muss bei der Bestellung eine Bestätigung angefordert werden. Der Lichtstrom und die elektrische Leistung weisen einen Toleranzbereich von +/-10% im Vergleich zum angezeigten Wert auf. Tq bei +25 °C auf (CIE 121).

Technische Änderungen vorbehalten.

Artikelnummern für notwendiges Zubehör

Befestigungsbügel



ART.-NR.	FARBE
A108BT	●

Fester Montagebügel-Set aus pulverbeschichtetem Edelstahl für die Aufbauinstallation (2 Stück).



ART.-NR.	FARBE	VERSION	L
A109FW	●	Kurze	57mm

Verstellbarer Montagebügel-Set aus pulverbeschichtetem Edelstahl für die Aufbauinstallation (2 Stück).
Rotation +/-90°.



ART.-NR.	FARBE	VERSION	L
A110FW	●	Mittlere	157mm

Verstellbarer Montagebügel-Set aus pulverbeschichtetem Edelstahl für die Aufbauinstallation (2 Stück).
Rotation +/-90°.



ART.-NR.	FARBE	VERSION	L
A111ZFW	●	Lange	303mm
A111YFW	●	Lange	453mm
A111XFW	●	Lange	603mm

Verstellbarer Montagebügel-Set aus pulverbeschichtetem Edelstahl für die Aufbauinstallation (2 Stück).
Rotation +/-90°.

Befestigungssystem



ART.-NR.	FARBE	H
A112	●	181mm

Erdspeiß.
Rostfreier Edelstahl mit Pulverbeschichtung.
Zu verwenden mit A108, A109, A110.

Zubehör

Verbinder



ART.-NR.
A117

IP66/IP68-Buchse.
5-polig (STANDARD 3G2,5mm² MAX, DALI 5G1,5mm² MAX).
Kabeldurchmesser von 7 bis 12mm.

TARGETTI

CCIAA Firenze
Share Capital: € 500.000,00
USt.-ID. (IT): 01537660480
Handelsregistereintrag: FI-275656

Targetti Sankey S.r.l.
Via Giuseppe Garibaldi, 82
50041 Calenzano (FI)
Italy

Tel: +39 055 37911
targetti.com
targetti@targetti.com

Aus Gründen der technologischen Entwicklung der elektronischen Bauteile unterliegen die aufgeführten Daten eventuellen Aktualisierungen. Daher muss bei der Bestellung eine Bestätigung angefordert werden.
Der Lichtstrom und die elektrische Leistung weisen einen Toleranzbereich von +/-10% im Vergleich zum angezeigten Wert auf. Tq bei +25 °C auf (CIE 121).

Technische Änderungen vorbehalten.

Zubehör

Verbinder



ART.-NR.

A118

Stecker-/Buchsenverbinder-Set IP66/IP68.
5-polig (STANDARD 3G2,5mm² MAX, DALI 5G1,5mm² MAX).
Kabeldurchmesser von 7 bis 12mm.

Kabel



ART.-NR.

L

A120Z

1000mm

A120Y

2000mm

A120X

3000mm

Verbindungsleitung.
Einschließlich 5-poliger Verbindungsstecker.
Für die ON-OFF Version oder DALI.

Blende



ART.-NR.

FARBE

L

A148YFW



868mm

Paraluce estetico e antiabbagliamento in alluminio verniciato.
Versione per proiettore standard e side box.