
LIGHTING SYSTEMS


Logico System - Ceiling/Suspension - Continuous light module - L. 3364mm

Code
1T5765DA90



LIGHT COLOUR	LIGHT DISTRIBUTION	OUTPUT
3000K 90	UGR	91W 6960lm

POWER SUPPLY CONTROL	COLOUR
220-240Vac DALI	



The figures on the drawing are expressed in mm.





3000K		H(m)	D(m)	Emax(lx)
Ra90			72°	
Fixture Power	91W	1	1.45	3116
Source Flux	10540lm	2	2.90	779
Fixture Flux	6960lm	3	4.35	346
Efficacy	76lm/W	4	5.80	195
Imax	3116cd	5	7.26	125

Technical Data

Concept

Linear LED fixture for ceiling mounted or suspension system installation.

Source

LED Engine made of linear LED boards Ra90. Tunable White version available on request.

Energy efficiency class	E
Nominal power	80W
Nominal flux	10540lm
Colour rendering index	90
Rf	91.4
Rg	100.8
CCT nominal	3000K
Lifetime (L80/B10)	100000h tq +25°C
Lifetime (L90/B10)	59000h tq +25°C

TARGETTI

CCIAA Firenze
Share Capital: € 500.000,00
VAT N. (IT): 01537660480
R.E.A: FI-275656

Targetti Sankey S.r.l.
Via Giuseppe Garibaldi, 82
50041 Calenzano (FI)
Italy

Tel: +39 055 37911
targetti.com
targetti@targetti.com

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.
Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.

Technical Data

Illuminotechnical characteristics

Direct/indirect emission. UGR<19 and L65<3000 cd/m² (EN-12464) Controlled light - Optical system composed of a highly reflective brushed aluminium reflector and a transparent polycarbonate screen coupled with a micro prismatic plate and a diffusion filter.

Emission	Direct/Indirect
Optic	UGR
Optical efficiency	66.03%
Fixture flux	6960lm
Luminous efficacy	76lm/W
Photobiological safety	Compliant with RG0 exempt risk group

Mechanical characteristics

White painted extruded aluminium body, available in four different lengths. Magnetic installation system to mount the light unit into the housing complete with an anti-fall safety cable.

Colour and finish	Deep black
Dimensions	AxBxH 3364x60x100mm
Weight	11.8Kg
Version	Linear
Degree of protection	IP20

Electrical characteristics

Integrated DALI power supply. Complete with electrical cables to guarantee feeding continuity (max 2kW for ceiling and recessed versions; max 0,6kW for the suspended version). Emergency Pack available on request. Luminaire compliant with EN 60598-2-22 for power supply from a centralised emergency system CPSS (Central Power Supply System), not incorporated in the luminaire - high risk areas excluded. The default power and flux are 100% in AC and 100% in DC.

Fixture Power	91W
Power supply	220-240Vac 50/60Hz
Insulation Class	CLASS 1
Type of driver / Control	DALI
Driver included	YES
SAFE FLICKER	PstLM=<1 and SVM=<0.4 (IEC TR 61547-1 and IEC TR 63158), to ensure a more comfortable and safe light
Ambient temperature	0°C / +25°C

Installation

For linear configurations complete with a special connector to attach to the power supply. For other configurations accessorise with special X, T and L connectors. To be completed with mounting systems and end caps.

Notes

Casambi control system available using a dedicated accessory. Check mounting instructions to verify the quantity of DALI drivers installed. 110-277Vac version available on request. Commissioning of the control system via free APP; the intervention of a specialist technician can be quoted on request.

Regulations and Certifications

CE

Technical Data

Warranty

5 years.

Warning

Luminaire designed for disposal/recycling at end-of-life. Replaceable (LED only) light source by a professional. Replaceable control gear by a professional.

TARGETTI

CCIAA Firenze
Share Capital: € 500.000,00
VAT N. (IT): 01537660480
R.E.A: FI-275656

Targetti Sankey S.r.l.
Via Giuseppe Garibaldi, 82
50041 Calenzano (FI)
Italy

Tel: +39 055 37911
targetti.com
targetti@targetti.com

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.
Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.

Related codes


End Caps



CODE	COLOUR
1T5938	●

End caps for Ceiling Mounted and Suspension.
2x


Mounting System



CODE	COLOUR
1T6920	●

Wall installation: painted metal bracket.
To be ordered in the following quantities for every fixture length:1 for 281mm version, 2 for the 562 / 1122 / 1682mm version, 3 for the 3364mm version.


Suspension



CODE	COLOUR	L
1T5900	●	2000mm
1T5903	●	4000mm

Suspension cable.
To be ordered in the following quantities for every fixture length:1 for 281mm version, 2 for the 562 / 1122 / 1682mm version, 3 for the 3364mm version, 3 for the L/T version and 4 for the X version.
Suspension cable compatible with ceiling or wall installations, even inclined.

Power Supply Kit




CODE	COLOUR	DRIVER	L
1T5906DA	●	DALI	4000mm

Suspension installation kit: power cable complete with a painted polycarbonate rosette.
Max 0.6kW.

Accessories

Electrical Connector



CODE
1T5911

Linear electrical connector.
EL/DALI.

Control systems



CODE

2T0131

IP20 Extender for wireless control of LED driver with dimming DALI (or 1-10V) interface based on Casambi technology.
It has a DALI2 output with the capacity to control up to 40 lighting fixtures.
With the addition of a further external BUS DALI power supply it is possible to control up to 64 fixtures.
IP20 Extender is preset to the DALI broadcast profile, meaning all the luminaires connected to it are dimmable at the same level.
In addition to the DALI broadcast other operating modes are available, such as:

- EXTENDER DALI 8CH
- EXTENDER DALI Tunable White
- EXTENDER 0/1-10V
- EXTENDER DALI 4CH
- EXTENDER DALI DT8 Tunable White

If different from the preset mode, the desired operating profile must be set directly by the user before coupling the extender to the Casambi network.
LxHxP=130x22x30mm.

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.
Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.