

- RECESSED LUMINAIRES
- CEILING LUMINAIRES
- PENDANT LUMINAIRES
- WALL MOUNTED LUMINAIRES

Threesixty Ø 590mm

- UGR

Code

IT6198DA90

LIGHT COLOUR	LIGHT DISTRIBUTION	OUTPUT
3000K 90	UGR	54W 5227lm
POWER SUPPLY CONTROL	COLOUR	
220-240Vac DALI		



The figures on the drawing are expressed in mm.



Technical Data

Concept

Circular LED fixture for suspension mounted installations.

Source

The LED Engine is made up of self-cooling circular boards. Tunable White version available on request.

Energy efficiency class	E
Nominal power	48W
Nominal flux	6640lm
Colour rendering index	90
R _f	91.4
R _g	100.8
CCT nominal	3000K
Lifetime (L80/B10)	100000h tq +25°C
Lifetime (L90/B10)	59000h tq +25°C

TARGETTI

CCIAA Firenze
Share Capital: € 500.000,00
VAT N. (IT): 01537660480
R.E.A: FI-275656

Targetti Sankey S.r.l.
Via Giuseppe Garibaldi, 82
50041 Calenzano (FI)
Italy

Tel: +39 055 37911
targetti.com
targetti@targetti.com

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.
Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.

Technical Data

Illuminotechnical characteristics

UGR Direct/Indirect Version: Transparent micro prismatic PMMA lower diffusive screen and spreader lens. Diffused indirect emission LED Chip On Board. UGR<19 and L65<3000 cd/m² (EN-12464).

Emission	Direct/Indirect
Optic	UGR
Optical efficiency	78.72%
Fixture flux	5227lm
Luminous efficacy	97lm/W
Photobiological safety	Compliant with RG1 low risk group

Mechanical characteristics

Calendered extruded aluminium body.

Colour and finish	Plaster white
Dimensions	ØxH 590x120mm
Weight	8.2Kg
Degree of protection	IP20 for recessed part
Degree of protection	IP40 for exposed part

Electrical characteristics

Integrated DALI power supply. Emergency Pack available on request. Equipped with a rapid connector for mains connection. Luminaire compliant with EN 60598-2-22 for power supply from a centralised emergency system CPSS (Central Power Supply System), not incorporated in the luminaire - high risk areas excluded. The default power and flux are 100% in AC and 100% in DC.

Fixture Power	54W
Power supply	220-240Vac 50/60Hz
Insulation Class	CLASS 1
Type of driver / Control	DALI - PUSH
Driver included	YES
SAFE FLICKER	PstLM=<1 and SVM=<0.4 (IEC TR 61547-1 and IEC TR 63158), to ensure a more comfortable and safe light
Ambient temperature	0°C / +25°C

Installation

Suspension installation is possible using a special accessory to be ordered separately.

Notes

Casambi control system available using a dedicated accessory. DIRECT/INDIRECT VERSION: Fitted with separate switches. Three different light effects available: direct light, indirect light and mixed direct/indirect light. Check mounting instructions to verify the quantity of DALI drivers installed. 110-277Vac version available on request. Commissioning of the control system via free APP; the intervention of a specialist technician can be quoted on request.

Warranty

5 years.

TARGETTI

CCIAA Firenze
Share Capital: € 500.000,00
VAT N. (IT): 01537660480
R.E.A: FI-275656

Targetti Sankey S.r.l.
Via Giuseppe Garibaldi, 82
50041 Calenzano (FI)
Italy

Tel: +39 055 37911
targetti.com
targetti@targetti.com

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.
Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.

Related codes

Suspension



CODE	COLOUR	L
1T6282		2000mm
1T6285		4000mm

Suspension kit composed of 3 steel cables with an ABS control system.
Suspension kit compatible with ceiling or wall installations, even inclined.

Power Supply Kit



CODE	COLOUR	DRIVER
1T6288DA		DALI

Accessory for suspension installation composed of a canopy and 3 or 5 poles complete with a 4000mm power cable.

Accessories

Control systems



CODE
2T0131

IP20 Extender for wireless control of LED driver with dimming DALI (or 1-10V) interface based on Casambi technology.

It has a DALI2 output with the capacity to control up to 40 lighting fixtures.

With the addition of a further external BUS DALI power supply it is possible to control up to 64 fixtures.

IP20 Extender is preset to the DALI broadcast profile, meaning all the luminaires connected to it are dimmable at the same level.

In addition to the DALI broadcast other operating modes are available, such as:

- EXTENDER DALI 8CH
- EXTENDER DALI Tunable White
- EXTENDER 0/1-10V
- EXTENDER DALI 4CH
- EXTENDER DALI DT8 Tunable White

If different from the preset mode, the desired operating profile must be set directly by the user before coupling the extender to the Casambi network.

LxHxP=130x22x30mm.