

IN-GROUND LUMINAIRES


# Jedi Nova 55

## Recessed Comfort

### 900

Code  
E0573FFL840ELBA

| LIGHT COLOUR         | LIGHT DISTRIBUTION                                                                | OUTPUT          |
|----------------------|-----------------------------------------------------------------------------------|-----------------|
| 4000K<br>80          | FL<br>27°                                                                         | 52.4W<br>3511lm |
| POWER SUPPLY CONTROL | COLOUR                                                                            |                 |
| 220-240Vac<br>ON-OFF |  |                 |



The figures on the drawing are expressed in mm.



### Technical Data

### Concept

Recessed linear LED projector.

### Source

High Power High Efficiency Ra80 linear LED board.

Energy efficiency class

Nominal power 47.2

Nominal flux 7197lm

Colour rendering index 80

CCT nominal 4000K

Lifetime (L80/B10) 100000h tq +25°C

Lifetime (L90/B10) 96000h tq +25°C

TARGETTI

CCIAA Firenze  
Share Capital: € 500.000,00  
VAT N. (IT): 01537660480  
R.E.A: FI-275656

Targetti Sankey S.r.l.  
Via Giuseppe Garibaldi, 82  
50041 Calenzano (FI)  
Italy

Tel: +39 055 37911  
targetti.com  
targetti@targetti.com

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.  
Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.

## Technical Data

### Illuminotechnical characteristics

Optic made of optical grade PMMA TIR lenses and a holographic filter. Comfort version with integrated optical accessory: aluminum honeycomb grid, matte black finish.

|                        |                                   |
|------------------------|-----------------------------------|
| Optic                  | FL                                |
| Beam angles            | FL 30°                            |
| Optical efficiency     | 48.78%                            |
| Fixture flux           | 3511lm                            |
| Luminous efficacy      | 67lm/W                            |
| Photobiological safety | Compliant with RG1 low risk group |

### Mechanical characteristics

Extruded anodised aluminium 15μ body. Extra clear 10mm thick glass flat screen.

|                       |                   |
|-----------------------|-------------------|
| Colour and finish     | Black anodized    |
| Dimensions            | AxBxH 882x65x95mm |
| Weight                | 5Kg               |
| Version               | Comfort           |
| Degree of protection  | IP66,IP67,IP68    |
| Mechanical Resistance | IK10              |

### Electrical characteristics

Integrated driver, available in the ON-OFF version (positioned below the optical body). Supplied with through-wiring with longitudinal sealing IN/OUT panel connectors (the sealing limits the risk of humidity raising towards the driver/optical body). Luminaire compliant with EN 60598-2-22 for power supply from a centralised emergency system CPSS (Central Power Supply System), not incorporated in the luminaire - high risk areas excluded. The default power and flux are 100% in AC and 100% in DC.

|                          |                                                                                                      |
|--------------------------|------------------------------------------------------------------------------------------------------|
| Fixture Power            | 52.4W                                                                                                |
| Power supply             | 220-240Vac 50/60Hz                                                                                   |
| Insulation Class         | CLASS 1                                                                                              |
| Type of driver / Control | ON-OFF - PUSH                                                                                        |
| Driver included          | YES                                                                                                  |
| SAFE FLICKER             | PstLM=<1 and SVM=<0.4 (IEC TR 61547-1 and IEC TR 63158), to ensure a more comfortable and safe light |
| Ambient temperature      | -25°C / +35°C                                                                                        |

### Installation

To be completed with an anodised aluminium insertion box. Continuous in-line installation version available.

### Notes

110-277Vac version available on request. All versions meet the drive-over and walk-over requirements of EN 60598-2-13. IP68: the projector is not suitable for permanent underwater installation but can withstand temporary accidental immersion to a depth of 1.5 metres (max.1h). IP69: IEC/EN 60529 standard compliant.

### Warranty

5 years.

# TARGETTI

CCIAA Firenze  
Share Capital: € 500.000,00  
VAT N. (IT): 01537660480  
R.E.A: FI-275656

Targetti Sankey S.r.l.  
Via Giuseppe Garibaldi, 82  
50041 Calenzano (FI)  
Italy

Tel: +39 055 37911  
targetti.com  
targetti@targetti.com

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.  
Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.

## Technical Data

## Warning

Luminaire designed for disposal/recycling at end-of-life. Replaceable (LED only) light source by a professional.  
Replaceable control gear by a professional.

# TARGETTI

CCIAA Firenze  
Share Capital: € 500.000,00  
VAT N. (IT): 01537660480  
R.E.A: FI-275656

Targetti Sankey S.r.l.  
Via Giuseppe Garibaldi, 82  
50041 Calenzano (FI)  
Italy

Tel: +39 055 37911  
targetti.com  
targetti@targetti.com

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.  
Luminous flux and power supply have +/-10% tolerances with respect to the indicated value.  $t_q +25^{\circ}\text{C}$  (CIE 121).

We reserve the right to make technical changes.

## Related codes

## Insertion Box



| CODE  | VERSION     | P     | H     | L     |
|-------|-------------|-------|-------|-------|
| A113Y | Stand Alone | 100mm | 108mm | 906mm |

Aluminium outer casing for Jedi Nova 55.  
In black anodised aluminum.



| CODE  | VERSION | P     | H     | L     |
|-------|---------|-------|-------|-------|
| A114Y | System  | 100mm | 108mm | 904mm |

Aluminium outer casing for Jedi Nova 55.  
In black anodised aluminum.

## Mounting System



## CODE

A116

Fixing plate kit for A113 and A114 installation sleeves.  
In aluminum.

## Accessories

## Connector



## CODE

A117

IP66/IP68 female connector.  
5 pôles (STANDARD 3G2,5mm<sup>2</sup> MAX, DALI 5G1,5mm<sup>2</sup> MAX).  
Cable diameter range from 7 to 12mm.



## CODE

A118

Male/female IP66/IP68 connector kit.  
5 pôles (STANDARD 3G2,5mm<sup>2</sup> MAX, DALI 5G1,5mm<sup>2</sup> MAX).  
Cable diameter range from 7 to 12mm.



## CODE

A119

Multiple connection box IP68.  
1 IN - 2 OUT 5 poles (STANDARD 3G2,5mm<sup>2</sup> MAX, DALI 5G1,5mm<sup>2</sup> MAX).  
Cable diameter range from 7 to 12mm.

# TARGETTI

CCIAA Firenze  
Share Capital: € 500.000,00  
VAT N. (IT): 01537660480  
R.E.A: FI-275656

Targetti Sankey S.r.l.  
Via Giuseppe Garibaldi, 82  
50041 Calenzano (FI)  
Italy

Tel: +39 055 37911  
targetti.com  
targetti@targetti.com

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.  
Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.

## Accessories

## Cable



| CODE  | L      |
|-------|--------|
| A120Z | 1000mm |
| A120Y | 2000mm |
| A120X | 3000mm |

Connection cable.  
Complete with 5 pole connectors.  
For the ON-OFF and DALI version.

**TARGETTI**

CCIAA Firenze  
Share Capital: € 500.000,00  
VAT N. (IT): 01537660480  
R.E.A: FI-275656

Targetti Sankey S.r.l.  
Via Giuseppe Garibaldi, 82  
50041 Calenzano (FI)  
Italy

Tel: +39 055 37911  
targetti.com  
targetti@targetti.com

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.  
Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.