

DURASTRIP DRIVERS

CHARACTERISTICS

SELV equivalent; protection device in case of short circuit or overload in the secondary circuit.

250W, 80W e 100W IP20 drivers are fit for use inside aluminium profiles (where indicated).



FLICKER FREE



| art. | W | Volt IN | Volt OUT | PF | L1 | L2 | H | 8011905 | |
|------------------|----|---------|----------|-----|-----|----|----|---------|---|
| SLD-50-24 | 50 | 100-240 | 24VDC | 0,9 | 280 | 30 | 17 | 976439 | 1 |
| SLD-80-24 | 80 | 100-240 | 24VDC | 0,9 | 320 | 30 | 17 | 976422 | 1 |



| art. | W | Volt IN | Volt OUT | PF | L | L1 | L2 | 8011905 | |
|-----------------------|-----|---------|----------|-----|-----|------|-----|---------|---|
| ZK73100 ♦ | 100 | 200-240 | I 24VDC | 0,9 | 46 | 39 | 221 | 833329 | 1 |
| ZK73200 ♦ | 200 | 200-240 | I 24VDC | 0,9 | 62 | 37 | 221 | 833336 | 1 |
| ZK73320* ♦ | 320 | 100-240 | I 24VDC | 0,9 | 84 | 41,3 | 246 | 843588 | 1 |
| ZK73600T*(1) ♦ | 600 | 120-240 | I 24VDC | 0,9 | 125 | 45 | 290 | 849894 | 1 |

* Possibility to control output voltage.

♦ To be discontinued



FLICKER FREE



| art. | W | Volt IN | Volt OUT | PF | L1 | L2 | H | 8011905 | |
|---------------------|-----|---------|----------|-----|-----|----|------|---------|---|
| ZK73100-SL ♦ | 100 | 200-240 | 24V DC | 0,9 | 320 | 30 | 18,5 | 843915 | 1 |

♦ To be discontinued

DURASTRIP DRIVERS



FLICKER FREE



| art. | W | Volt IN | Volt OUT | PF | L | L2 | H | 8011905 | |
|------------------------------------|-----|---------|----------|------|-----|-----|------|---------|---|
| XLG-100-24-A | 100 | 100-240 | 24VDC | 0,9 | 140 | 63 | 32 | 976958 | 1 |
| XLG-150-24-A | 150 | 100-240 | 24VDC | 0,9 | 180 | 63 | 35.5 | 976941 | 1 |
| XLG-200-24-A | 200 | 100-240 | 24VDC | 0,9 | 199 | 63 | 35.5 | 976934 | 1 |
| ELG-240-24A-3Y | 240 | 100-240 | 24VDC | 0,9 | 244 | 71 | 38 | 981303 | 1 |
| HLG-320H-24 | 320 | 100-240 | 24VDC | 0,9 | 252 | 90 | 44 | 981297 | 1 |
| HLG-600H-24A | 600 | 100-240 | 24VDC | 0,9 | 280 | 144 | 49 | 976491 | 1 |
| HLG-320H-48A ⁽¹⁾ | 320 | 100-240 | 48VDC | 0,95 | 252 | 90 | 43,8 | 931575 | 1 |