# **DURASTRIP ULTRA HD RGB**

#### LED

LED 3535RGB

●= 615-625nm; ●= 520-530nm; ●= 465-475nm; 240 LED/m

70W (14W/m) 24VDC

Lifetime: >50,000 h Warranty: 5 years

## **COLOURS OF LIGHT**

RGB

## **DIMMABILITY**

Dimmable 0-100% Flicker Free DMX with ZKCDMXFF, ZKCDMX-RFF Analogue and digital domotic control systems CASAMBI compatible

## CONNECTIONS

IP20: terminals with free wires
IP65: complete with a 15 cm long IP65/68 M/F cable on 2 sides.
Maximum connection length 5 m. Max 4A.
Strips can be cut to size by following the cutting indications printed

Strips can be cut to size by following the cutting indications printed on the strips.

#### **ASSEMBLY**

Complete with 3M double sided tape to attach to the surface. When using double sided tape degrease the application surface adequately. Always use with aluminium profiles for heat dissipation.


#### PACKAGE

Packaged in 5 m reels.

Or custom products cut to specific lengths see page 11, 318.

The most powerful RGB strip in the range, 240 LED/m, 3 in 1 3535RGB. This new generation chip is very compact: this allows for optimisation of heat and increases the lifespan ensuring colour stability over time. From a lighting point of view it provides excellent performance in terms of luminous efficiency: ULTRA RGB contributes to meeting the needs of installations that require a decorative impact and applications that demand a strong light supply with high emission uniformity in the best way.

#### LED SPACING AND PITCH CUT



Cutting DURASTRIP to size\*:

fixed cost of piece work



<sup>\*</sup> Please consider pitch cut. Includes a 20 cm cable.

## IP20



#### **IP65**



108 DURASTRIP

# **DURASTRIP ULTRA HD RGB**





IP20

art.	W	W/m		N° LED/m		L	L1	L2	8011905		
07URGB2414INUHD ►	70	14	•••	240	120°	12	2	5000	950200	1	

► Orderable only with MOQ

IP65


art.	W	W/m		N° LED/m		L	L1	L2	8011905		
07URGB2414EXUHD	70	14	•••	240	120°	14	4	5000	953058	1	

■ Limited availability - reorderable only with MOQ



art	Cut and mount kit for Strip IP68 and IP65 - RGB	80119058		
KT68PA-RGB	This kit includes 4 terminal blocks with 15 cm wire, 10 silicone fixing bridges with screws, 10 end caps	955588	1	







For further details on other connection configurations see the connection diagrams on the following pages or at this link.



# DRIVER

70W IP20	SLD-80-24
70W IP65	XLG-100-24-A

# CONTROLLER

7	DALI-ZKTPC (DALI)
	ZKCDAFF (DALI)
	ZKCDMXWFF (DMX)
	<b>ZKC1-10FF</b> (1-10)
	FF = FLICKER FREE

# **PROFILES**

//.	UNIVERSAL PROFILES	
4//	SURFACE PROFILES	
	RECESSED PROFILES	
	FLEXIBLE PROFILES	

DRIVER: complete info on page 161

TARGETTI powered by DURALAMP