RECESSED PROFILES: P02H

CHARACTERISTICS

Reduced width recessed profile with edge protection finishing flaps. Equipped with angle-joint accessory.

CAN BE USED WITH LED STRIPS WITH MAXIMUM WIDTH:

12 mm.

MAXIMUM POWER:

15W/m

MATERIALS

6063 aluminium profile with white PMMA screen.

ACCESSORIES INCLUDED

Every 3 metre bar is complete with 3 sets of end caps (with or without holes) and 3 sets of mounting clips.

INSTALLATION

Recessed. Cabling can be in line with the profile or exit the bottom of the profile.

PACKAGE

IP20

Supplied in packages of 5 bars, each one measuring 3 meters complete with screen and accessories. Available with separate codes: 90° junction bracket as well as spare accessories.

VA04


Cutting	Project	profiles	to	size*:
---------	---------	----------	----	--------

	fixed	cost	of	piece	work	
--	-------	------	----	-------	------	--

* Includes mounting accessories.

24.60 24.60 12.70 17.50





art	Description		L1	Н	L	8011905	Ð
P02H-S-PF-300 +	profile complete with PMMA screen	and accessories	24,6	8,28	3000	912390	1 / 5
MAX 12mm V		e discontinued					
		art	Description			8011905	
		P02H-A-EC +	3+3 PC silver col	our end ca	aps	912406	1
		art	Description			8011905	Ð
	Contraction of the second	P02H-A-MC +	3 sets of metal t	orackets		912413	1
34.00		art	Description			8011905	Ð
	a a a	P02H-A-CP +	3 PC silver colou	r junction	brackets	912420	1
20.80		art	Description			8011905	Ð
	41.60	P02H-A-CP90 +	3 silver colour jun	ction brack	ets with 90° a	angle 912437	1
41.60		◆ To be discont	inued				