RECESSED PROFILES: P07B

CHARACTERISTICS

Recessed profile with gullwing finishing flaps typically used to join two different finishes to an underlying surface.

CAN BE USED WITH LED STRIPS WITH MAXIMUM WIDTH:

12 mm.

MAXIMUM POWER:

10W/m

MATERIALS

6063 aluminium profile with white PMMA screen.

ACCESSORIES INCLUDED

Every 3 metre bar is complete with 3 end caps (with and without hole).

INSTALLATION

Recessed. Cabling can be in line with the profile or exit the bottom of the profile.

PACKAGE


Supplied in packages of 5 bars, each one measuring 3 meters complete with screen and accessories. Spare accessories available with separate code.




fixed cost of piece work

* Includes mounting accessories.









| IP20 | IK10 | | | | | | | |
|-----------------|------|---|----|-------|------|---------|-------|--|
| art | | Description | L1 | Н | L | 8011905 | | |
| P07B-S-PF-300 + | | profile complete with PMMA screen and accessories | 52 | 13,85 | 3000 | 913625 | 1 / 5 | |





◆ To be discontinued



| art | Description | | |
|--------------|--------------|--------|---|
| P07B-A-ECM + | 3+3 end caps | 913632 | 1 |

• To be discontinued

264 PROJECT PROFILES