

# PLASTER-IN ALUMINIUM PROFILES: PRINCG

## CHARACTERISTICS

Anodised aluminium profile for trimmed flush recessed installation and installation in plasterboard. Recessed support along the profile for perfect stability.

## CAN BE USED WITH LED STRIPS WITH MAXIMUM WIDTH:

20 mm.

## MAXIMUM POWER

30W/m

## MATERIALS

6063 aluminium profile with white PMMA screen.

## ACCESSORIES INCLUDED



Every 2 metre bar is complete with 1 set of end caps (with and without hole).

## INSTALLATION

For recessed installation in plasterboard or ceilings with tiles. Cabling can be in line with the profile or exit the bottom of the profile.

## PACKAGE

Supplied in packages of 7 bars, each one measuring 2 meters complete with screen and accessories. Spare accessories for additional cutting available with a separate code.



Cutting Project profiles to size\*:

fixed cost of piece work

VA04


\* Includes mounting accessories.

IP20	IK10
------	------

art	Description	L1	H	L	8011905	
<b>PRINCG</b> ♦	profile complete with PMMA screen and accessories	64	15,5	2000	844738	1/7



♦ To be discontinued



art	Description	8011905	
<b>KTPRINCG</b> ♦	2 metal end caps	844790	1

♦ To be discontinued